



# PRW STEEL

*Product Catalog*

**P.R.W. Steel Supply, Inc. • Paso Robles Welding**  
2905 Union Road, Paso Robles CA 93446  
(805) 239-1688 • (800) 439-1694 Toll Free • (805) 239-5753 Fax  
**[www.prwsteel.com](http://www.prwsteel.com)**



# Index



## Grating

Bar ..... 61

Cat Walk ..... 61

Grip Strut ..... 62



Pipe ..... 37



## Plates

Abrasion Resisting ..... 30

Aluminum ..... 73

High Strength ..... 31-32

Hot Rolled ..... 27-29

Pickled & Oiled ..... 23

Stainless Annealed & Pickled ..... 68



Rebar ..... 13



## Redi Rod

Carbon Steel Rod Oil Finish ..... 14

Electro Zinc Plated ..... 14

Stainless ..... 14

## Tubing



Square ..... 38-39



Rectangle..... 39-40



Pipe-Size..... 41



Round..... 42



Round Mechanical..... 43-57



## Rounds

Cold Rolled ..... 15-16

Galvanized ..... 12

Hot Rolled ..... 12

Stainless ..... 63

Turned Ground and Polished ..... 16

## Stainless



Angle ..... 63



Annealed & Pickled Plates ..... 68



Annealed & Pickled Sheets ..... 67



Channel ..... 63



Expanded Metal ..... 66



Flats ..... 64



Pipe ..... 65



Plates ..... 68



Polished Sheets ..... 67



Rectangle Tubing ..... 66



Redi Rod ..... 14



Round ..... 63



Sheets ..... 67



Square Tubing ..... 66



Squares ..... 63



Strips ..... 64

# Index

|                                          |       |
|------------------------------------------|-------|
| AISI Carbon Steel Tolerance Ranges ..... | 21    |
| Carbon Pipe Schedules .....              | 36    |
| Decimal Conversion Table .....           | 75    |
| Fabrication .....                        | 78-82 |
| Glossary of Terms .....                  | 76-77 |

# Beams

ASTM A-36

## I Beams



| A    |       |        |           | B         | C            |
|------|-------|--------|-----------|-----------|--------------|
| Size | WT/FT | Length | WT/Length | Web Thick | Flange Width |
| 3"   | 5.70  | 20'    | 114.00    | 0.170     | 2.330        |
| 4"   | 7.70  | 20'    | 154.00    | 0.193     | 2.663        |
| 4"   | 7.70  | 40'    | 308.00    | 0.193     | 2.663        |
| 5"   | 10.00 | 20'    | 200.00    | 0.214     | 3.004        |
| 5"   | 10.00 | 40'    | 400.00    | 0.214     | 3.004        |
| 6"   | 12.50 | 20'    | 250.00    | 0.232     | 3.332        |
| 6"   | 12.50 | 40'    | 500.00    | 0.232     | 3.332        |
| 7"   | 15.30 | 20'    | 306.00    | 0.252     | 3.662        |
| 8"   | 18.40 | 20'    | 368.00    | 0.271     | 4.001        |
| 8"   | 18.40 | 40'    | 736.00    | 0.271     | 4.001        |
| 10"  | 25.40 | 20'    | 508.00    | 0.311     | 4.661        |
| 10"  | 25.40 | 40'    | 1016.00   | 0.311     | 4.661        |
| 12"  | 31.80 | 20'    | 636.00    | 0.350     | 5.000        |
| 12"  | 31.80 | 40'    | 1272.00   | 0.350     | 5.000        |
| 15"  | 42.90 | 40'    | 1716.00   | 0.411     | 5.501        |

I Beams –The edges of the flanges of I beams are tapered in for added strength. They are used for structural purposes and also for hoists and cranes.

## Wide Flange Beams



| A    |       |        |           |       | B         | C            | D            |
|------|-------|--------|-----------|-------|-----------|--------------|--------------|
| Size | WT/FT | Length | WT/Length | Depth | Web Thick | Flange Width | Flange Thick |
| 4"   | 13.00 | 20'    | 260.00    | 4.16  | 0.280     | 4.060        | 0.345        |
| 4"   | 13.00 | 40'    | 520.00    | 4.16  | 0.280     | 4.060        | 0.345        |
| 6"   | 9.00  | 20'    | 180.00    | 5.90  | 0.170     | 3.940        | 0.215        |
| 6"   | 9.00  | 40'    | 360.00    | 5.90  | 0.170     | 3.940        | 0.215        |
| 6"   | 12.00 | 20'    | 240.00    | 6.03  | 0.230     | 4.000        | 0.280        |
| 6"   | 12.00 | 40'    | 480.00    | 6.03  | 0.230     | 4.000        | 0.280        |
| 6"   | 12.00 | 50'    | 600.00    | 6.03  | 0.230     | 4.000        | 0.280        |
| 6"   | 16.00 | 20'    | 320.00    | 6.28  | 0.260     | 4.030        | 0.405        |
| 6"   | 16.00 | 40'    | 640.00    | 6.28  | 0.260     | 4.030        | 0.405        |
| 6"   | 15.00 | 20'    | 300.00    | 5.99  | 0.230     | 5.990        | 0.260        |
| 6"   | 15.00 | 40'    | 600.00    | 5.99  | 0.230     | 5.990        | 0.260        |
| 6"   | 15.00 | 50'    | 750.00    | 5.99  | 0.230     | 5.990        | 0.260        |
| 6"   | 20.00 | 20'    | 400.00    | 6.20  | 0.260     | 6.020        | 0.365        |
| 6"   | 20.00 | 40'    | 800.00    | 6.20  | 0.260     | 6.020        | 0.365        |

Wide Flange Beams –The web on wide flange beams is longer than the width of the flanges. Wide flange beams are used primarily for structural purposes.

H Beams –H beams are symmetrical beams where the dimensions of the height and width are equal or nearly equal. They are used mainly for structural purposes.

ASTM A-36 –Low carbon, structural quality steel used in bridges, building construction, and general structural applications. Minimum Mechanical Properties: (Yield 36,000 psi. min.) (Tensile 58,000 - 80,000 psi.)

## Beams

ASTM A-36




## Wide Flange Beams




## Wide Flange Beams

| Size | WT/FT | Length | WT/Length | A     |           |              |              |
|------|-------|--------|-----------|-------|-----------|--------------|--------------|
|      |       |        |           | Depth | Web Thick | Flange Width | Flange Thick |
| 8"   | 13.00 | 20'    | 260.00    | 7.99  | 0.230     | 4.000        | 0.255        |
| 8"   | 13.00 | 40'    | 520.00    | 7.99  | 0.230     | 4.000        | 0.255        |
| 8"   | 15.00 | 40'    | 600.00    | 8.11  | 0.245     | 4.015        | 0.315        |
| 8"   | 18.00 | 20'    | 360.00    | 8.14  | 0.230     | 5.250        | 0.330        |
| 8"   | 18.00 | 30'    | 540.00    | 8.14  | 0.230     | 5.250        | 0.330        |
| 8"   | 18.00 | 40'    | 720.00    | 8.14  | 0.230     | 5.250        | 0.330        |
| 8"   | 18.00 | 50'    | 900.00    | 8.14  | 0.230     | 5.250        | 0.330        |
| 8"   | 21.00 | 20'    | 420.00    | 8.28  | 0.250     | 5.270        | 0.400        |
| 8"   | 21.00 | 40'    | 840.00    | 8.28  | 0.250     | 5.270        | 0.400        |
| 8"   | 24.00 | 20'    | 480.00    | 7.93  | 0.245     | 6.495        | 0.400        |
| 8"   | 24.00 | 40'    | 960.00    | 7.93  | 0.245     | 6.495        | 0.400        |
| 8"   | 24.00 | 50'    | 1200.00   | 7.93  | 0.245     | 6.495        | 0.400        |
| 8"   | 28.00 | 20'    | 560.00    | 8.06  | 0.285     | 6.535        | 0.465        |
| 8"   | 28.00 | 30'    | 840.00    | 8.06  | 0.285     | 6.535        | 0.465        |
| 8"   | 28.00 | 40'    | 1120.00   | 8.06  | 0.285     | 6.535        | 0.465        |
| 8"   | 31.00 | 20'    | 620.00    | 8.00  | 0.285     | 7.995        | 0.435        |
| 8"   | 31.00 | 40'4"  | 1250.33   | 8.00  | 0.285     | 7.995        | 0.435        |
| 8"   | 31.00 | 50'    | 1550.00   | 8.00  | 0.285     | 7.995        | 0.435        |
| 10"  | 12.00 | 20'    | 240.00    | 9.87  | 0.190     | 3.960        | 0.210        |
| 10"  | 12.00 | 40'    | 480.00    | 9.87  | 0.190     | 3.960        | 0.210        |
| 10"  | 15.00 | 20'    | 300.00    | 9.99  | 0.230     | 4.000        | 0.270        |
| 10"  | 15.00 | 40'    | 600.00    | 9.99  | 0.230     | 4.000        | 0.270        |
| 10"  | 19.00 | 20'    | 380.00    | 10.24 | 0.250     | 4.020        | 0.395        |
| 10"  | 19.00 | 40'    | 760.00    | 10.24 | 0.250     | 4.020        | 0.395        |

| Size | WT/FT | Length | WT/Length | A     |           |              |              |
|------|-------|--------|-----------|-------|-----------|--------------|--------------|
|      |       |        |           | Depth | Web Thick | Flange Width | Flange Thick |
| 10"  | 22.00 | 20'    | 440.00    | 10.17 | 0.240     | 5.750        | 0.360        |
| 10"  | 22.00 | 30'    | 660.00    | 10.17 | 0.240     | 5.750        | 0.360        |
| 10"  | 22.00 | 40'    | 880.00    | 10.17 | 0.240     | 5.750        | 0.360        |
| 10"  | 22.00 | 50'    | 1100.00   | 10.17 | 0.240     | 5.750        | 0.360        |
| 10"  | 54.00 | 20'    | 1080.00   | 10.09 | 0.370     | 10.030       | 0.615        |
| 10"  | 54.00 | 40'4"  | 2178.00   | 10.09 | 0.370     | 10.030       | 0.615        |
| 12"  | 16.00 | 20'    | 320.00    | 11.99 | 0.220     | 3.990        | 0.265        |
| 12"  | 16.00 | 40'    | 640.00    | 11.99 | 0.220     | 3.990        | 0.265        |
| 12"  | 22.00 | 20'    | 440.00    | 12.31 | 0.260     | 4.030        | 0.425        |
| 12"  | 22.00 | 40'    | 880.00    | 12.31 | 0.260     | 4.030        | 0.425        |
| 12"  | 26.00 | 40'    | 1040.00   | 12.22 | 0.230     | 6.490        | 0.380        |
| 12"  | 26.00 | 50'    | 1300.00   | 12.22 | 0.230     | 6.490        | 0.380        |
| 12"  | 30.00 | 20'    | 600.00    | 12.34 | 0.260     | 6.520        | 0.440        |
| 12"  | 30.00 | 40'    | 1200.00   | 12.34 | 0.260     | 6.520        | 0.440        |
| 12"  | 65.00 | 20'    | 1300.00   | 12.12 | 0.390     | 12.000       | 0.605        |
| 12"  | 65.00 | 40'4"  | 2621.67   | 12.12 | 0.390     | 12.000       | 0.605        |
| 14"  | 30.00 | 40'    | 1200.00   | 13.84 | 0.270     | 6.730        | 0.385        |
| 14"  | 30.00 | 50'    | 1500.00   | 13.84 | 0.270     | 6.730        | 0.385        |
| 16"  | 36.00 | 35'    | 1260.00   | 15.86 | 0.295     | 6.985        | 0.430        |
| 16"  | 36.00 | 50'    | 1800.00   | 15.86 | 0.295     | 6.985        | 0.430        |
| 18"  | 40.00 | 40'    | 1600.00   | 17.90 | 0.315     | 6.015        | 0.525        |





## Bar Channel

## Channel

ASTM A-36




## Channel

| A x B x C            |        |         |          |
|----------------------|--------|---------|----------|
| Size                 | Length | WT / FT | WT / Bar |
| 1 x 1/2 x 1/8        | 20'    | 0.840   | 16.80    |
| 1 x 1 x 11 ga.       | 10'    | 1.280   | 12.80    |
| 1-1/4 x 1/2 x 1/8    | 20'    | 1.010   | 20.20    |
| 1-1/2 x 1/2 x 1/8    | 20'    | 1.120   | 22.40    |
| 1-1/2 x 9/16 x 3/16  | 20'    | 1.440   | 28.80    |
| 1-1/2 x 3/4 x 1/8    | 20'    | 1.170   | 23.40    |
| 1-5/8 x 7/8 x 11 ga. | 10'    | 1.200   | 12.00    |
| 2 x 1/2 x 1/8        | 20'    | 1.430   | 28.60    |
| 2 x 9/16 x 3/16      | 20'    | 1.860   | 37.20    |
| 2 x 1 x 1/8          | 20'    | 1.590   | 31.80    |
| 2 x 1 x 3/16         | 20'    | 2.320   | 46.40    |
| 2-1/2 x 5/8 x 3/16   | 20'    | 2.270   | 45.40    |

Formed 1010 Material

| A     |         |        |          | B            | C         |
|-------|---------|--------|----------|--------------|-----------|
| Size  | WT / FT | Length | WT / Bar | Flange Width | Web Thick |
| 3" LC | 3.500   | 20'    | 70.00    | 1.350        | 0.130     |
| 3" LC | 3.500   | 40'    | 140.00   | 1.350        | 0.130     |
| 3"    | 4.100   | 20'    | 82.00    | 1.410        | 0.170     |
| 3"    | 4.100   | 40'    | 164.00   | 1.410        | 0.170     |
| 3"    | 5.000   | 20'    | 100.00   | 1.498        | 0.258     |
| 3"    | 6.000   | 20'    | 120.00   | 1.596        | 0.356     |
| 4"    | 5.400   | 20'    | 108.00   | 1.584        | 0.184     |
| 4"    | 5.400   | 40'    | 216.00   | 1.584        | 0.184     |
| 4"    | 7.250   | 20'    | 145.00   | 1.721        | 0.321     |
| 4"    | 7.250   | 40'    | 290.00   | 1.721        | 0.321     |
| 5"    | 6.700   | 20'    | 134.00   | 1.750        | 0.190     |
| 5"    | 6.700   | 40'    | 268.00   | 1.750        | 0.190     |
| 5"    | 9.000   | 20'    | 180.00   | 1.885        | 0.325     |

ASTM- A36 – Low carbon, structural quality steel used in bridges, building construction, and general structural applications. Minimum Mechanical Properties:  
Yield – 36,000 psi. min. Tensile – 58,000 - 80,000 psi.



## Channel


ASTM A-36



## Channel

B C

| A    |         |        |          | Flange | Web   |
|------|---------|--------|----------|--------|-------|
| Size | WT / FT | Length | WT / Bar | Width  | Thick |
| 6"   | 8.200   | 20'    | 164.00   | 1.920  | 0.200 |
| 6"   | 8.200   | 40'    | 328.00   | 1.920  | 0.200 |
| 6"   | 10.500  | 20'    | 210.00   | 2.034  | 0.314 |
| 6"   | 10.500  | 40'    | 420.00   | 2.034  | 0.314 |
| 6"   | 13.000  | 20'    | 260.00   | 2.157  | 0.437 |
| 6"   | 13.000  | 40'    | 520.00   | 2.157  | 0.437 |
| 7"   | 9.800   | 20'    | 196.00   | 2.090  | 0.210 |
| 7"   | 9.800   | 40'    | 392.00   | 2.090  | 0.210 |
| 7"   | 12.250  | 20'    | 245.00   | 2.194  | 0.314 |
| 7"   | 14.750  | 20'    | 295.00   | 2.299  | 0.419 |
| 7"   | 14.750  | 40'    | 590.00   | 2.299  | 0.419 |
| 8"   | 11.500  | 20'    | 230.00   | 2.260  | 0.220 |
| 8"   | 11.500  | 40'    | 460.00   | 2.260  | 0.220 |
| 8"   | 13.750  | 20'    | 275.00   | 2.343  | 0.303 |
| 8"   | 13.750  | 40'    | 550.00   | 2.343  | 0.303 |
| 8"   | 18.750  | 20'    | 375.00   | 2.527  | 0.487 |
| 9"   | 13.400  | 20'    | 268.00   | 2.433  | 0.233 |
| 9"   | 13.400  | 40'    | 536.00   | 2.433  | 0.233 |
| 10"  | 15.300  | 20'    | 306.00   | 2.600  | 0.240 |
| 10"  | 15.300  | 40'    | 612.00   | 2.600  | 0.240 |
| 10"  | 15.300  | 50'    | 765.00   | 2.600  | 0.240 |
| 10"  | 20.000  | 20'    | 400.00   | 2.739  | 0.379 |
| 10"  | 20.000  | 40'    | 800.00   | 2.739  | 0.379 |
| 10"  | 25.000  | 20'    | 500.00   | 2.886  | 0.526 |
| 10"  | 25.000  | 40'    | 1000.00  | 2.886  | 0.526 |
| 12"  | 20.700  | 20'    | 414.00   | 2.942  | 0.282 |
| 12"  | 20.700  | 40'    | 828.00   | 2.942  | 0.282 |
| 12"  | 20.700  | 50'    | 1035.00  | 2.942  | 0.282 |
| 12"  | 30.000  | 20'    | 600.00   | 3.170  | 0.510 |
| 12"  | 30.000  | 40'    | 1200.00  | 3.170  | 0.510 |



## Jr. Channel

| A    |         |        |          | Flange | Web   |
|------|---------|--------|----------|--------|-------|
| Size | WT / FT | Length | WT / Bar | Width  | Thick |
| 10"  | 6.500   | 20'    | 130.00   | 1.127  | 0.152 |
| 10"  | 6.500   | 40'    | 260.00   | 1.127  | 0.152 |
| 10"  | 8.400   | 20'    | 168.00   | 1.500  | 0.170 |
| 10"  | 8.400   | 40'    | 336.00   | 1.500  | 0.170 |
| 12"  | 10.600  | 20'    | 212.00   | 1.500  | 0.190 |
| 12"  | 10.600  | 40'    | 424.00   | 1.500  | 0.190 |



## Galvanized Bar Channel

| Size                | WT / FT | Length | WT / Bar |
|---------------------|---------|--------|----------|
| 1-1/2 x 9/16 x 3/16 | 1.516   | 20'    | 30.32    |
| 2 x 1 x 1/8         | 1.674   | 20'    | 33.48    |
| 2 x 1 x 3/16        | 2.442   | 20'    | 48.84    |



## Galvanized Channel

| A        |         |        |          | Flange | Web   |
|----------|---------|--------|----------|--------|-------|
| Size     | WT / FT | Length | WT / Bar | Width  | Thick |
| 3" 4.1#  | 4.316   | 20'    | 86.32    | 1.410  | 0.170 |
| 4" 5.4#  | 5.684   | 20'    | 113.68   | 1.584  | 0.184 |
| 4" 7.25# | 7.632   | 20'    | 152.64   | 1.721  | 0.321 |
| 5" 6.7#  | 7.053   | 20'    | 141.06   | 1.750  | 0.190 |
| 6" 8.2#  | 8.632   | 20'    | 172.64   | 1.920  | 0.200 |

## MC CHANNEL – Ship

Conforms to ASTM A572 & A992 Gr. 50.  
Stock Lengths: 20, 40 and 60 Ft.



## Sizes in Stock

| Depth in in. Wt./Ft./ Lbs. (A) | Flange Width in in. (B) | Web Thick in in. (C) | Depth in in. Wt./Ft./ Lbs. (A) | Flange Width in in. (B) | Web Thick in in. (C) |
|--------------------------------|-------------------------|----------------------|--------------------------------|-------------------------|----------------------|
| MC 3 x 7.1                     | 1.938                   | .312                 | MC 10 x 22.0                   | 3.315                   | .312                 |
| MC 4 x 13.8                    | 2.500                   | .500                 |                                | 25.0                    | 3.405                |
| MC 6 x 12.0                    | 2.497                   | .310                 |                                | 28.5                    | 3.950                |
|                                | 15.1                    | 2.941                |                                | 33.6                    | 4.100                |
|                                | 15.3                    | 3.500                |                                | 41.1                    | 4.321                |
|                                | 16.3                    | 3.000                |                                | 31.0                    | 3.670                |
|                                | 18.0                    | 3.504                |                                | 35.0                    | 3.767                |
| MC 7 x 19.1                    | 3.452                   | .352                 | MC 12 x 40.0                   | 3.890                   | .590                 |
|                                | 22.7                    | 3.603                |                                | 45.0                    | 4.012                |
| MC 8 x 18.7                    | 2.978                   | .353                 |                                | 50.0                    | 4.135                |
|                                | 20.0                    | 3.025                |                                | 31.8                    | 4.000                |
|                                | 21.4                    | 3.450                |                                | 50.0                    | 4.412                |
|                                | 22.8                    | 3.502                |                                | 42.7                    | 3.950                |
| MC 9 x 23.9                    | 3.450                   | .400                 | MC 13 x 45.8                   | 4.000                   | .500                 |
|                                | 25.4                    | 3.500                |                                | 51.9                    | 4.100                |
|                                |                         |                      |                                | 58.0                    | 4.200                |

Many sizes available as A36



# Angles - Bar Size

ASTM A-36




## Angles

| Size                 | Length | WT / FT | WT / Bar |
|----------------------|--------|---------|----------|
| 1/2 x 1/2 x 1/8      | 20'    | 0.380   | 7.60     |
| 3/4 x 3/4 x 1/8      | 20'    | 0.590   | 11.80    |
| 7/8 x 7/8 x 1/8      | 20'    | 0.700   | 14.00    |
| 1 x 1 x 1/8          | 20'    | 0.800   | 16.00    |
| 1 x 1 x 1/8          | 20'6"  | 0.800   | 16.40    |
| 1 x 1 x 3/16         | 20'    | 1.160   | 23.20    |
| 1 x 1 x 1/4          | 20'    | 1.490   | 29.80    |
| 1-1/4 x 1-1/4 x 1/8  | 20'    | 1.010   | 20.20    |
| 1-1/4 x 1-1/4 x 3/16 | 20'    | 1.480   | 29.60    |
| 1-1/4 x 1-1/4 x 1/4  | 20'    | 1.920   | 38.40    |
| 1-3/8 x 7/8 x 1/8    | 20'    | 0.910   | 18.20    |
| 1-3/8 x 7/8 x 3/16   | 20'    | 1.320   | 26.40    |
| 1-1/2 x 1-1/2 x 1/8  | 20'    | 1.230   | 24.60    |
| 1-1/2 x 1-1/2 x 3/16 | 20'    | 1.800   | 36.00    |
| 1-1/2 x 1-1/2 x 1/4  | 20'    | 2.340   | 46.80    |
| 1-3/4 x 1-1/4 x 1/4  | 20'    | 2.340   | 46.80    |
| 1-3/4 x 1-3/4 x 1/8  | 20'    | 1.440   | 28.80    |
| 1-3/4 x 1-3/4 x 3/16 | 20'    | 2.120   | 42.40    |
| 1-3/4 x 1-3/4 x 1/4  | 20'    | 2.770   | 55.40    |



## Angles

| Size                 | Length | WT / FT | WT / Bar |
|----------------------|--------|---------|----------|
| 2 x 1-1/4 x 3/16     | 20'    | 1.960   | 39.20    |
| 2 x 1-1/4 x 1/4      | 20'    | 2.550   | 51.00    |
| 2 x 1-1/2 x 1/8      | 20'    | 1.440   | 28.80    |
| 2 x 1-1/2 x 3/16     | 20'    | 2.120   | 42.40    |
| 2 x 1-1/2 x 1/4      | 20'    | 2.770   | 55.40    |
| 2 x 2 x 1/8          | 20'    | 1.650   | 33.00    |
| 2 x 2 x 3/16         | 20'    | 2.440   | 48.80    |
| 2 x 2 x 1/4          | 20'    | 3.190   | 63.80    |
| 2 x 2 x 1/4          | 40'    | 3.190   | 127.60   |
| 2 x 2 x 5/16         | 20'    | 3.920   | 78.40    |
| 2 x 2 x 3/8          | 20'    | 4.700   | 94.00    |
| 2-1/2 x 1-1/2 x 3/16 | 20'    | 2.440   | 48.80    |
| 2-1/2 x 1-1/2 x 1/4  | 20'    | 3.190   | 63.80    |
| 2-1/2 x 2 x 3/16     | 20'    | 2.750   | 55.00    |
| 2-1/2 x 2 x 1/4      | 20'    | 3.620   | 72.40    |
| 2-1/2 x 2 x 3/8      | 20'    | 5.300   | 106.00   |
| 2-1/2 x 2-1/2 x 1/8  | 10'    | 2.130   | 21.30    |
| 2-1/2 x 2-1/2 x 3/16 | 20'    | 3.070   | 61.40    |
| 2-1/2 x 2-1/2 x 1/4  | 20'    | 4.100   | 82.00    |
| 2-1/2 x 2-1/2 x 5/16 | 20'    | 5.000   | 100.00   |
| 2-1/2 x 2-1/2 x 3/8  | 20'    | 5.900   | 118.00   |
| 2-1/2 x 2-1/2 x 1/2  | 20'    | 7.700   | 154.00   |





A x B x C

## Angles

## Angles - Structural


ASTM A-36



A x B x C

## Angles

| Size                 | Length | WT / FT | WT / Bar |
|----------------------|--------|---------|----------|
| 3 x 1-1/2 x 1/8      | 10'    | 1.920   | 19.20    |
| 3 x 2 x 1/8          | 10'    | 2.130   | 21.30    |
| 3 x 2 x 3/16         | 20'    | 3.070   | 61.40    |
| 3 x 2 x 1/4          | 20'    | 4.100   | 82.00    |
| 3 x 2 x 5/16         | 20'    | 5.000   | 100.00   |
| 3 x 2 x 3/8          | 20'    | 5.900   | 118.00   |
| 3 x 2 x 1/2          | 20'    | 7.700   | 154.00   |
| 3 x 2-1/2 x 3/16     | 20'    | 3.390   | 67.80    |
| 3 x 2-1/2 x 1/4      | 20'    | 4.500   | 90.00    |
| 3 x 3 x 1/8          | 10'    | 2.550   | 25.50    |
| 3 x 3 x 3/16         | 20'    | 3.710   | 74.20    |
| 3 x 3 x 1/4          | 20'    | 4.900   | 98.00    |
| 3 x 3 x 1/4          | 40'    | 4.900   | 196.00   |
| 3 x 3 x 5/16         | 20'    | 6.100   | 122.00   |
| 3 x 3 x 3/8          | 20'    | 7.200   | 144.00   |
| 3 x 3 x 1/2          | 20'    | 9.400   | 188.00   |
| 3-1/2 x 2-1/2 x 1/4  | 20'    | 4.900   | 98.00    |
| 3-1/2 x 3 x 3/8      | 20'    | 7.900   | 158.00   |
| 3-1/2 x 3-1/2 x 1/4  | 20'    | 5.800   | 116.00   |
| 3-1/2 x 3-1/2 x 5/16 | 20'    | 7.200   | 144.00   |
| 3-1/2 x 3-1/2 x 3/8  | 20'    | 8.500   | 170.00   |
| 3-1/2 x 3-1/2 x 1/2  | 20'    | 11.100  | 222.00   |
| 4 x 2 x 1/8          | 10'    | 2.400   | 24.00    |
| 4 x 3 x 1/4          | 20'    | 5.800   | 116.00   |
| 4 x 3 x 5/16         | 20'    | 7.200   | 144.00   |
| 4 x 3 x 3/8          | 20'    | 8.500   | 170.00   |
| 4 x 3 x 3/8          | 40'    | 8.500   | 340.00   |
| 4 x 3 x 1/2          | 20'    | 11.100  | 222.00   |
| 4 x 3-1/2 x 1/4      | 20'    | 6.200   | 124.00   |
| 4 x 3-1/2 x 5/16     | 20'    | 7.700   | 154.00   |
| 4 x 3-1/2 x 3/8      | 20'    | 9.100   | 182.00   |



| Size             | Length | WT / FT | WT / Bar |
|------------------|--------|---------|----------|
| 4 x 4 x 1/4      | 20'    | 6.600   | 132.00   |
| 4 x 4 x 1/4      | 40'    | 6.600   | 264.00   |
| 4 x 4 x 5/16     | 20'    | 8.200   | 164.00   |
| 4 x 4 x 3/8      | 20'    | 9.800   | 196.00   |
| 4 x 4 x 3/8      | 40'    | 9.800   | 392.00   |
| 4 x 4 x 1/2      | 20'    | 12.800  | 256.00   |
| 4 x 4 x 1/2      | 40'    | 12.800  | 512.00   |
| 5 x 3 x 1/4      | 20'    | 6.600   | 132.00   |
| 5 x 3 x 1/4      | 40'    | 6.600   | 264.00   |
| 5 x 3 x 5/16     | 20'    | 8.200   | 164.00   |
| 5 x 3 x 3/8      | 20'    | 9.800   | 196.00   |
| 5 x 3 x 3/8      | 40'    | 9.800   | 392.00   |
| 5 x 3 x 1/2      | 20'    | 12.800  | 256.00   |
| 5 x 3-1/2 x 1/4  | 20'    | 7.000   | 140.00   |
| 5 x 3-1/2 x 5/16 | 20'    | 8.700   | 174.00   |
| 5 x 3-1/2 x 3/8  | 20'    | 10.400  | 208.00   |
| 5 x 3-1/2 x 3/8  | 40'    | 10.400  | 416.00   |
| 5 x 3-1/2 x 1/2  | 20'    | 13.600  | 272.00   |
| 5 x 5 x 5/16     | 20'    | 10.300  | 206.00   |
| 5 x 5 x 3/8      | 20'    | 12.300  | 246.00   |
| 5 x 5 x 3/8      | 40'    | 12.300  | 492.00   |
| 6 x 3-1/2 x 5/16 | 20'    | 9.800   | 196.00   |
| 6 x 4 x 5/16     | 20'    | 10.300  | 206.00   |
| 6 x 4 x 5/16     | 40'    | 10.300  | 412.00   |
| 6 x 4 x 3/8      | 20'    | 12.300  | 246.00   |
| 6 x 4 x 3/8      | 40'    | 12.300  | 492.00   |
| 6 x 4 x 1/2      | 20'    | 16.200  | 324.00   |
| 6 x 6 x 5/16     | 20'    | 12.500  | 250.00   |
| 6 x 6 x 3/8      | 20'    | 14.900  | 298.00   |
| 6 x 6 x 3/8      | 40'    | 14.900  | 596.00   |
| 6 x 6 x 1/2      | 20'    | 19.600  | 392.00   |
| 6 x 6 x 1/2      | 40'    | 19.600  | 784.00   |
| 8 x 8 x 1/2      | 20'    | 26.400  | 528.00   |

**T Iron**

ASTM A-36

| Size                 | Length | WT / FT | WT / Bar |
|----------------------|--------|---------|----------|
| 1-3/4 x 1-3/4 x 3/16 | 20'    | 2.26    | 45.20    |
| 2 x 2 x 1/4          | 20'    | 3.62    | 72.40    |

**Galvanized Angles**

ASTM A-36

**A x B x C**

| Size                 | Length | WT / FT | WT / Bar |
|----------------------|--------|---------|----------|
| 1 x 1 x 1/8          | 20'    | 0.842   | 16.84    |
| 1 x 1 x 3/16         | 20'    | 1.221   | 24.42    |
| 1 x 1 x 1/4          | 20'    | 1.568   | 31.36    |
| 1-1/4 x 1-1/4 x 1/8  | 20'    | 1.063   | 21.26    |
| 1-1/4 x 1-1/4 x 3/16 | 20'    | 1.558   | 31.16    |
| 1-1/4 x 1-1/4 x 1/4  | 20'    | 2.021   | 40.42    |
| 1-1/2 x 1-1/2 x 1/8  | 20'    | 1.295   | 25.90    |
| 1-1/2 x 1-1/2 x 3/16 | 20'    | 1.895   | 37.90    |
| 1-1/2 x 1-1/2 x 1/4  | 20'    | 2.463   | 49.26    |
| 2 x 2 x 1/8          | 20'    | 1.737   | 34.74    |
| 2 x 2 x 3/16         | 20'    | 2.568   | 51.36    |
| 2 x 2 x 1/4          | 20'    | 3.358   | 67.16    |
| 2-1/2 x 2-1/2 x 3/16 | 20'    | 3.232   | 64.64    |
| 2-1/2 x 2-1/2 x 1/4  | 20'    | 4.316   | 86.32    |


**Galvanized Angles**

ASTM A-36

**A x B x C**

| Size                 | Length | WT / FT | WT / Bar |
|----------------------|--------|---------|----------|
| 3 x 2 x 3/16         | 20'    | 3.232   | 64.64    |
| 3 x 3 x 3/16         | 20'    | 3.905   | 78.10    |
| 3 x 3 x 1/4          | 20'    | 5.158   | 103.16   |
| 3 x 3 x 3/8          | 20'    | 7.579   | 151.58   |
| 3-1/2 x 3-1/2 x 5/16 | 20'    | 7.579   | 151.58   |
| 4 x 3 x 1/4          | 20'    | 6.105   | 122.10   |
| 4 x 4 x 1/4          | 20'    | 6.947   | 138.94   |
| 4 x 4 x 3/8          | 20'    | 10.316  | 206.32   |
| 5 x 3 x 1/4          | 20'    | 6.947   | 138.94   |
| 6 x 6 x 3/8          | 20'    | 15.684  | 313.68   |

**ASTM A-36** – Low carbon, structural quality steel used in bridges, building construction, and general structural applications. Estimated Minimum Mechanical Properties (EMMP): Yield 36,000 psi. min. – Tensile 58,000-80,000 psi.



# Strips

Commercial Quality / M1020 / ASTM A-36



## Hot Rolled Strips

| Size         | Length | WT / FT | WT / Bar |
|--------------|--------|---------|----------|
| 1/8 x 1/2    | 20'    | 0.213   | 4.26     |
| 1/8 x 3/4    | 20'    | 0.319   | 6.38     |
| 1/8 x 1      | 20'    | 0.425   | 8.50     |
| 1/8 x 1-1/4  | 20'    | 0.531   | 10.62    |
| 1/8 x 1-1/2  | 20'    | 0.638   | 12.76    |
| 1/8 x 1-3/4  | 20'    | 0.744   | 14.88    |
| 1/8 x 2      | 20'    | 0.850   | 17.00    |
| 1/8 x 2-1/4  | 20'    | 0.956   | 19.12    |
| 1/8 x 2-1/2  | 20'    | 1.063   | 21.26    |
| 1/8 x 3      | 20'    | 1.275   | 25.50    |
| 1/8 x 3-1/2  | 20'    | 1.488   | 29.76    |
| 1/8 x 4      | 20'    | 1.700   | 34.00    |
| 1/8 x 5      | 20'    | 2.125   | 42.50    |
| 1/8 x 6      | 20'    | 2.550   | 51.00    |
| 1/8 x 8      | 10'    | 3.400   | 34.00    |
| 1/8 x 10     | 10'    | 4.250   | 42.50    |
| 1/8 x 12     | 10'    | 5.100   | 51.00    |
|              |        |         |          |
| 3/16 x 1/2   | 20'    | 0.319   | 6.38     |
| 3/16 x 3/4   | 20'    | 0.478   | 9.56     |
| 3/16 x 1     | 20'    | 0.638   | 12.76    |
| 3/16 x 1-1/4 | 20'    | 0.797   | 15.94    |
| 3/16 x 1-1/2 | 20'    | 0.956   | 19.12    |
| 3/16 x 1-3/4 | 20'    | 1.116   | 22.32    |
| 3/16 x 2     | 20'    | 1.275   | 25.50    |
| 3/16 x 2-1/2 | 20'    | 1.594   | 31.88    |
| 3/16 x 3     | 20'    | 1.913   | 38.26    |
| 3/16 x 3-1/2 | 20'    | 2.231   | 44.62    |
| 3/16 x 4     | 20'    | 2.550   | 51.00    |
| 3/16 x 5     | 20'    | 3.188   | 63.76    |
| 3/16 x 5-1/2 | 20'    | 3.506   | 70.12    |
| 3/16 x 6     | 20'    | 3.825   | 76.50    |
| 3/16 x 8     | 10'    | 5.100   | 51.00    |
| 3/16 x 10    | 10'    | 6.375   | 63.75    |
| 3/16 x 12    | 10'    | 7.650   | 76.50    |



## Galvanized Strips

| Size         | Length | WT / FT | WT / Bar |
|--------------|--------|---------|----------|
| 1/8 x 1      | 10'    | 0.482   | 4.82     |
| 1/8 x 1-1/2  | 10'    | 0.723   | 7.23     |
| 1/8 x 2      | 10'    | 0.963   | 9.63     |
|              |        |         |          |
| 3/16 x 1     | 20'    | 0.672   | 13.44    |
| 3/16 x 1-1/4 | 20'    | 0.839   | 16.78    |
| 3/16 x 1-1/2 | 20'    | 1.006   | 20.12    |
| 3/16 x 2     | 20'    | 1.342   | 26.84    |
| 3/16 x 3     | 20'    | 2.014   | 40.28    |
| 3/16 x 3-1/2 | 20'    | 2.348   | 46.96    |

**ASTM A-36** – Low carbon, structural quality steel used in bridges, building construction, and general structural applications. Estimated Minimum Mechanical Properties (EMMP):

Yield – 36,000 psi.

Tensile – 58,000 - 80,000 psi.

**M1020** – A low carbon, low manganese, general purpose, merchant quality steel that is suitable for forming and welding. Estimated Minimum Mechanical Properties (EMMP):

Yield – 43,000 psi.

Tensile – 65,000 psi.



## Hot Rolled Flats

M1020 / ASTM A-36

| Size         | Length | WT / FT | WT / Length |
|--------------|--------|---------|-------------|
| 1/4 x 1/2    | 20'    | 0.425   | 8.50        |
| 1/4 x 3/4    | 20'    | 0.638   | 12.76       |
| 1/4 x 1      | 20'    | 0.850   | 17.00       |
| 1/4 x 1-1/4  | 20'    | 1.063   | 21.26       |
| 1/4 x 1-1/2  | 20'    | 1.275   | 25.50       |
| 1/4 x 1-3/4  | 20'    | 1.488   | 29.76       |
| 1/4 x 2      | 20'    | 1.700   | 34.00       |
| 1/4 x 2-1/4  | 20'    | 1.913   | 38.26       |
| 1/4 x 2-1/2  | 20'    | 2.125   | 42.50       |
| 1/4 x 2-3/4  | 20'    | 2.338   | 46.76       |
| 1/4 x 3      | 20'    | 2.550   | 51.00       |
| 1/4 x 3-1/2  | 20'    | 2.975   | 59.50       |
| 1/4 x 4      | 20'    | 3.400   | 68.00       |
| 1/4 x 4-1/2  | 20'    | 3.825   | 76.50       |
| 1/4 x 5      | 20'    | 4.250   | 85.00       |
| 1/4 x 5-1/2  | 20'    | 4.675   | 93.50       |
| 1/4 x 6      | 20'    | 5.100   | 102.00      |
| 1/4 x 7      | 20'    | 5.950   | 119.00      |
| 1/4 x 8      | 20'    | 6.800   | 136.00      |
| 1/4 x 10     | 20'    | 8.500   | 170.00      |
| 1/4 x 12     | 20'    | 10.200  | 204.00      |
|              |        |         |             |
| 5/16 x 1     | 20'    | 1.063   | 21.26       |
| 5/16 x 1-1/4 | 20'    | 1.328   | 26.56       |
| 5/16 x 1-1/2 | 20'    | 1.594   | 31.88       |
| 5/16 x 1-3/4 | 20'    | 1.859   | 37.18       |
| 5/16 x 2     | 20'    | 2.125   | 42.50       |
| 5/16 x 2-1/2 | 20'    | 2.656   | 53.12       |
| 5/16 x 3     | 20'    | 3.188   | 63.76       |
| 5/16 x 3-1/2 | 20'    | 3.719   | 74.38       |
| 5/16 x 4     | 20'    | 4.250   | 85.00       |
| 5/16 x 4-1/2 | 20'    | 4.781   | 95.62       |
| 5/16 x 5     | 20'    | 5.313   | 106.26      |
| 5/16 x 6     | 20'    | 6.375   | 127.50      |

## Flats



## Hot Rolled Flats

M1020 / ASTM A-36

| Size        | Length | WT / FT | WT / Length |
|-------------|--------|---------|-------------|
| 3/8 x 3/4   | 20'    | 0.956   | 19.12       |
| 3/8 x 1     | 20'    | 1.275   | 25.50       |
| 3/8 x 1-1/4 | 20'    | 1.594   | 31.88       |
| 3/8 x 1-1/2 | 20'    | 1.913   | 38.26       |
| 3/8 x 1-3/4 | 20'    | 2.231   | 44.62       |
| 3/8 x 2     | 20'    | 2.550   | 51.00       |
| 3/8 x 2-1/4 | 20'    | 2.869   | 57.38       |
| 3/8 x 2-1/2 | 20'    | 3.188   | 63.76       |
| 3/8 x 2-3/4 | 20'    | 3.506   | 70.12       |
| 3/8 x 3     | 20'    | 3.825   | 76.50       |
| 3/8 x 3-1/2 | 20'    | 4.463   | 89.26       |
| 3/8 x 4     | 20'    | 5.100   | 102.00      |
| 3/8 x 4-1/2 | 20'    | 5.738   | 114.76      |
| 3/8 x 5     | 20'    | 6.375   | 127.50      |
| 3/8 x 5-1/2 | 20'    | 7.013   | 140.26      |
| 3/8 x 6     | 20'    | 7.650   | 153.00      |
| 3/8 x 6-1/2 | 20'    | 8.288   | 165.76      |
| 3/8 x 7     | 20'    | 8.925   | 178.50      |
| 3/8 x 8     | 20'    | 10.200  | 204.00      |
| 3/8 x 9     | 20'    | 11.480  | 229.60      |
| 3/8 x 10    | 20'    | 12.750  | 255.00      |
| 3/8 x 12    | 10'    | 15.300  | 153.00      |
| 3/8 x 12    | 20'    | 15.300  | 306.00      |

M1020 – A low carbon, low manganese, general purpose, merchant quality steel that is suitable for forming and welding. Estimated Minimum Mechanical Properties (EMMP):

Yield – 43,000 psi.

Tensile – 65,000 psi.

## Flats



## Hot Rolled Flats

M1020 / ASTM A-36



## Hot Rolled Flats

M1020 / ASTM A-36

| Size        | Length | WT / FT | WT / Length |
|-------------|--------|---------|-------------|
| 1/2 x 3/4   | 20'    | 1.275   | 25.50       |
| 1/2 x 1     | 20'    | 1.700   | 34.00       |
| 1/2 x 1-1/4 | 20'    | 2.125   | 42.50       |
| 1/2 x 1-1/2 | 20'    | 2.550   | 51.00       |
| 1/2 x 1-3/4 | 20'    | 2.975   | 59.50       |
| 1/2 x 2     | 20'    | 3.400   | 68.00       |
| 1/2 x 2-1/4 | 20'    | 3.825   | 76.50       |
| 1/2 x 2-1/2 | 20'    | 4.250   | 85.00       |
| 1/2 x 2-3/4 | 20'    | 4.675   | 93.50       |
| 1/2 x 3     | 20'    | 5.100   | 102.00      |
| 1/2 x 3-1/4 | 20'    | 5.525   | 110.50      |
| 1/2 x 3-1/2 | 20'    | 5.950   | 119.00      |
| 1/2 x 4     | 20'    | 6.800   | 136.00      |
| 1/2 x 4-1/2 | 20'    | 7.650   | 153.00      |
| 1/2 x 5     | 20'    | 8.500   | 170.00      |
| 1/2 x 5-1/2 | 20'    | 9.350   | 187.00      |
| 1/2 x 6     | 20'    | 10.200  | 204.00      |
| 1/2 x 6-1/2 | 20'    | 11.050  | 221.00      |
| 1/2 x 7     | 20'    | 11.900  | 238.00      |
| 1/2 x 8     | 20'    | 13.600  | 272.00      |
| 1/2 x 9     | 20'    | 15.300  | 306.00      |
| 1/2 x 10    | 20'    | 17.000  | 340.00      |
| 1/2 x 12    | 20'    | 20.400  | 408.00      |
|             |        |         |             |
| 5/8 x 1     | 20'    | 2.125   | 42.50       |
| 5/8 x 1-1/2 | 20'    | 3.188   | 63.76       |
| 5/8 x 2     | 20'    | 4.250   | 85.00       |
| 5/8 x 2-1/2 | 20'    | 5.313   | 106.26      |
| 5/8 x 3     | 20'    | 6.375   | 127.50      |
| 5/8 x 3-1/2 | 20'    | 7.438   | 148.76      |
| 5/8 x 4     | 20'    | 8.500   | 170.00      |
| 5/8 x 4-1/2 | 20'    | 9.563   | 191.26      |
| 5/8 x 5     | 20'    | 10.630  | 212.60      |
| 5/8 x 6     | 20'    | 12.750  | 255.00      |
| 5/8 x 7     | 20'    | 14.880  | 297.60      |
| 5/8 x 8     | 20'    | 17.000  | 340.00      |
| 5/8 x 9     | 20'    | 19.130  | 382.60      |
| 5/8 x 10    | 20'    | 21.250  | 425.00      |
| 5/8 x 12    | 20'    | 25.500  | 510.00      |

| Size          | Length | WT / FT | WT / Length |
|---------------|--------|---------|-------------|
| 3/4 x 1       | 20'    | 2.550   | 51.00       |
| 3/4 x 1-1/2   | 20'    | 3.825   | 76.50       |
| 3/4 x 2       | 20'    | 5.100   | 102.00      |
| 3/4 x 2-1/2   | 20'    | 6.375   | 127.50      |
| 3/4 x 2-3/4   | 20'    | 7.013   | 140.26      |
| 3/4 x 3       | 20'    | 7.650   | 153.00      |
| 3/4 x 3-1/2   | 20'    | 8.925   | 178.50      |
| 3/4 x 4       | 20'    | 10.200  | 204.00      |
| 3/4 x 4-1/2   | 20'    | 11.480  | 229.60      |
| 3/4 x 5       | 20'    | 12.750  | 255.00      |
| 3/4 x 6       | 20'    | 15.300  | 306.00      |
| 3/4 x 7       | 20'    | 17.850  | 357.00      |
| 3/4 x 8       | 20'    | 20.400  | 408.00      |
| 3/4 x 9       | 20'    | 22.950  | 459.00      |
| 3/4 x 10      | 20'    | 25.500  | 510.00      |
| 3/4 x 12      | 20'    | 30.600  | 612.00      |
|               |        |         |             |
| 1 x 1-1/2     | 20'    | 5.100   | 102.00      |
| 1 x 2         | 20'    | 6.800   | 136.00      |
| 1 x 2-1/2     | 20'    | 8.500   | 170.00      |
| 1 x 3         | 20'    | 10.200  | 204.00      |
| 1 x 3-1/2     | 20'    | 11.900  | 238.00      |
| 1 x 4         | 20'    | 13.600  | 272.00      |
| 1 x 5         | 20'    | 17.000  | 340.00      |
| 1 x 6         | 20'    | 20.400  | 408.00      |
| 1 x 7         | 20'    | 23.800  | 476.00      |
| 1 x 8         | 20'    | 27.200  | 544.00      |
| 1 x 10        | 20'    | 34.000  | 680.00      |
| 1 x 12        | 20'    | 40.800  | 816.00      |
|               |        |         |             |
| 1-1/4 x 2     | 20'    | 8.500   | 170.00      |
| 1-1/4 x 3     | 20'    | 12.750  | 255.00      |
| 1-1/4 x 4     | 20'    | 17.000  | 340.00      |
|               |        |         |             |
| 1-1/2 x 2-1/4 | 20'    | 11.480  | 229.60      |
| 1-1/2 x 4-1/2 | 20'    | 22.950  | 459.00      |
|               |        |         |             |
| 2 x 5         | 20'    | 34.000  | 680.00      |

## Flats



### Galvanized Flats

ASTM A-36

| Size        | Length | WT / FT | WT / Length |
|-------------|--------|---------|-------------|
| 1/4 x 1     | 20'    | 0.895   | 17.90       |
| 1/4 x 1-1/4 | 20'    | 1.119   | 22.38       |
| 1/4 x 1-1/2 | 20'    | 1.342   | 26.84       |
| 1/4 x 2     | 20'    | 1.789   | 35.78       |
| 1/4 x 2-1/2 | 20'    | 2.237   | 44.74       |
| 1/4 x 3     | 20'    | 2.684   | 53.68       |
| 1/4 x 4     | 20'    | 3.579   | 71.58       |
| 1/4 x 6     | 20'    | 5.368   | 107.36      |
| 3/8 x 2     | 20'    | 2.684   | 53.68       |
| 3/8 x 3     | 20'    | 4.026   | 80.52       |
| 3/8 x 6     | 20'    | 8.053   | 161.06      |
| 1/2 x 7     | 20'    | 12.526  | 250.52      |



### Hot Rolled Flats M1044

| Size    | Length | WT / FT | WT / Length |
|---------|--------|---------|-------------|
| 1/2 x 3 | 20'    | 5.100   | 102.00      |



### Hot Rolled Flats 1045

| Size     | Length | WT / FT | WT / Length |
|----------|--------|---------|-------------|
| 5/16 x 4 | 24'4"  | 4.250   | 103.42      |
| 3/4 x 4  | 20'    | 10.200  | 204.00      |
| 3/4 x 5  | 20'    | 12.750  | 255.00      |
| 1 x 5    | 20'    | 17.000  | 340.00      |

H.R. Flat M1044 – This is a medium carbon, similar to the properties of 1045 but contains lesser amounts of manganese. Strength levels and heat treatability are very close to the same. Estimated Minimum Mechanical Properties (EMMP):

Yield – 44,000 psi.      Tensile – 80,000 psi.

H.R. Flat 1045 – This is a medium carbon which increases strength levels and heat treatability. Commonly used for axles, shafts, gears, and connecting rods. Estimated Minimum Mechanical Properties (EMMP):

Yield – 60,000 psi.      Tensile – 95,000 psi.



## Hot Rolled Rounds

M1020 / ASTM A-36

| Size   | Length | WT / FT | WT / Length |
|--------|--------|---------|-------------|
| 1/4"   | 20'    | 0.167   | 3.34        |
| 5/16"  | 20'    | 0.261   | 5.22        |
| 3/8"   | 20'    | 0.376   | 7.52        |
| 7/16"  | 20'    | 0.511   | 10.22       |
| 1/2"   | 20'    | 0.668   | 13.36       |
| 9/16"  | 20'    | 0.845   | 16.90       |
| 5/8"   | 20'    | 1.043   | 20.86       |
| 3/4"   | 20'    | 1.502   | 30.04       |
| 7/8"   | 20'    | 2.045   | 40.90       |
| 1"     | 20'    | 2.670   | 53.40       |
| 1-1/8" | 20'    | 3.380   | 67.60       |
| 1-1/4" | 20'    | 4.173   | 83.46       |
| 1-3/8" | 20'    | 5.049   | 100.98      |
| 1-1/2" | 20'    | 6.008   | 120.16      |
| 1-3/4" | 20'    | 8.178   | 163.56      |
| 2"     | 20'    | 10.680  | 213.60      |



## Galvanized Rounds

M1020 / ASTM A-36

| Size | Length | WT / FT | WT / Length |
|------|--------|---------|-------------|
| 1/2" | 20'    | 0.703   | 14.06       |
| 5/8" | 20'    | 1.098   | 21.96       |
| 3/4" | 20'    | 1.581   | 31.62       |



## Hot Rolled Squares

M1020 / ASTM A-36

| Size   | Length | WT / FT | WT / Bar |
|--------|--------|---------|----------|
| 3/8"   | 20'    | 0.478   | 9.56     |
| 1/2"   | 20'    | 0.850   | 17.00    |
| 5/8"   | 20'    | 1.328   | 26.56    |
| 3/4"   | 20'    | 1.913   | 38.26    |
| 1"     | 20'    | 3.400   | 68.00    |
| 1-1/4" | 20'    | 5.313   | 106.26   |
| 1-1/2" | 20'    | 7.650   | 153.00   |
| 2"     | 20'    | 13.600  | 272.00   |

**ASTM A-36** – Low carbon, structural quality steel used in bridges, building construction, and general structural applications. Estimated Minimum Mechanical Properties (EMMP): Yield 36,000 psi. min. – Tensile 58,000-80,000 psi.

**M1020** – Low carbon, low manganese, general purpose, merchant quality steel that is suitable for forming and welding. Estimated Minimum Mechanical Properties (EMMP): Yield 43,000 psi – Tensile 65,000 psi.





## Rebar & Wire Mesh

### Reinforcing Bars

ASTM A-615 – Billet Steel Deformed Bars – No Grade – Grades 40 & 60

| Size         | IMP | Grade | Length | WT / FT | WT / Length |
|--------------|-----|-------|--------|---------|-------------|
| 3/8" #10mm   | #3  | NG    | 20'    | 0.376   | 7.52        |
| 1/2" #13mm   | #4  | NG    | 20'    | 0.668   | 13.36       |
| 5/8" #16mm   | #5  | NG    | 20'    | 1.043   | 20.86       |
| 3/4" #19mm   | #6  | NG    | 20'    | 1.502   | 30.04       |
| 3/8" #10mm   | #3  | G40   | 20'    | 0.376   | 7.52        |
| 1/2" #13mm   | #4  | G40   | 20'    | 0.668   | 13.36       |
| 5/8" #16mm   | #5  | G40   | 20'    | 1.043   | 20.86       |
| 3/4" #19mm   | #6  | G40   | 20'    | 1.502   | 30.04       |
| 1/2" #13mm   | #4  | G60   | 20'    | 0.668   | 13.36       |
| 1/2" #13mm   | #4  | G60   | 30'    | 0.668   | 20.04       |
| 5/8" #16mm   | #5  | G60   | 20'    | 1.043   | 20.86       |
| 3/4" #19mm   | #6  | G60   | 20'    | 1.502   | 30.04       |
| 7/8" #22mm   | #7  | G60   | 20'    | 2.045   | 40.90       |
| 1" #25mm     | #8  | G60   | 20'    | 2.670   | 53.40       |
| 1-1/8" #29mm | #9  | G60   | 20'    | 3.380   | 67.60       |

### Reinforcing Wire Mesh Rolls

| Size        | Length    | WT/EA  |
|-------------|-----------|--------|
| 6 x 6 10/10 | 5' x 150' | 148.00 |
| 6 x 6 6/6   | 5' x 150' | 305.00 |



### Reinforcing Wire Mesh Sheets

| Size        | Length   | WT/EA |
|-------------|----------|-------|
| 6 x 6 10/10 | 4' x 8'  | 6.72  |
| 6 x 6 10/10 | 8' x 20' | 33.60 |
| 6 x 6 6/6   | 8' x 20' | 67.20 |

### Reinforcing Bars

**ASTM 615** – New billet-deformed bars. Reinforcing bars are commonly used for concrete reinforcement. The bar's surface is supplied with small lugs which eliminate motion of concrete in relation to the bar. We stock three grades.

**No Grade** – Bendable but can run into hard spots. This is the most economical grade.

**Grade 40** – Best formability. Estimated Minimum Mechanical Properties (EMMP):

Yield – 40,000 psi. Tensile – 70,000 psi.

**Grade 60** – Highest strength of our three grades. Estimated Minimum Mechanical

Properties (EMMP): Yield – 60,000 psi. Tensile – 90,000 psi.

### Wire Mesh

6" x 6" – wire pattern = 6" x 6" squares

10/10 – wire gauge = 10ga. both directions

6/6 – wire gauge = 6ga. both directions

6 x 6 10/10 – also known as – W1.4/W1.4

6 x 6 6/6 – also known as – W2.9 / W2.9



## Threaded Carbon Steel Rod

(Oil Finish)

## Redi Rod

National Course



## Electro Zinc Plated

| Size       | Length | WT / FT | WT / Length |
|------------|--------|---------|-------------|
| 1/4" blk   | 6'     | 0.118   | 0.708       |
| 1/4" blk   | 10'    | 0.118   | 1.180       |
| 1/4" blk   | 12'    | 0.118   | 1.416       |
| 5/16" blk  | 6'     | 0.197   | 1.182       |
| 5/16" blk  | 10'    | 0.197   | 1.970       |
| 3/8" blk   | 6'     | 0.284   | 1.704       |
| 3/8" blk   | 10'    | 0.284   | 2.840       |
| 7/16" blk  | 6'     | 0.390   | 2.340       |
| 1/2" blk   | 6'     | 0.515   | 3.090       |
| 1/2" blk   | 10'    | 0.515   | 5.150       |
| 9/16" blk  | 6'     | 0.660   | 3.960       |
| 5/8" blk   | 6'     | 0.825   | 4.950       |
| 5/8" blk   | 10'    | 0.825   | 8.250       |
| 3/4" blk   | 6'     | 1.215   | 7.290       |
| 3/4" blk   | 10'    | 1.215   | 12.15       |
| 7/8" blk   | 6'     | 1.675   | 10.05       |
| 7/8" blk   | 10'    | 1.675   | 16.75       |
| 1" blk     | 6'     | 2.190   | 13.14       |
| 1" blk     | 10'    | 2.190   | 21.90       |
| 1-1/2" blk | 12'    | 5.050   | 60.60       |

| Size       | Length | WT / FT | WT / Length |
|------------|--------|---------|-------------|
| 1/4" galv  | 6'     | 0.118   | 0.708       |
| 1/4" galv  | 12'    | 0.118   | 1.416       |
| 5/16" galv | 6'     | 0.197   | 1.182       |
| 3/8" galv  | 6'     | 0.284   | 1.704       |
| 3/8" galv  | 12'    | 0.284   | 3.408       |
| 7/16" galv | 3'     | 0.390   | 1.170       |
| 7/16" galv | 6'     | 0.390   | 2.340       |
| 1/2" galv  | 6'     | 0.515   | 3.090       |
| 1/2" galv  | 12'    | 0.515   | 6.180       |
| 5/8" galv  | 6'     | 0.825   | 4.950       |
| 5/8" galv  | 12'    | 0.825   | 9.900       |
| 3/4" galv  | 6'     | 1.215   | 7.290       |
| 7/8" galv  | 6'     | 1.675   | 10.05       |
| 1" galv    | 6'     | 2.190   | 13.14       |



## Type 304 Stainless Steel Threaded Rod

| Size     | Length | WT / FT | WT / Length |
|----------|--------|---------|-------------|
| 1/4" SS  | 12'    | 0.123   | 1.476       |
| 5/16" SS | 12'    | 0.201   | 2.412       |
| 3/8" SS  | 12'    | 0.296   | 3.552       |
| 7/16" SS | 6'     | 0.406   | 2.436       |
| 7/16" SS | 12'    | 0.406   | 4.872       |
| 1/2" SS  | 6'     | 0.539   | 3.234       |
| 1/2" SS  | 12'    | 0.539   | 6.468       |
| 5/8" SS  | 6'     | 0.852   | 5.112       |
| 5/8" SS  | 12'    | 0.852   | 10.22       |
| 3/4" SS  | 6'     | 1.249   | 7.49        |
| 3/4" SS  | 12'    | 1.249   | 14.99       |
| 7/8" SS  | 12'    | 1.724   | 20.69       |
| 1" SS    | 12'    | 2.256   | 27.07       |

**Cold Rolled Rounds 1018**

| Size     | Length | WT / FT | WT / Length |
|----------|--------|---------|-------------|
| 5/32"    | 12'    | 0.065   | 0.78        |
| 3/16"    | 12'    | 0.094   | 1.13        |
| 1/4"     | 12'    | 0.167   | 2.00        |
| 1/4"     | 20'    | 0.167   | 3.34        |
| 5/16"    | 20'    | 0.261   | 5.22        |
| 3/8"     | 20'    | 0.376   | 7.52        |
| 7/16"    | 20'    | 0.511   | 10.22       |
| 1/2"     | 12'    | 0.668   | 8.02        |
| 1/2"     | 20'    | 0.668   | 13.36       |
| 9/16     | 20'    | 0.845   | 16.90       |
| 5/8"     | 20'    | 1.043   | 20.86       |
| 11/16"   | 20'    | 1.262   | 25.24       |
| 3/4"     | 20'    | 1.502   | 30.04       |
| 13/16"   | 20'    | 1.763   | 35.26       |
| 7/8"     | 20'    | 2.045   | 40.90       |
| 15/16"   | 20'    | 2.347   | 46.94       |
|          |        |         |             |
| 1"       | 20'    | 2.670   | 53.40       |
| 1-1/16"  | 20'    | 3.015   | 60.30       |
| 1-1/8"   | 20'    | 3.380   | 67.60       |
| 1-3/16"  | 20'    | 3.766   | 75.32       |
| 1-1/4"   | 20'    | 4.173   | 83.46       |
| 1-5/16"  | 20'    | 4.600   | 92.00       |
| 1-3/8"   | 20'    | 5.049   | 100.98      |
| 1-7/16"  | 20'    | 5.518   | 110.36      |
| 1-1/2"   | 20'    | 6.008   | 120.16      |
| 1-5/8"   | 20'    | 7.052   | 141.04      |
| 1-11/16" | 20'    | 7.604   | 152.08      |
| 1-3/4"   | 20'    | 8.178   | 163.56      |
| 1-7/8"   | 20'    | 9.388   | 187.76      |
| 1-15/16" | 20'    | 10.020  | 200.40      |
|          |        |         |             |
| 2"       | 20'    | 10.680  | 213.60      |
| 2-3/16"  | 20'    | 12.780  | 255.60      |
| 2-1/4"   | 20'    | 13.520  | 270.40      |
| 2-7/16"  | 20'    | 15.870  | 317.40      |
| 2-1/2"   | 20'    | 16.690  | 333.80      |
| 2-3/4"   | 20'    | 20.190  | 403.80      |
| 2-15/16" | 20'    | 23.040  | 460.80      |

**Rounds****Cold Rolled Rounds 1018**

| Size    | Length | WT / FT | WT / Length |
|---------|--------|---------|-------------|
| 3"      | 20'    | 24.030  | 480.60      |
| 3-1/4"  | 20'    | 28.210  | 564.20      |
| 3-7/16" | 20'    | 31.550  | 631.00      |
| 3-1/2"  | 20'    | 32.710  | 654.20      |
|         |        |         |             |
| 4"      | 12'    | 42.730  | 512.76      |

**Cold Rolled Rounds 1045**

| Size    | Length | WT / FT | WT / Length |
|---------|--------|---------|-------------|
| 1/4"    | 20'    | 0.167   | 3.34        |
| 3/8"    | 12'    | 0.376   | 4.51        |
| 3/8"    | 20'    | 0.376   | 7.52        |
| 1/2"    | 20'    | 0.668   | 13.36       |
| 5/8"    | 20'    | 1.043   | 20.86       |
| 3/4"    | 20'    | 1.502   | 30.04       |
| 7/8"    | 20'    | 2.045   | 40.90       |
|         |        |         |             |
| 1"      | 20'    | 2.670   | 53.40       |
| 1-1/8"  | 20'    | 3.380   | 67.60       |
| 1-3/16" | 20'    | 3.766   | 75.32       |
| 1-1/4"  | 20'    | 4.173   | 83.46       |
| 1-5/16" | 20'    | 4.600   | 92.00       |
| 1-3/8"  | 20'    | 5.049   | 100.98      |
| 1-7/16" | 20'    | 5.518   | 110.36      |
| 1-1/2"  | 20'    | 6.008   | 120.16      |
| 1-5/8"  | 20'    | 7.052   | 141.04      |
| 1-3/4"  | 20'    | 8.178   | 163.56      |
|         |        |         |             |
| 2"      | 20'    | 10.680  | 213.60      |
| 2-3/16" | 20'    | 12.780  | 255.60      |
| 2-1/4"  | 20'    | 13.520  | 270.40      |
| 2-1/2"  | 20'    | 16.690  | 333.80      |
| 2-3/4"  | 20'    | 20.190  | 403.80      |
|         |        |         |             |
| 3"      | 20'    | 24.030  | 480.60      |
| 3-1/2"  | 20'    | 32.710  | 654.20      |

**1018** – A low carbon steel that is easily welded or brazed with fair machinability and good hardening properties. Manufactured for cold forming and bending. Estimated Minimum Mechanical Properties (EMMP):

Yield – 54,000 psi. Tensile – 64,000 psi.

## Rounds

**Cold Rolled Rounds 1045**

Turned Ground and Polished

| Size   | Length | WT / FT | WT / Length |
|--------|--------|---------|-------------|
| 3/4"   | 22' rl | 1.502   | 33.04       |
| 1"     | 21' rl | 2.670   | 56.07       |
| 1-1/4" | 20' rl | 4.173   | 83.46       |
| 1-1/2" | 20' rl | 6.008   | 120.16      |
| 1-3/4" | 22' rl | 8.178   | 179.92      |
| 2"     | 24' rl | 10.680  | 256.32      |
| 2-1/2" | 21' rl | 16.690  | 350.49      |

**Cold Rolled Rounds 1144**

| Size   | Length | WT / FT | WT / Length |
|--------|--------|---------|-------------|
| 1"     | 12'    | 2.670   | 32.04       |
| 1-1/2" | 12'    | 6.008   | 72.10       |

**Cold Rolled Rounds 1215**

| Size | Length | WT / FT | WT / Length |
|------|--------|---------|-------------|
| 1"   | 12'    | 2.670   | 32.04       |

**Cold Rolled 1144 Rounds**

Stress Relieved

| Size    | Length | WT / FT | WT / Length |
|---------|--------|---------|-------------|
| 5/16"   | 12' rl | 0.261   | 3.13        |
| 3/8"    | 12' rl | 0.376   | 4.51        |
| 1/2"    | 12' rl | 0.668   | 8.02        |
| 5/8"    | 12' rl | 1.043   | 12.52       |
| 3/4"    | 12' rl | 1.502   | 18.02       |
| 7/8"    | 12' rl | 2.045   | 24.54       |
| 1"      | 12' rl | 2.670   | 32.04       |
| 1-1/8"  | 12' rl | 3.380   | 40.56       |
| 1-1/4"  | 12' rl | 4.173   | 50.08       |
| 1-3/8"  | 12' rl | 5.049   | 60.59       |
| 1-7/16" | 12' rl | 5.518   | 66.22       |
| 1-1/2"  | 12' rl | 6.008   | 72.10       |

**Cold Rolled 1144 Rounds**

Stress Relieved

| Size     | Length | WT / FT | WT / Length |
|----------|--------|---------|-------------|
| 1-5/8"   | 12' rl | 7.052   | 84.62       |
| 1-11/16" | 12' rl | 7.604   | 91.25       |
| 1-3/4"   | 12' rl | 8.178   | 98.14       |
| 1-7/8"   | 12' rl | 9.388   | 112.66      |
| 1-15/16" | 12' rl | 10.020  | 120.24      |
| 2"       | 12' rl | 10.680  | 128.16      |
| 2-3/16"  | 12' rl | 12.780  | 153.36      |
| 2-1/4"   | 12' rl | 13.520  | 162.24      |
| 2-7/16"  | 12' rl | 15.870  | 190.44      |
| 2-1/2"   | 12' rl | 16.690  | 200.28      |
| 2-15/16" | 12' rl | 23.040  | 276.48      |
| 3"       | 12' rl | 24.030  | 288.36      |
| 3"       | 20' rl | 24.030  | 480.60      |
| 3-1/4"   | 12' rl | 28.210  | 338.52      |
| 3-1/2"   | 12' rl | 32.710  | 392.52      |

**Cold Rolled 1144 Rounds**

Stress Relieved Turned Ground &amp; Polished

| Size   | Length | WT / FT | WT / Length |
|--------|--------|---------|-------------|
| 1"     | 12' rl | 2.670   | 32.04       |
| 1-1/4" | 12' rl | 4.173   | 50.08       |

**1045** – This higher carbon range steel is produced with a smoother finish and has more strength than the 1018. The 1045 does not machine freely, can be forced satisfactorily, is fair for brazing, and welding requires a specific technique. Commonly used for shafts, connecting rods, bolts, wheel flanges, and gears. Response to heat treatment is excellent. Estimated Minimum Mechanical Properties (EMMP): Yield – 77,000 psi. Tensile – 91,000 psi.

**Cold Drawn 1144 Bars** – Higher carbon and sulphur levels resulting in superior machinability but restricts weldability. Estimated Minimum Mechanical Properties (EMMP): Yield – 90,000 psi. Tensile – 108,000 psi.

## Cold Rolled Squares & Hexagons



### Cold Rolled Squares 1018

| Size   | Length | WT / FT | WT / Bar |
|--------|--------|---------|----------|
| 3/16"  | 12'    | 0.120   | 1.44     |
| 1/4"   | 12'    | 0.213   | 2.56     |
| 5/16"  | 12'    | 0.332   | 3.98     |
| 3/8"   | 12'    | 0.478   | 5.74     |
| 7/16"  | 12'    | 0.651   | 7.81     |
| 1/2"   | 12'    | 0.850   | 10.20    |
| 5/8"   | 12'    | 1.328   | 15.94    |
| 3/4"   | 12'    | 1.913   | 22.96    |
| 7/8"   | 12'    | 2.603   | 31.24    |
| 1"     | 12'    | 3.400   | 40.80    |
| 1-1/8" | 12'    | 4.303   | 51.64    |
| 1-1/4" | 12'    | 5.313   | 63.76    |
| 1-1/2" | 12'    | 7.650   | 91.80    |
| 2"     | 12'    | 13.600  | 163.20   |
| 3"     | 12'    | 30.600  | 367.20   |



### Cold Rolled Squares 1045

| Size   | Length | WT / FT | WT / Bar |
|--------|--------|---------|----------|
| 1-1/4" | 12'    | 5.313   | 63.76    |

**1215** – Low carbon, resulphurized, and rephosphorized screw machine steel. This is very fast machining material with a smooth and bright finish used for studs, nuts, fasteners, etc. Can be case hardened. Average Mechanical Properties:

Yield – 60,000-75,000 psi.

Tensile – 70,000-85,000 psi.



### Cold Rolled Hexagons 1018

| Size   | Length | WT / FT | WT / Bar |
|--------|--------|---------|----------|
| 3/8"   | 12' rl | 0.414   | 4.97     |
| 7/16"  | 12' rl | 0.564   | 6.77     |
| 1/2"   | 12' rl | 0.736   | 8.83     |
| 9/16"  | 12' rl | 0.932   | 11.18    |
| 5/8"   | 12' rl | 1.150   | 13.80    |
| 11/16" | 12' rl | 1.392   | 16.70    |
| 3/4"   | 12' rl | 1.656   | 19.87    |
| 7/8"   | 12' rl | 2.254   | 27.05    |
| 1"     | 12' rl | 2.944   | 35.33    |
| 1-1/8" | 12' rl | 3.727   | 44.72    |
| 1-1/4" | 12' rl | 4.601   | 55.21    |
| 1-3/8" | 12' rl | 5.567   | 66.80    |
| 1-1/2" | 12' rl | 6.625   | 79.50    |



### Cold Rolled Hexagons 12L14

| Size   | Length | WT / FT | WT / Bar |
|--------|--------|---------|----------|
| 1/2"   | 12' rl | 0.736   | 8.83     |
| 5/8"   | 12' rl | 1.150   | 13.80    |
| 3/4"   | 12' rl | 1.656   | 19.87    |
| 7/8"   | 12' rl | 2.254   | 27.05    |
| 1"     | 12' rl | 2.945   | 35.34    |
| 1-1/8" | 12' rl | 3.727   | 44.72    |
| 1-1/4" | 12' rl | 4.601   | 55.21    |
| 1-1/2" | 12' rl | 6.625   | 79.50    |



### Cold Rolled 1144 Hexagons

#### Stress Relieved

| Size   | Length | WT / FT | WT / Length |
|--------|--------|---------|-------------|
| 9/16"  | 12' rl | 0.932   | 11.18       |
| 3/4"   | 12' rl | 1.656   | 19.87       |
| 1"     | 12' rl | 2.944   | 35.33       |
| 1-1/8" | 12' rl | 3.727   | 44.72       |

## Flats



### Cold Drawn Flats 1018

| Size         | Length | WT / FT | WT / Length |
|--------------|--------|---------|-------------|
| 1/8 x 1/2    | 12'    | 0.213   | 2.56        |
| 1/8 x 3/4    | 12'    | 0.319   | 3.83        |
| 1/8 x 1      | 12'    | 0.425   | 5.10        |
| 1/8 x 1-1/2  | 12'    | 0.638   | 7.66        |
| 1/8 x 1-3/4  | 12'    | 0.744   | 8.93        |
| 1/8 x 2      | 12'    | 0.850   | 10.20       |
| 1/8 x 2-1/2  | 12'    | 1.063   | 12.76       |
| 1/8 x 3      | 12'    | 1.275   | 15.30       |
| 1/8 x 4      | 12'    | 1.700   | 20.40       |
|              |        |         |             |
| 3/16 x 1/2   | 12'    | 0.319   | 3.83        |
| 3/16 x 3/4   | 12'    | 0.478   | 5.74        |
| 3/16 x 1     | 12'    | 0.638   | 7.66        |
| 3/16 x 1-1/2 | 12'    | 0.956   | 11.47       |
| 3/16 x 2     | 12'    | 1.275   | 15.30       |
| 3/16 x 2-1/2 | 12'    | 1.594   | 19.13       |
| 3/16 x 3     | 12'    | 1.913   | 22.96       |
| 3/16 x 4     | 12'    | 2.550   | 30.60       |
| 3/16 x 5     | 12'    | 3.188   | 38.26       |
| 3/16 x 6     | 12'    | 3.825   | 45.90       |
|              |        |         |             |
| 1/4 x 1/2    | 12'    | 0.425   | 5.10        |
| 1/4 x 3/4    | 12'    | 0.638   | 7.66        |
| 1/4 x 7/8    | 12'    | 0.744   | 8.93        |
| 1/4 x 1      | 12'    | 0.850   | 10.20       |
| 1/4 x 1-1/4  | 12'    | 1.063   | 12.76       |
| 1/4 x 1-1/2  | 12'    | 1.275   | 15.30       |
| 1/4 x 1-3/4  | 12'    | 1.488   | 17.86       |
| 1/4 x 2      | 12'    | 1.700   | 20.40       |
| 1/4 x 2-1/2  | 12'    | 2.125   | 25.50       |
| 1/4 x 3      | 12'    | 2.550   | 30.60       |
| 1/4 x 3-1/2  | 12'    | 2.975   | 35.70       |
| 1/4 x 4      | 12'    | 3.400   | 40.80       |
| 1/4 x 5      | 12'    | 4.250   | 51.00       |
| 1/4 x 6      | 12'    | 5.100   | 61.20       |
| 1/4 x 7      | 12'    | 5.950   | 71.40       |



### Cold Drawn Flats 1018

| Size         | Length | WT / FT | WT / Length |
|--------------|--------|---------|-------------|
| 5/16 x 1/2   | 12'    | 0.531   | 6.37        |
| 5/16 x 1     | 12'    | 1.063   | 12.76       |
| 5/16 x 1-1/2 | 12'    | 1.594   | 19.13       |
| 5/16 x 2     | 12'    | 2.125   | 25.50       |
|              |        |         |             |
| 3/8 x 1/2    | 12'    | 0.638   | 7.66        |
| 3/8 x 3/4    | 12'    | 0.956   | 11.47       |
| 3/8 x 1      | 12'    | 1.275   | 15.30       |
| 3/8 x 1-1/4  | 12'    | 1.594   | 19.13       |
| 3/8 x 1-1/2  | 12'    | 1.913   | 22.96       |
| 3/8 x 2      | 12'    | 2.550   | 30.60       |
| 3/8 x 2-1/2  | 12'    | 3.188   | 38.26       |
| 3/8 x 3      | 12'    | 3.825   | 45.90       |
| 3/8 x 3-1/2  | 12'    | 4.463   | 53.56       |
| 3/8 x 3-3/4  | 12'    | 4.781   | 57.37       |
| 3/8 x 4      | 12'    | 5.100   | 61.20       |
| 3/8 x 5      | 12'    | 6.375   | 76.50       |
| 3/8 x 6      | 12'    | 7.650   | 91.80       |
|              |        |         |             |
| 7/16 x 1     | 12'    | 1.488   | 17.86       |
| 7/16 x 1-1/2 | 12'    | 2.231   | 26.77       |
| 7/16 x 2     | 12'    | 2.975   | 35.70       |
| 7/16 x 3     | 12'    | 4.463   | 53.56       |
| 7/16 x 4     | 12'    | 5.950   | 71.40       |

**1018** – A low carbon steel that is easily welded or brazed with fair machinability and good hardening properties. Manufactured for cold forming and bending. Estimated Minimum Mechanical Properties (EMMP): Yield 54,000 psi. Tensile 64,000 psi.

## Flats



### Cold Drawn Flats 1018

| Size        | Length | WT / FT | WT / Length |
|-------------|--------|---------|-------------|
| 1/2 x 3/4   | 12'    | 1.275   | 15.30       |
| 1/2 x 1     | 12'    | 1.700   | 20.40       |
| 1/2 x 1-1/4 | 12'    | 2.125   | 25.50       |
| 1/2 x 1-1/2 | 12'    | 2.550   | 30.60       |
| 1/2 x 2     | 12'    | 3.400   | 40.80       |
| 1/2 x 2-1/2 | 12'    | 4.250   | 51.00       |
| 1/2 x 3     | 12'    | 5.100   | 61.20       |
| 1/2 x 3-1/2 | 12'    | 5.950   | 71.40       |
| 1/2 x 4     | 12'    | 6.800   | 81.60       |
| 1/2 x 4-1/2 | 12'    | 7.650   | 91.80       |
| 1/2 x 5     | 12'    | 8.500   | 102.00      |
| 1/2 x 6     | 12'    | 10.200  | 122.40      |
|             |        |         |             |
| 5/8 x 1     | 12'    | 2.125   | 25.50       |
| 5/8 x 1-1/4 | 12'    | 2.656   | 31.87       |
| 5/8 x 1-1/2 | 12'    | 3.188   | 38.26       |
| 5/8 x 1-3/4 | 12'    | 3.719   | 44.63       |
| 5/8 x 2     | 12'    | 4.250   | 51.00       |
| 5/8 x 2-1/2 | 12'    | 5.313   | 63.76       |
| 5/8 x 3     | 12'    | 6.375   | 76.50       |
| 5/8 x 4     | 12'    | 8.500   | 102.00      |
| 5/8 x 6     | 12'    | 12.750  | 153.00      |
| 5/8 x 7     | 12'    | 14.880  | 178.56      |



### Cold Drawn Flats 1018

| Size        | Length | WT / FT | WT / Length |
|-------------|--------|---------|-------------|
| 3/4 x 1     | 12'    | 2.550   | 30.60       |
| 3/4 x 1-1/2 | 12'    | 3.825   | 45.90       |
| 3/4 x 2     | 12'    | 5.100   | 61.20       |
| 3/4 x 2-1/2 | 12'    | 6.375   | 76.50       |
| 3/4 x 3     | 12'    | 7.650   | 91.80       |
| 3/4 x 4     | 12'    | 10.200  | 122.40      |
| 3/4 x 5     | 12'    | 12.750  | 153.00      |
| 3/4 x 5-1/2 | 12'    | 14.030  | 168.36      |
| 3/4 x 6     | 12'    | 15.300  | 183.60      |
|             |        |         |             |
| 1 x 1-1/4   | 12'    | 4.250   | 51.00       |
| 1 x 1-1/2   | 12'    | 5.100   | 61.20       |
| 1 x 2       | 12'    | 6.800   | 81.60       |
| 1 x 3       | 12'    | 10.200  | 122.40      |
| 1 x 3-1/2   | 12'    | 11.900  | 142.80      |
| 1 x 4       | 12'    | 13.600  | 163.20      |

# Forming



# Shearing





**AISI**  
**Thickness Tolerance Ranges**  
**Carbon Steel Sheets**  
**Hot Rolled • Hot Rolled Pickled & Oiled • Cold Rolled**

| Gauge No. | Thickness, inches |                     |                  | lbs. per sq. ft. | Gauge No. | Thickness, inches |                  | lbs. per sq. ft. |
|-----------|-------------------|---------------------|------------------|------------------|-----------|-------------------|------------------|------------------|
|           | Dec. Equiv.       | Tol. Range HR & P&O | Tol. Range CR    | Weight Equiv.    |           | Dec. Equiv.       | Tol. Range CR    | Weight Equiv.    |
| 4         | 0.2242            | 0.2332<br>0.2152    |                  | 9.375            | 19        | 0.0418            | 0.0458<br>0.0378 | 1.750            |
| 5         | 0.2092            | 0.2182<br>0.2002    |                  | 9.750            | 20        | 0.0359            | 0.0389<br>0.0329 | 1.500            |
| 6         | 0.1943            | 0.2033<br>0.1853    |                  | 8.125            | 21        | 0.0329            | 0.0359<br>0.0299 | 1.375            |
| 7         | 0.1793            | 0.1873<br>0.1713    | 0.1883<br>0.1703 | 7.500            | 22        | 0.0299            | 0.0329<br>0.0269 | 1.250            |
| 8         | 0.1644            | 0.1724<br>0.1564    | 0.1734<br>0.1554 | 6.875            | 23        | 0.0269            | 0.0299<br>0.0239 | 1.125            |
| 9         | 0.1495            | 0.1575<br>0.1415    | 0.1585<br>0.1405 | 6.250            | 24        | 0.0239            | 0.0269<br>0.0209 | 1.000            |
| 10        | 0.1345            | 0.1425<br>0.1265    | 0.1405<br>0.1285 | 5.625            | 25        | 0.0209            | 0.0239<br>0.0179 | 0.875            |
| 11        | 0.1196            | 0.1276<br>0.1116    | 0.1256<br>0.1136 | 5.000            | 26        | 0.0179            | 0.0199<br>0.0159 | 0.750            |
| 12        | 0.1046            | 0.1126<br>0.0966    | 0.1106<br>0.0986 | 4.375            | 27        | 0.0164            | 0.0184<br>0.0144 | 0.688            |
| 13        | 0.0897            | 0.0967<br>0.0827    | 0.0947<br>0.0847 | 3.750            | 28        | 0.0149            | 0.0169<br>0.0129 | 0.625            |
| 14        | 0.0747            | 0.0817<br>0.0677    | 0.0797<br>0.0697 | 3.125            | 29        | 0.0135            | 0.0155<br>0.0115 | 0.562            |
| 15        | 0.0673            | 0.0733<br>0.0613    | 0.0723<br>0.0623 | 2.812            | 30        | 0.0120            | 0.0130<br>0.0110 | 0.500            |
| 16        | 0.0598            | 0.0658<br>0.0538    | 0.0648<br>0.0548 | 2.500            |           |                   |                  |                  |
| 17        | 0.0538            | 0.0598<br>0.0478    | 0.0578<br>0.0498 | 2.250            |           |                   |                  |                  |
| 18        | 0.0478            | 0.0528<br>0.0428    | 0.0518<br>0.0438 | 2.000            |           |                   |                  |                  |




## Hot Rolled Sheets

Commercial Quality – Low Carbon – ASTM A-569

| Gauge       | Size     | WT / FT | WT / Sheet |
|-------------|----------|---------|------------|
| 16 ga. H.R. | 36 x 96  | 2.500   | 60.00      |
| 16 ga. H.R. | 36 x 120 | 2.500   | 75.00      |
| 16 ga. H.R. | 36 x 144 | 2.500   | 90.00      |
| 16 ga. H.R. | 42 x 120 | 2.500   | 87.50      |
| 16 ga. H.R. | 48 x 96  | 2.500   | 80.00      |
| 16 ga. H.R. | 48 x 120 | 2.500   | 100.00     |
| 16 ga. H.R. | 48 x 144 | 2.500   | 120.00     |
| 16 ga. H.R. | 60 x 96  | 2.500   | 100.00     |
| 16 ga. H.R. | 60 x 120 | 2.500   | 125.00     |
| 16 ga. H.R. | 60 x 144 | 2.500   | 150.00     |
| 14 ga. H.R. | 36 x 96  | 3.125   | 75.00      |
| 14 ga. H.R. | 36 x 120 | 3.125   | 93.75      |
| 14 ga. H.R. | 36 x 144 | 3.125   | 112.50     |
| 14 ga. H.R. | 42 x 96  | 3.125   | 87.50      |
| 14 ga. H.R. | 42 x 120 | 3.125   | 109.38     |
| 14 ga. H.R. | 48 x 96  | 3.125   | 100.00     |
| 14 ga. H.R. | 48 x 120 | 3.125   | 125.00     |
| 14 ga. H.R. | 48 x 144 | 3.125   | 150.00     |
| 14 ga. H.R. | 60 x 96  | 3.125   | 125.00     |
| 14 ga. H.R. | 60 x 120 | 3.125   | 156.25     |
| 14 ga. H.R. | 60 x 144 | 3.125   | 187.50     |
| 14 ga. H.R. | 72 x 96  | 3.125   | 150.00     |
| 14 ga. H.R. | 72 x 120 | 3.125   | 187.50     |
| 14 ga. H.R. | 72 x 144 | 3.125   | 225.00     |
| 13 ga. H.R. | 48 x 96  | 3.750   | 120.00     |
| 13 ga. H.R. | 48 x 120 | 3.750   | 150.00     |
| 12 ga. H.R. | 36 x 96  | 4.375   | 105.00     |
| 12 ga. H.R. | 36 x 120 | 4.375   | 131.25     |
| 12 ga. H.R. | 36 x 144 | 4.375   | 157.50     |
| 12 ga. H.R. | 42 x 120 | 4.375   | 153.12     |
| 12 ga. H.R. | 48 x 96  | 4.375   | 140.00     |
| 12 ga. H.R. | 48 x 120 | 4.375   | 175.00     |

| Gauge       | Size     | WT / FT | WT / Sheet |
|-------------|----------|---------|------------|
| 12 ga. H.R. | 48 x 144 | 4.375   | 210.00     |
| 12 ga. H.R. | 60 x 96  | 4.375   | 175.00     |
| 12 ga. H.R. | 60 x 120 | 4.375   | 218.75     |
| 12 ga. H.R. | 60 x 144 | 4.375   | 262.50     |
| 12 ga. H.R. | 72 x 96  | 4.375   | 210.00     |
| 12 ga. H.R. | 72 x 120 | 4.375   | 262.50     |
| 12 ga. H.R. | 72 x 144 | 4.375   | 315.00     |
| 11 ga. H.R. | 36 x 96  | 5.000   | 120.00     |
| 11 ga. H.R. | 36 x 120 | 5.000   | 150.00     |
| 11 ga. H.R. | 48 x 96  | 5.000   | 160.00     |
| 11 ga. H.R. | 48 x 120 | 5.000   | 200.00     |
| 11 ga. H.R. | 48 x 144 | 5.000   | 240.00     |
| 11 ga. H.R. | 60 x 96  | 5.000   | 200.00     |
| 11 ga. H.R. | 60 x 120 | 5.000   | 250.00     |
| 11 ga. H.R. | 60 x 144 | 5.000   | 300.00     |
| 11 ga. H.R. | 72 x 120 | 5.000   | 300.00     |
| 11 ga. H.R. | 72 x 144 | 5.000   | 360.00     |
| 10 ga. H.R. | 36 x 96  | 5.625   | 135.00     |
| 10 ga. H.R. | 36 x 120 | 5.625   | 168.75     |
| 10 ga. H.R. | 36 x 144 | 5.625   | 202.50     |
| 10 ga. H.R. | 42 x 120 | 5.625   | 196.88     |
| 10 ga. H.R. | 48 x 96  | 5.625   | 180.00     |
| 10 ga. H.R. | 48 x 120 | 5.625   | 225.00     |
| 10 ga. H.R. | 48 x 144 | 5.625   | 270.00     |
| 10 ga. H.R. | 60 x 96  | 5.625   | 225.00     |
| 10 ga. H.R. | 60 x 120 | 5.625   | 281.25     |
| 10 ga. H.R. | 60 x 144 | 5.625   | 337.50     |
| 10 ga. H.R. | 72 x 96  | 5.625   | 270.00     |
| 10 ga. H.R. | 72 x 120 | 5.625   | 337.50     |
| 10 ga. H.R. | 72 x 144 | 5.625   | 405.00     |
| 10 ga. H.R. | 84 x 96  | 5.625   | 315.00     |
| 10 ga. H.R. | 84 x 120 | 5.625   | 393.75     |

**Hot Rolled Sheets**

Commercial Quality – Low Carbon – ASTM A-569

| Gauge      | Size         | WT / FT | WT / Sheet |
|------------|--------------|---------|------------|
| 8 ga. H.R. | 48 x 96      | 6.875   | 220.00     |
| 8 ga. H.R. | 48 x 144     | 6.875   | 330.00     |
| 8 ga. H.R. | 48-5/8 x 120 | 6.875   | 278.58     |
| 7 ga. H.R. | 36 x 96      | 7.500   | 180.00     |
| 7 ga. H.R. | 36 x 120     | 7.500   | 225.00     |
| 7 ga. H.R. | 36 x 144     | 7.500   | 270.00     |
| 7 ga. H.R. | 48 x 96      | 7.500   | 240.00     |
| 7 ga. H.R. | 48 x 120     | 7.500   | 300.00     |
| 7 ga. H.R. | 48 x 144     | 7.500   | 360.00     |
| 7 ga. H.R. | 60 x 96      | 7.500   | 300.00     |
| 7 ga. H.R. | 60 x 120     | 7.500   | 375.00     |
| 7 ga. H.R. | 60 x 144     | 7.500   | 450.00     |
| 7 ga. H.R. | 72 x 96      | 7.500   | 360.00     |
| 7 ga. H.R. | 72 x 120     | 7.500   | 450.00     |
| 7 ga. H.R. | 72 x 144     | 7.500   | 540.00     |
| 3/16 H.R.  | 48 x 96      | 7.660   | 245.12     |
| 3/16 H.R.  | 48 x 120     | 7.660   | 306.40     |
| 4 ga. H.R. | 48 x 120     | 9.375   | 375.00     |

Low Carbon, Commercial Quality (CO) – A soft steel sheet well suited for forming and welding where surface finish is not critical. The low carbon content will allow material to bend easily in both directions. Conforms to ASTM-A569. Yield – 38,000 psi. Tensile – 52,000.

**Pickled and Oiled Sheets**

Hot Rolled – Low Carbon – ASTM A-569

| Gauge      | Size     | WT / FT | WT / Sheet |
|------------|----------|---------|------------|
| 14 ga. P&O | 48 x 96  | 3.125   | 100.00     |
| 14 ga. P&O | 48 x 120 | 3.125   | 125.00     |
| 14 ga. P&O | 60 x 120 | 3.125   | 156.25     |
| 13 ga. P&O | 48 x 144 | 3.750   | 180.00     |
| 12 ga. P&O | 48 x 96  | 4.375   | 140.00     |
| 12 ga. P&O | 48 x 120 | 4.375   | 175.00     |
| 12 ga. P&O | 48 x 144 | 4.375   | 210.00     |
| 12 ga. P&O | 60 x 96  | 4.375   | 175.00     |
| 12 ga. P&O | 60 x 120 | 4.375   | 218.75     |
| 11 ga. P&O | 48 x 96  | 5.000   | 160.00     |
| 11 ga. P&O | 48 x 120 | 5.000   | 200.00     |
| 10 ga. P&O | 48 x 96  | 5.625   | 180.00     |
| 10 ga. P&O | 48 x 120 | 5.625   | 225.00     |
| 10 ga. P&O | 48 x 144 | 5.625   | 270.00     |
| 10 ga. P&O | 60 x 120 | 5.625   | 281.25     |
| 7 ga. P&O  | 48 x 96  | 7.500   | 240.00     |
| 7 ga. P&O  | 48 x 120 | 7.500   | 300.00     |
| 7 ga. P&O  | 48 x 144 | 7.500   | 360.00     |
| 7 ga. P&O  | 60 x 120 | 7.500   | 375.00     |
| 3/16 P&O   | 48 X 120 | 7.660   | 306.40     |

**Pickled and Oiled Plate**

Hot Rolled – Low Carbon – ASTM A-569

| Gauge   | Size     | WT / FT | WT / Sheet |
|---------|----------|---------|------------|
| 1/4 P&O | 48 x 120 | 10.210  | 408.40     |

HR Pickled and Oiled – Commercial quality steel that has been acid pickled to remove mill oxide. This improves surface appearance, finishing quality, and helps to cause less wear on tooling. Sheets are oiled to prevent surface rust. Fabrication characteristics are the same as commercial quality. Conforms to ASTM-A569.



## Cold Rolled Sheets

Commercial Quality – Low Carbon – ASTM A-366

| Gauge       | Size     | WT / FT | WT / Sheet |
|-------------|----------|---------|------------|
| 22 ga. C.R. | 36 x 120 | 1.250   | 37.50      |
| 22 ga. C.R. | 48 x 96  | 1.250   | 40.00      |
| 22 ga. C.R. | 48 x 120 | 1.250   | 50.00      |
| 20 ga. C.R. | 48 x 96  | 1.500   | 48.00      |
| 20 ga. C.R. | 48 x 120 | 1.500   | 60.00      |
| 20 ga. C.R. | 48 x 144 | 1.500   | 72.00      |
| 20 ga. C.R. | 60 x 120 | 1.500   | 75.00      |
| 18 ga. C.R. | 36 x 96  | 2.000   | 48.00      |
| 18 ga. C.R. | 36 x 120 | 2.000   | 60.00      |
| 18 ga. C.R. | 48 x 96  | 2.000   | 64.00      |
| 18 ga. C.R. | 48 x 120 | 2.000   | 80.00      |
| 18 ga. C.R. | 48 x 144 | 2.000   | 96.00      |
| 18 ga. C.R. | 60 x 120 | 2.000   | 100.00     |
| 18 ga. C.R. | 60 x 144 | 2.000   | 120.00     |
| 16 ga. C.R. | 36 x 96  | 2.500   | 60.00      |
| 16 ga. C.R. | 36 x 120 | 2.500   | 75.00      |
| 16 ga. C.R. | 36 x 144 | 2.500   | 90.00      |
| 16 ga. C.R. | 48 x 96  | 2.500   | 80.00      |
| 16 ga. C.R. | 48 x 120 | 2.500   | 100.00     |
| 16 ga. C.R. | 60 x 120 | 2.500   | 125.00     |
| 16 ga. C.R. | 60 x 144 | 2.500   | 150.00     |
| 16 ga. C.R. | 72 x 120 | 2.500   | 150.00     |



## Cold Rolled Sheets

Commercial Quality – Low Carbon – ASTM A-366

| Gauge       | Size     | WT / FT | WT / Sheet |
|-------------|----------|---------|------------|
| 14 ga. C.R. | 36 x 96  | 3.125   | 75.00      |
| 14 ga. C.R. | 36 x 120 | 3.125   | 93.75      |
| 14 ga. C.R. | 36 x 144 | 3.125   | 112.50     |
| 14 ga. C.R. | 48 x 96  | 3.125   | 100.00     |
| 14 ga. C.R. | 48 x 120 | 3.125   | 125.00     |
| 14 ga. C.R. | 48 x 144 | 3.125   | 150.00     |
| 14 ga. C.R. | 60 x 120 | 3.125   | 156.25     |
| 14 ga. C.R. | 60 x 144 | 3.125   | 187.50     |
| 14 ga. C.R. | 72 x 120 | 3.125   | 187.50     |
| 14 ga. C.R. | 72 x 144 | 3.125   | 225.00     |
| 12 ga. C.R. | 48 x 96  | 4.375   | 140.00     |
| 12 ga. C.R. | 48 x 120 | 4.375   | 175.00     |
| 12 ga. C.R. | 60 x 120 | 4.375   | 218.75     |
| 11 ga. C.R. | 36 x 96  | 5.000   | 120.00     |
| 11 ga. C.R. | 36 x 120 | 5.000   | 150.00     |
| 11 ga. C.R. | 48 x 96  | 5.000   | 160.00     |
| 11 ga. C.R. | 48 x 120 | 5.000   | 200.00     |
| 10 ga. C.R. | 48 x 96  | 5.625   | 180.00     |
| 10 ga. C.R. | 48 x 120 | 5.625   | 225.00     |

Cold Rolled Sheet – A superior surface finish to hot rolled pickled and oiled and closer thickness tolerances. The matte finish is an excellent base for paints, enamels and lacquers. Cold Rolled Sheets have good weldability and formability bending easily in both directions. Oiled to prevent surface rust. Conforms to ASTM A-366.

## Galvanized Sheets G-90



### Galvanized Sheets

| Gauge  | Size     | WT / SQ FT | WT / Sheet |
|--------|----------|------------|------------|
| 30 ga. | 36 x 96  | 0.656      | 15.74      |
| 30 ga. | 36 x 120 | 0.656      | 19.68      |
| 28 ga. | 36 x 96  | 0.781      | 18.74      |
| 28 ga. | 36 x 120 | 0.781      | 23.43      |
| 26 ga. | 36 x 96  | 0.906      | 21.74      |
| 26 ga. | 36 x 120 | 0.906      | 27.18      |
| 26 ga. | 48 x 96  | 0.906      | 28.99      |
| 26 ga. | 48 x 120 | 0.906      | 36.24      |
| 26 ga. | 60 x 96  | 0.906      | 36.24      |
| 26 ga. | 60 x 120 | 0.906      | 45.30      |
| 24 ga. | 36 x 96  | 1.156      | 27.74      |
| 24 ga. | 36 x 120 | 1.156      | 34.68      |
| 24 ga. | 48 x 96  | 1.156      | 36.99      |
| 24 ga. | 48 x 120 | 1.156      | 46.24      |
| 24 ga. | 60 x 120 | 1.156      | 57.80      |
| 22 ga. | 36 x 96  | 1.406      | 33.74      |
| 22 ga. | 36 x 120 | 1.406      | 42.18      |
| 22 ga. | 48 x 96  | 1.406      | 44.99      |
| 22 ga. | 48 x 120 | 1.406      | 56.24      |
| 22 ga. | 48 x 144 | 1.406      | 67.49      |
| 22 ga. | 60 x 120 | 1.406      | 70.30      |
| 20 ga. | 36 x 96  | 1.656      | 39.74      |
| 20 ga. | 36 x 120 | 1.656      | 49.68      |
| 20 ga. | 36 x 144 | 1.656      | 59.62      |
| 20 ga. | 48 x 96  | 1.656      | 52.99      |
| 20 ga. | 48 x 120 | 1.656      | 66.24      |
| 20 ga. | 48 x 144 | 1.656      | 79.49      |
| 20 ga. | 60 x 120 | 1.656      | 82.80      |



### Galvanized Sheets

| Gauge  | Size     | WT / SQ FT | WT / Sheet |
|--------|----------|------------|------------|
| 18 ga. | 36 x 96  | 2.156      | 51.74      |
| 18 ga. | 36 x 120 | 2.156      | 64.68      |
| 18 ga. | 48 x 96  | 2.156      | 68.99      |
| 18 ga. | 48 x 120 | 2.156      | 86.24      |
| 18 ga. | 48 x 144 | 2.156      | 103.49     |
| 18 ga. | 60 x 120 | 2.156      | 107.80     |
| 18 ga. | 60 x 144 | 2.156      | 129.36     |
| 16 ga. | 36 x 96  | 2.656      | 63.74      |
| 16 ga. | 36 x 120 | 2.656      | 79.68      |
| 16 ga. | 48 x 96  | 2.656      | 84.99      |
| 16 ga. | 48 x 120 | 2.656      | 106.24     |
| 16 ga. | 60 x 96  | 2.656      | 106.24     |
| 16 ga. | 60 x 120 | 2.656      | 132.80     |
| 14 ga. | 36 x 96  | 3.281      | 78.74      |
| 14 ga. | 36 x 120 | 3.281      | 98.43      |
| 14 ga. | 36 x 144 | 3.281      | 118.12     |
| 14 ga. | 48 x 96  | 3.281      | 104.99     |
| 14 ga. | 48 x 120 | 3.281      | 131.24     |
| 14 ga. | 48 x 144 | 3.281      | 157.49     |
| 14 ga. | 60 x 96  | 3.281      | 131.24     |
| 14 ga. | 60 x 120 | 3.281      | 164.05     |
| 12 ga. | 36 x 96  | 4.531      | 108.74     |
| 12 ga. | 36 x 120 | 4.531      | 135.93     |
| 12 ga. | 48 x 96  | 4.531      | 144.99     |
| 12 ga. | 48 x 120 | 4.531      | 181.24     |
| 12 ga. | 48 x 144 | 4.531      | 217.49     |
| 12 ga. | 60 x 96  | 4.531      | 181.24     |
| 12 ga. | 60 x 120 | 4.531      | 226.55     |
| 12 ga. | 60 x 144 | 4.531      | 271.86     |
| 11 ga. | 48 x 120 | 5.156      | 206.24     |
| 10 ga. | 48 x 96  | 5.781      | 184.99     |
| 10 ga. | 48 x 120 | 5.781      | 231.24     |
| 10 ga. | 48 x 144 | 5.781      | 277.49     |
| 10 ga. | 60 x 120 | 5.781      | 289.05     |

**Galvanized Sheet** – Galvanized sheets are produced from low-carbon, pickled steel that is annealed and zinc coated in a continuous hot dip process. This material is suitable for stamping, cold drawing, and forming without causing the zinc coating to peel or flake. They can be welded and soldered. The standard thickness coating is G-90. All 14 ga. and heavier are commercial quality and all 16 ga. and lighter are lock forming quality. Conforms to ASTM-A653.

## Galvannealed & Paintgrip Sheets



### Paintgrip Sheets

ASTM A-526 G-90

| Gauge  | Size     | WT / SQ FT | WT / Sheet |
|--------|----------|------------|------------|
| 24 ga. | 48 x 96  | 1.156      | 36.99      |
| 24 ga. | 48 x 120 | 1.156      | 46.24      |

Paintgrip Sheets – A phosphate film is added to the surface of a standard galvanized sheet for paint adherence. These sheets have a flat, dull gray appearance with no spangles. Can be rolled, formed, or stamped without losing its coating. Used primarily for signs or other applications where excellent surface finish is required.

Galvannealed Sheets – Sheets are heat treated after coating which bonds the zinc to the steel base and eliminates the spangle. No surface preparation is necessary before painting. Coating weight is A60 or A40.



### Galvannealed Sheets

(A40 Coating)


| Gauge  | Size     | WT / SQ FT | WT / Sheet |
|--------|----------|------------|------------|
| 20 ga. | 48 x 120 | 1.656      | 66.24      |
| 16 ga. | 48 x 96  | 2.656      | 84.99      |
| 16 ga. | 48 x 120 | 2.656      | 106.24     |
| 14 ga. | 48 x 96  | 3.281      | 104.99     |
| 14 ga. | 48 x 120 | 3.281      | 131.24     |
| 14 ga. | 60 x 96  | 3.281      | 131.24     |
| 14 ga. | 60 x 120 | 3.281      | 164.05     |
| 12 ga. | 60 x 120 | 4.531      | 226.55     |



### Galvannealed Sheets

(A60 Coating)

| Gauge  | Size     | WT / SQ FT | WT / Sheet |
|--------|----------|------------|------------|
| 22 ga. | 48 x 120 | 1.406      | 56.24      |
| 18 ga. | 48 x 120 | 2.156      | 86.24      |
| 18 ga. | 60 x 144 | 2.156      | 129.36     |



## Hot Rolled Plates

Commercial Quality – Low Carbon 1008-1010

| Size  | Width    | WT / SQ FT | WT / Sheet |
|-------|----------|------------|------------|
| 1/4"  | 36 x 96  | 10.210     | 245.04     |
| 1/4"  | 36 x 120 | 10.210     | 306.30     |
| 1/4"  | 36 x 144 | 10.210     | 367.56     |
| 1/4"  | 48 x 96  | 10.210     | 326.72     |
| 1/4"  | 48 x 120 | 10.210     | 408.40     |
| 1/4"  | 48 x 144 | 10.210     | 490.08     |
| 1/4"  | 50 x 120 | 10.210     | 425.42     |
| 1/4"  | 60 x 96  | 10.210     | 408.40     |
| 1/4"  | 60 x 120 | 10.210     | 510.50     |
| 1/4"  | 60 x 144 | 10.210     | 612.60     |
| 1/4"  | 60 x 240 | 10.210     | 1021.00    |
| 1/4"  | 72 x 96  | 10.210     | 490.08     |
| 1/4"  | 72 x 120 | 10.210     | 612.60     |
| 1/4"  | 72 x 144 | 10.210     | 735.12     |
| 5/16" | 48 x 96  | 12.760     | 408.32     |
| 5/16" | 48 x 120 | 12.760     | 510.40     |
| 5/16" | 48 x 144 | 12.760     | 612.48     |
| 5/16" | 60 x 96  | 12.760     | 510.40     |
| 5/16" | 60 x 120 | 12.760     | 638.00     |
| 5/16" | 60 x 144 | 12.760     | 765.60     |

| Size | Width    | WT / SQ FT | WT / Sheet |
|------|----------|------------|------------|
| 3/8" | 36 x 96  | 15.320     | 367.68     |
| 3/8" | 36 x 120 | 15.320     | 459.60     |
| 3/8" | 48 x 96  | 15.320     | 490.24     |
| 3/8" | 48 x 120 | 15.320     | 612.80     |
| 3/8" | 48 x 144 | 15.320     | 735.36     |
| 3/8" | 60 x 96  | 15.320     | 612.80     |
| 3/8" | 60 x 120 | 15.320     | 766.00     |
| 3/8" | 60 x 144 | 15.320     | 919.20     |
| 1/2" | 36 x 96  | 20.420     | 490.08     |
| 1/2" | 36 x 120 | 20.420     | 612.60     |
| 1/2" | 48 x 96  | 20.420     | 653.44     |
| 1/2" | 48 x 120 | 20.420     | 816.80     |
| 1/2" | 60 x 120 | 20.420     | 1021.00    |
| 1/2" | 72 x 120 | 20.420     | 1225.20    |
| 1/2" | 72 x 144 | 20.420     | 1470.24    |

ASTM A36 – Low carbon, structural quality steel used in bridges, building construction, and general structural applications. Minimum Mechanical Properties:

Yield – 36,000 spi. min. Tensile – 58,000-80,000 psi.



## Hot Rolled Plates

ASTM A-36

| Size       | Width        | WT / SQ FT | WT / Sheet |
|------------|--------------|------------|------------|
| 3/16" A-36 | 60 x 120     | 7.660      | 383.00     |
| 3/16" A-36 | 60 x 144     | 7.660      | 459.60     |
| 1/4" A-36  | 48 x 96      | 10.210     | 326.72     |
| 1/4" A-36  | 48 x 120     | 10.210     | 408.40     |
| 1/4" A-36  | 48 x 144     | 10.210     | 490.08     |
| 1/4" A-36  | 60 x 96      | 10.210     | 408.40     |
| 1/4" A-36  | 60 x 120     | 10.210     | 510.50     |
| 1/4" A-36  | 60 x 240     | 10.210     | 1021.00    |
| 1/4" A-36  | 72 x 120     | 10.210     | 612.60     |
| 1/4" A-36  | 72 x 144     | 10.210     | 735.12     |
| 1/4" A-36  | 72 x 240     | 10.210     | 1225.20    |
| 1/4" A-36  | 96 x 144     | 10.210     | 980.16     |
| 1/4" A-36  | 96 x 240     | 10.210     | 1633.60    |
| 1/4" A-36  | 120 x 240    | 10.210     | 2042.00    |
| 5/16" A-36 | 60 x 120     | 12.760     | 638.00     |
| 5/16" A-36 | 72 x 96      | 12.760     | 612.48     |
| 5/16" A-36 | 72 x 120     | 12.760     | 765.60     |
| 5/16" A-36 | 72 x 240     | 12.760     | 1531.20    |
| 5/16" A-36 | 96 x 240     | 12.760     | 2041.60    |
| 5/16" A-36 | 120 x 240    | 12.760     | 2552.00    |
| 3/8" A-36  | 48 x 96      | 15.320     | 490.24     |
| 3/8" A-36  | 48 x 120     | 15.320     | 612.80     |
| 3/8" A-36  | 59-3/4 x 96  | 15.320     | 610.25     |
| 3/8" A-36  | 59-3/4 x 120 | 15.320     | 762.81     |
| 3/8" A-36  | 60 x 96      | 15.320     | 612.80     |
| 3/8" A-36  | 60 x 120     | 15.320     | 766.00     |
| 3/8" A-36  | 60 x 144     | 15.320     | 919.20     |
| 3/8" A-36  | 60 x 240     | 15.320     | 1532.00    |

| Size      | Width     | WT / SQ FT | WT / Sheet |
|-----------|-----------|------------|------------|
| 3/8" A-36 | 72 x 120  | 15.320     | 919.20     |
| 3/8" A-36 | 72 x 144  | 15.320     | 1103.04    |
| 3/8" A-36 | 72 x 240  | 15.320     | 1838.40    |
| 3/8" A-36 | 84 x 240  | 15.320     | 2144.80    |
| 3/8" A-36 | 96 x 240  | 15.320     | 2451.20    |
| 3/8" A-36 | 120 x 240 | 15.320     | 3064.00    |
| 1/2" A-36 | 48 x 96   | 20.420     | 653.44     |
| 1/2" A-36 | 48 x 120  | 20.420     | 816.80     |
| 1/2" A-36 | 48 x 144  | 20.420     | 980.16     |
| 1/2" A-36 | 60 x 120  | 20.420     | 1021.00    |
| 1/2" A-36 | 60 x 144  | 20.420     | 1225.20    |
| 1/2" A-36 | 72 x 120  | 20.420     | 1225.20    |
| 1/2" A-36 | 72 x 144  | 20.420     | 1470.24    |
| 1/2" A-36 | 72 x 240  | 20.420     | 2450.40    |
| 1/2" A-36 | 84 x 240  | 20.420     | 2858.80    |
| 1/2" A-36 | 96 x 240  | 20.420     | 3267.20    |
| 5/8" A-36 | 48 x 96   | 25.530     | 816.96     |
| 5/8" A-36 | 48 x 120  | 25.530     | 1021.20    |
| 5/8" A-36 | 60 x 120  | 25.530     | 1276.50    |
| 5/8" A-36 | 72 x 120  | 25.530     | 1531.80    |
| 5/8" A-36 | 84 x 144  | 25.530     | 2144.52    |
| 5/8" A-36 | 84 x 240  | 25.530     | 3574.20    |
| 5/8" A-36 | 96 x 240  | 25.530     | 4084.80    |





## Hot Rolled Plates

ASTM A-36

| Size        | Width    | WT / SQ FT | WT / Sheet |
|-------------|----------|------------|------------|
| 3/4" A-36   | 48 x 96  | 30.630     | 980.16     |
| 3/4" A-36   | 48 x 120 | 30.630     | 1225.20    |
| 3/4" A-36   | 60 x 120 | 30.630     | 1531.50    |
| 3/4" A-36   | 72 x 120 | 30.630     | 1837.80    |
| 3/4" A-36   | 84 x 120 | 30.630     | 2144.10    |
| 3/4" A-36   | 84 x 144 | 30.630     | 2572.92    |
| 3/4" A-36   | 84 x 240 | 30.630     | 4288.20    |
| 3/4" A-36   | 96 x 240 | 30.630     | 4900.80    |
| 7/8" A-36   | 72 x 120 | 35.740     | 2144.40    |
| 7/8" A-36   | 96 x 240 | 35.740     | 5718.40    |
| 1" A-36     | 48 x 96  | 40.840     | 1306.88    |
| 1" A-36     | 48 x 120 | 40.840     | 1633.60    |
| 1" A-36     | 60 x 120 | 40.840     | 2042.00    |
| 1" A-36     | 72 x 120 | 40.840     | 2450.40    |
| 1" A-36     | 72 x 240 | 40.840     | 4900.80    |
| 1" A-36     | 84 x 144 | 40.840     | 3430.56    |
| 1" A-36     | 84 x 240 | 40.840     | 5717.60    |
| 1" A-36     | 96 x 144 | 40.840     | 3920.64    |
| 1" A-36     | 96 x 150 | 40.840     | 4084.00    |
| 1" A-36     | 96 x 240 | 40.840     | 6534.40    |
| 1-1/8" A-36 | 84 x 144 | 45.950     | 3859.80    |
| 1-1/4" A-36 | 48 x 72  | 51.050     | 1225.20    |
| 1-1/4" A-36 | 72 x 144 | 51.050     | 3675.60    |
| 1-1/4" A-36 | 72 x 240 | 51.050     | 6126.00    |
| 1-1/4" A-36 | 84 x 144 | 51.050     | 4288.20    |
| 1-1/4" A-36 | 84 x 240 | 51.050     | 7147.00    |
| 1-3/8" A-36 | 48 x 72  | 56.160     | 1347.84    |
| 1-3/8" A-36 | 72 x 144 | 56.160     | 4043.52    |

| Size        | Width    | WT / SQ FT | WT / Sheet |
|-------------|----------|------------|------------|
| 1-1/2" A-36 | 48 x 72  | 61.260     | 1470.24    |
| 1-1/2" A-36 | 72 x 144 | 61.260     | 4410.72    |
| 1-1/2" A-36 | 84 x 144 | 61.260     | 5145.84    |
| 1-1/2" A-36 | 96 x 144 | 61.260     | 5880.96    |
| 1-3/4" A-36 | 72 x 144 | 71.470     | 5145.84    |
| 2" A-36     | 48 x 72  | 81.680     | 1960.32    |
| 2" A-36     | 72 x 144 | 81.680     | 5880.96    |
| 2" A-36     | 84 x 144 | 81.680     | 6861.12    |
| 2" A-36     | 96 x 144 | 81.680     | 7841.28    |
| 2-1/4" A-36 | 74 x 144 | 91.890     | 6799.86    |
| 2-1/4" A-36 | 84 x 144 | 91.890     | 7718.76    |
| 2-1/2" A-36 | 84 x 144 | 102.100    | 8576.40    |
| 2-3/4" A-36 | 84 x 120 | 112.310    | 7861.70    |
| 3" A-36     | 84 x 120 | 122.520    | 8576.40    |
| 3" A-36     | 84 x 144 | 122.520    | 10291.68   |
| 3-1/2" A-36 | 84 x 144 | 142.940    | 12006.96   |
| 4" A-36     | 84 x 120 | 163.360    | 11435.20   |

## Floor Plate



### Floor Plate (Medium Pattern)

| Size   | Width    | WT / SQ FT | WT / Sheets |
|--------|----------|------------|-------------|
| 16 ga. | 48 x 96  | 3.000      | 96.00       |
| 16 ga. | 48 x 120 | 3.000      | 120.00      |
| 14 ga. | 48 x 96  | 3.750      | 120.00      |
| 14 ga. | 48 x 120 | 3.750      | 150.00      |
| 14 ga. | 60 x 120 | 3.750      | 187.50      |
| 12 ga. | 48 x 96  | 5.250      | 168.00      |
| 12 ga. | 48 x 120 | 5.250      | 210.00      |
| 12 ga. | 60 x 96  | 5.250      | 210.00      |
| 12 ga. | 60 x 120 | 5.250      | 262.50      |
| 12 ga. | 60 x 144 | 5.250      | 315.00      |
| 12 ga. | 60 x 240 | 5.250      | 525.00      |
| 1/8"   | 48 x 96  | 6.160      | 197.12      |
| 1/8"   | 48 x 120 | 6.160      | 246.40      |
| 1/8"   | 48 x 144 | 6.160      | 295.68      |
| 1/8"   | 60 x 96  | 6.160      | 246.40      |
| 1/8"   | 60 x 120 | 6.160      | 308.00      |
| 1/8"   | 60 x 144 | 6.160      | 369.60      |
| 1/8"   | 72 x 96  | 6.160      | 295.68      |
| 1/8"   | 72 x 120 | 6.160      | 369.60      |
| 1/8"   | 72 x 144 | 6.160      | 443.52      |

**Floor Plate** – A low carbon product with raised lugs in a cross hatch pattern which provides better traction for driving or walking. Conforms to ASTM A-786. Thickness does not include projections.



### Floor Plate (Medium Pattern)

| Size  | Width    | WT / SQ FT | WT / Sheets |
|-------|----------|------------|-------------|
| 3/16" | 48 x 96  | 8.710      | 278.72      |
| 3/16" | 48 x 120 | 8.710      | 348.40      |
| 3/16" | 48 x 144 | 8.710      | 418.08      |
| 3/16" | 60 x 96  | 8.710      | 348.40      |
| 3/16" | 60 x 120 | 8.710      | 435.50      |
| 3/16" | 60 x 144 | 8.710      | 522.60      |
| 3/16" | 72 x 96  | 8.710      | 418.08      |
| 3/16" | 72 x 120 | 8.710      | 522.60      |
| 1/4"  | 48 x 96  | 11.260     | 360.32      |
| 1/4"  | 48 x 120 | 11.260     | 450.40      |
| 1/4"  | 60 x 96  | 11.260     | 450.40      |
| 1/4"  | 60 x 120 | 11.260     | 563.00      |
| 1/4"  | 60 x 144 | 11.260     | 675.60      |
| 1/4"  | 72 x 120 | 11.260     | 675.60      |
| 3/8"  | 48 x 96  | 16.370     | 523.84      |
| 3/8"  | 48 x 120 | 16.370     | 654.80      |
| 3/8"  | 60 x 96  | 16.370     | 654.80      |
| 3/8"  | 60 x 120 | 16.370     | 818.50      |

### Abrasion Resisting Sheet & Plate



| Size   | Width    | WT / SQ FT | WT / Sheet |
|--------|----------|------------|------------|
| 10 ga. | 48 x 120 | 5.625      | 225.00     |
| 3/16"  | 48 x 120 | 7.660      | 306.40     |
| 3/16"  | 60 x 120 | 7.660      | 383.00     |
| 1/4"   | 48 x 120 | 10.210     | 408.40     |
| 1/4"   | 60 x 120 | 10.210     | 510.50     |
| 3/8"   | 48 x 120 | 15.320     | 612.80     |
| 3/8"   | 60 x 120 | 15.320     | 766.00     |

**AR MED Sheet and Plate** – This abrasion resisting product is medium carbon, high manganese, and has a Brinell Hardness typically in the range of 200/250. This material is produced primarily for use in the materials-handling industry such as sideboards and guides on conveyors, chutes, hoppers and mixer drums. Can be welded, machined, drilled, punched, and takes a moderate amount of forming and rolling.

## High Strength Sheets & Plate



### High Strength A572-50

| Thickness | Size     | WT / SQ FT | WT / Sheet |
|-----------|----------|------------|------------|
| 5/16"     | 72 x 120 | 12.760     | 765.60     |
| 5/16"     | 84 x 120 | 12.760     | 893.20     |
| 5/16"     | 96 x 120 | 12.760     | 1020.80    |
| 3/8"      | 73 x 242 | 15.320     | 1879.47    |
| 5/8"      | 48 x 120 | 25.530     | 1021.20    |
| 5/8"      | 60 x 120 | 25.530     | 1276.50    |
| 3/4"      | 72 x 120 | 30.630     | 1837.80    |
| 3/4"      | 96 x 240 | 30.630     | 4900.80    |
| 1"        | 72 x 135 | 40.840     | 2756.70    |
| 2"        | 96 x 144 | 81.680     | 7841.28    |

| High Strength HR A607-45 |          |            |            |
|--------------------------|----------|------------|------------|
| Thickness                | Size     | WT / SQ FT | WT / Sheet |
| 5 ga.                    | 48 x 125 | 9.750      | 406.25     |



### High Strength HR A607-50

| Thickness | Size     | WT / SQ FT | WT / Sheet |
|-----------|----------|------------|------------|
| 12 ga.    | 48 x 120 | 4.375      | 175.00     |
| 11 ga.    | 72 x 144 | 5.000      | 360.00     |
| 10 ga.    | 48 x 120 | 5.625      | 225.00     |
| 10 ga.    | 72 x 120 | 5.625      | 337.50     |
| 7 ga.     | 60 x 120 | 7.500      | 375.00     |
| 7 ga.     | 60 x 144 | 7.500      | 450.00     |
| 3/16"     | 48 x 96  | 7.660      | 245.12     |
| 3/16"     | 54 x 120 | 7.660      | 344.70     |
| 3/16"     | 72 x 96  | 7.660      | 367.68     |
| 3/16"     | 72 x 120 | 7.660      | 459.60     |
| 3/16"     | 72 x 144 | 7.660      | 551.52     |
| 1/4"      | 72 x 120 | 10.210     | 612.60     |
| 1/4"      | 72 x 144 | 10.210     | 735.12     |

| High Strength A656-80 |          |            |            |
|-----------------------|----------|------------|------------|
| Thickness             | Size     | WT / SQ FT | WT / Sheet |
| 3/8"                  | 48 x 96  | 15.320     | 490.24     |
| 1/2"                  | 60 x 120 | 20.420     | 1021.00    |
| 5/8"                  | 84 x 132 | 25.530     | 1965.81    |
| 3/4"                  | 85 x 241 | 30.630     | 4357.33    |

High Strength Sheets – High Strength/Low Alloy (HSLA) – High Strength Sheets have improved formability and better weldability than commercial quality sheets and are used where weight reduction is a factor.

ASTM A572-50 – Good cold forming and welding properties. Atmospheric corrosion resistance is the same as carbon steel. Estimated Minimum Mechanical Properties (EMMP): Yield – 50,000 psi. Tensile – 65,000 psi.

ASTM A607 – Produced to specific minimum yield strengths where corrosion resistance is not a requirement. A607 has good formability and weldability. Estimated Minimum Mechanical Properties (EMMP) –

Grade 45 – Yield – 45,000 psi. Tensile – 60,000 psi.

Grade 50 – Yield – 50,000 psi. Tensile – 65,000 psi.

ASTM A656-80 – Good cold forming, welding, and toughness properties.

## High Strength Sheets & Plate



### High Strength HR A715-50

| Thickness | Size     | WT / SQ FT | WT / Sheet |
|-----------|----------|------------|------------|
| 12 ga.    | 48 x 120 | 4.375      | 175.00     |
| 12 ga.    | 48 x 144 | 4.375      | 210.00     |
| 12 ga.    | 60 x 120 | 4.375      | 218.75     |
| 12 ga.    | 60 x 144 | 4.375      | 262.50     |
| 11 ga.    | 60 x 120 | 5.000      | 250.00     |
| 11 ga.    | 60 x 144 | 5.000      | 300.00     |
| 10 ga.    | 48 x 96  | 5.625      | 180.00     |
| 10 ga.    | 48 x 120 | 5.625      | 225.00     |
| 10 ga.    | 48 x 144 | 5.625      | 270.00     |
| 10 ga.    | 60 x 96  | 5.625      | 225.00     |
| 10 ga.    | 60 x 120 | 5.625      | 281.25     |
| 10 ga.    | 60 x 144 | 5.625      | 337.50     |
| 10 ga.    | 72 x 96  | 5.625      | 270.00     |
| 10 ga.    | 72 x 120 | 5.625      | 337.50     |
| 10 ga.    | 72 x 144 | 5.625      | 405.00     |
| 9 ga.     | 60 x 120 | 6.250      | 312.50     |
| 7 ga.     | 48 x 120 | 7.500      | 300.00     |
| 7 ga.     | 48 x 144 | 7.500      | 360.00     |
| 7 ga.     | 60 x 96  | 7.500      | 300.00     |
| 7 ga.     | 60 x 120 | 7.500      | 375.00     |
| 7 ga.     | 60 x 144 | 7.500      | 450.00     |
| 3/16"     | 48 x 96  | 7.660      | 245.12     |
| 3/16"     | 48 x 120 | 7.660      | 306.40     |
| 3/16"     | 48 x 144 | 7.660      | 367.68     |
| 3/16"     | 60 x 120 | 7.660      | 383.00     |
| 3/16"     | 60 x 144 | 7.660      | 459.60     |
| 3/16"     | 72 x 120 | 7.660      | 459.60     |



### High Strength HR A715-50

| Thickness | Size     | WT / SQ FT | WT / Sheet |
|-----------|----------|------------|------------|
| 1/4"      | 48 x 96  | 10.210     | 326.72     |
| 1/4"      | 48 x 120 | 10.210     | 408.40     |
| 1/4"      | 48 x 144 | 10.210     | 490.08     |
| 1/4"      | 60 x 96  | 10.210     | 408.40     |
| 1/4"      | 60 x 120 | 10.210     | 510.50     |
| 1/4"      | 60 x 144 | 10.210     | 612.60     |
| 3/8"      | 48 x 120 | 15.320     | 612.80     |
| 3/8"      | 60 x 120 | 15.320     | 766.00     |
| 1/2"      | 60 x 120 | 20.420     | 1021.00    |



### High Strength HR A715-80

| Thickness | Size         | WT / SQ FT | WT / Sheet |
|-----------|--------------|------------|------------|
| 10 ga.    | 60 x 144     | 5.625      | 337.50     |
| 10 ga.    | 72 x 144     | 5.625      | 405.00     |
| 3/16"     | 60 x 120     | 7.660      | 383.00     |
| 1/4"      | 60-1/2 x 120 | 10.210     | 514.75     |
| 1/4"      | 61 x 96      | 10.210     | 415.21     |
| 1/4"      | 61 x 120     | 10.210     | 519.01     |
| 5/16"     | 48 x 103     | 12.760     | 438.09     |
| 3/8"      | 72 x 120     | 15.320     | 919.20     |

**ASTM A 715** – Best formability and weldability with good fatigue resistance. Suited for applications involving forming tight radii. Estimated Minimum Mechanical Properties (EMMP) –

Grade 50 – Yield – 50,000 psi. Tensile 65,000 psi.

Grade 80 – Yield – 80,000 psi. Tensile – 90,000 psi.

## Hot Rolled Coils

| Thickness<br>and Width | Lbs. per<br>Sq. Ft. | Grade |     |     |
|------------------------|---------------------|-------|-----|-----|
|                        |                     | 1010  | P&O | A36 |
| 16ga. x 36             | 2.500               | x     | —   | —   |
| 16ga. x 42             | 2.500               | x     | —   | —   |
| 16ga. x 48             | 2.500               | x     | —   | —   |
| 16ga. x 60             | 2.500               | x     | —   | —   |
| 14ga. x 36             | 3.125               | x     | —   | —   |
| 14ga. x 40             | 3.125               | x     | —   | —   |
| 14ga. x 42             | 3.125               | x     | —   | —   |
| 14ga. x 48             | 3.125               | x     | x   | —   |
| 14ga. x 50             | 3.125               | x     | —   | —   |
| 14ga. x 58             | 3.125               | x     | —   | —   |
| 14ga. x 60             | 3.125               | x     | x   | —   |
| 14ga. x 72             | 3.125               | x     | —   | —   |
| 13ga. x 48             | 3.750               | x     | x   | —   |
| 13ga. x 60             | 3.750               | —     | x   | —   |
| 12ga. x 36             | 4.375               | x     | —   | —   |
| 12ga. x 42             | 4.375               | x     | —   | —   |
| 12ga. x 48             | 4.375               | x     | x   | —   |
| 12ga. x 60             | 4.375               | x     | x   | —   |
| 12ga. x 72             | 4.375               | x     | —   | —   |
| 11ga. x 36             | 5.000               | x     | x   | —   |
| 11ga. x 48             | 5.000               | x     | x   | —   |
| 11ga. x 60             | 5.000               | x     | —   | —   |
| 10ga. x 36             | 5.625               | x     | —   | —   |
| 10ga. x 42             | 5.625               | x     | —   | —   |
| 10ga. x 48             | 5.625               | x     | x   | —   |
| 10ga. x 60             | 5.625               | x     | x   | —   |
| 10ga. x 72             | 5.625               | x     | —   | —   |
| 10ga. x 84             | 5.625               | x     | —   | —   |
| 8ga. x 36              | 6.875               | x     | —   | —   |
| 8ga. x 48              | 6.875               | x     | —   | —   |
| 8ga. x 52              | 6.875               | x     | —   | —   |

| Thickness<br>and Width  | Lbs. per<br>Sq. Ft. | Grade |     |     |
|-------------------------|---------------------|-------|-----|-----|
|                         |                     | 1010  | P&O | A36 |
| 7ga. x 36               | 7.500               | x     | —   | —   |
| 7ga. x 38               | 7.500               | x     | —   | —   |
| 7ga. x 42               | 7.500               | x     | —   | —   |
| 7ga. x 48               | 7.500               | x     | x   | —   |
| 7ga. x 54               | 7.500               | x     | —   | —   |
| 7ga. x 60               | 7.500               | x     | x   | —   |
| 7ga. x 72               | 7.500               | x     | —   | —   |
| 3/16 0.177 min x 60     | 7.660               | —     | —   | x   |
| 3/16 0.180 min x 48     | 7.660               | x     | x   | —   |
| 3/16 0.180 min x 54-1/2 | 7.660               | x     | —   | —   |
| 4 ga. 0.221 min x 48    | 9.375               | x     | —   | —   |
| 1/4" x 36               | 10.210              | x     | —   | —   |
| 1/4" x 37               | 10.210              | x     | —   | —   |
| 1/4" x 43               | 10.210              | x     | —   | —   |
| 1/4" x 46               | 10.210              | x     | —   | —   |
| 1/4" x 48               | 10.210              | x     | x   | x   |
| 1/4" x 50               | 10.210              | x     | —   | —   |
| 1/4" x 60               | 10.210              | x     | —   | x   |
| 1/4" x 72               | 10.210              | x     | —   | x   |
| 5/16" x 48              | 12.760              | x     | —   | —   |
| 5/16" x 60              | 12.760              | x     | —   | x   |
| 5/16" x 72              | 12.760              | —     | —   | x   |
| 3/8" x 36               | 15.320              | x     | —   | —   |
| 3/8" x 48               | 15.320              | x     | —   | x   |
| 3/8" x 60               | 15.320              | x     | —   | x   |
| 3/8" x 72               | 15.320              | x     | —   | x   |
| 1/2" x 36               | 20.420              | x     | —   | —   |
| 1/2" x 40               | 20.420              | —     | x   | —   |
| 1/2" x 48               | 20.420              | x     | —   | x   |
| 1/2" x 54               | 20.420              | —     | x   | —   |
| 1/2" x 60               | 20.420              | x     | —   | x   |
| 1/2" x 72               | 20.420              | —     | —   | x   |

**Cold Rolled Coils**

| Thickness and Width | Lbs. per Sq. Ft. |
|---------------------|------------------|
| 22ga. x 48          | 1.250            |
| 22ga. x 60          | 1.250            |
| 20ga. x 48          | 1.500            |
| 20ga. x 60          | 1.500            |
| 18ga. x 36          | 2.000            |
| 18ga. x 48          | 2.000            |
| 18ga. x 60          | 2.000            |
| 16ga. x 36          | 2.500            |
| 16ga. x 48          | 2.500            |
| 16ga. x 60          | 2.500            |
| 16ga. x 72          | 2.500            |
| 14ga. x 36          | 3.125            |
| 14ga. x 48          | 3.125            |
| 14ga. x 60          | 3.125            |
| 14ga. x 72          | 3.125            |
| 12ga. x 48          | 4.375            |
| 11ga. x 36          | 5.000            |
| 11ga. x 48          | 5.000            |

**Galvanized Coils**

| Thickness and Width | Lbs. per Sq. Ft. |
|---------------------|------------------|
| 30ga. x 36          | 0.656            |
| 28ga. x 36          | 0.781            |
| 26ga. x 36          | 0.906            |
| 26ga. x 48          | 0.906            |
| 26ga. x 60          | 0.906            |
| 24ga. x 36          | 1.156            |
| 24ga. x 48          | 1.156            |
| 24ga. x 60          | 1.156            |
| 22ga. x 36          | 1.406            |
| 22ga. x 48          | 1.406            |
| 22ga. x 60          | 1.406            |
| 20ga. x 36          | 1.656            |
| 20ga. x 48          | 1.656            |
| 20ga. x 60          | 1.656            |
| 18ga. x 36          | 2.156            |
| 18ga. x 48          | 2.156            |
| 18ga. x 60          | 2.156            |
| 16ga. x 36          | 2.656            |
| 16ga. x 48          | 2.656            |
| 16ga. x 60          | 2.656            |
| 14ga. x 36          | 3.281            |
| 14ga. x 48          | 3.281            |
| 14ga. x 60          | 3.281            |
| 12ga. x 36          | 4.531            |
| 12ga. x 48          | 4.531            |
| 12ga. x 60          | 4.531            |
| 11ga. x 48          | 5.156            |
| 10ga. x 36          | 5.781            |
| 10ga. x 48          | 5.781            |
| 10ga. x 60          | 5.781            |

**Galvannealed Coils**

| Thickness and Width | Lbs. Per Sq. Ft. | Coating |     |
|---------------------|------------------|---------|-----|
|                     |                  | A40     | A60 |
| 18ga. x 48          | 2.156            | —       | x   |
| 18ga. x 60          | 2.156            | —       | x   |
| 16ga. x 48          | 2.656            | x       | —   |
| 14ga. x 48          | 3.281            | x       | —   |
| 14ga. x 60          | 3.281            | x       | —   |
| 12ga. x 60          | 4.531            | x       | —   |
| 11ga. x 48          | 5.156            | x       | —   |
| 11ga. x 60          | 5.156            | x       | —   |

**Floor Plate Coils**

| Thickness | Width | Lbs. per Sq. Ft. |
|-----------|-------|------------------|
| 14ga.     | 48    | 3.75             |
| 14ga.     | 60    | 3.75             |
| 12ga.     | 48    | 5.25             |
| 12ga.     | 60    | 5.25             |
| 1/8"      | 48    | 6.16             |
| 1/8"      | 60    | 6.16             |
| 1/8"      | 72    | 6.16             |
| 3/16"     | 48    | 8.71             |
| 3/16"     | 60    | 8.71             |
| 3/16"     | 72    | 8.71             |
| 1/4"      | 48    | 11.26            |
| 1/4"      | 60    | 11.26            |
| 3/8"      | 48    | 16.37            |
| 3/8"      | 60    | 16.37            |

## High Strength Coils

| Thickness<br>and Width   | Lbs. per<br>Sq. Ft. | Grade   |         |         |         |            |         |
|--------------------------|---------------------|---------|---------|---------|---------|------------|---------|
|                          |                     | A607-45 | A607-50 | A607-60 | A715-50 | 715-50 P&O | A715-80 |
| 14ga. x 48               | 3.125               | –       | –       | –       | x       | –          | –       |
| 12ga. x 48               | 4.375               | –       | –       | –       | x       | –          | –       |
| 12ga. x 60               | 4.375               | –       | –       | –       | x       | –          | –       |
| 11ga. x 48               | 5.000               | –       | –       | –       | –       | x          | –       |
| 11ga. x 51               | 5.000               | –       | –       | –       | –       | –          | x       |
| 11ga. x 60               | 5.000               | –       | –       | –       | x       | –          | –       |
| 11ga. x 72               | 5.000               | –       | –       | –       | x       | –          | –       |
| 10ga. x 48               | 5.625               | –       | –       | –       | x       | –          | x       |
| 10ga. x 60               | 5.625               | –       | –       | –       | x       | x          | x       |
| 10ga. x 72               | 5.625               | –       | x       | –       | –       | –          | x       |
|                          |                     |         |         |         |         |            |         |
| 9ga. 0.142 min x 60      | 6.250               | –       | –       | –       | x       | x          | –       |
|                          |                     |         |         |         |         |            |         |
| 8ga. 0.154 min x 48      | 6.875               | x       | –       | –       | –       | –          | –       |
|                          |                     |         |         |         |         |            |         |
| 7ga. 0.1719 min x 48     | 7.500               | –       | –       | –       | x       | –          | –       |
| 7ga. 0.1719 min x 60     | 7.500               | –       | –       | –       | x       | –          | –       |
|                          |                     |         |         |         |         |            |         |
| 3/16" 0.177 min x 48-1/2 | 7.660               | –       | –       | –       | x       | –          | –       |
| 3/16" 0.177 min x 53     | 7.660               | –       | –       | x       | –       | –          | –       |
| 3/16" 0.177 min x 54     | 7.660               | –       | –       | –       | x       | –          | –       |
|                          |                     |         |         |         |         |            |         |
| 3/16" 0.180 min x 60     | 7.660               | –       | –       | –       | x       | x          | x       |
| 3/16" 0.180 min x 72     | 7.660               | –       | x       | –       | x       | –          | –       |
|                          |                     |         |         |         |         |            |         |
| 5ga. 0.209 min x 48      | 8.750               | –       | –       | –       | x       | –          | –       |
|                          |                     |         |         |         |         |            |         |
| 1/4" 0.240 min x 41      | 10.210              | –       | –       | x       | –       | –          | –       |
| 1/4" 0.240 min x 48      | 10.210              | –       | –       | –       | x       | –          | –       |
| 1/4" 0.240 min x 51      | 10.210              | –       | –       | x       | –       | –          | –       |
| 1/4" 0.240 min x 60      | 10.210              | –       | –       | –       | x       | x          | –       |
| 1/4" 0.240 min x 61      | 10.210              | –       | –       | –       | –       | –          | x       |
| 1/4" 0.240 min x 66      | 10.210              | –       | –       | x       | –       | –          | –       |
| 1/4" 0.240 min x 72      | 10.210              | –       | x       | –       | x       | –          | –       |
|                          |                     |         |         |         |         |            |         |
| 5/16" x 48               | 12.760              | –       | –       | –       | –       | –          | x       |
| 5/16" x 56-3/4           | 12.760              | –       | –       | –       | –       | –          | x       |
|                          |                     |         |         |         |         |            |         |

| Carbon Pipe Schedules |                   |                          |         |                   |                   |
|-----------------------|-------------------|--------------------------|---------|-------------------|-------------------|
| Pipe Size             | O.D.<br>in Inches | Wall Thickness in Inches |         | I.D.<br>in Inches | I.D.<br>in Inches |
|                       |                   | A.S.A. Pipe Schedules    |         |                   |                   |
|                       |                   | Sch. 40                  | Sch. 80 | Sch. 40           | Sch. 80           |
| 1/8"                  | 0.405             | 0.068                    | 0.095   | 0.269             | 0.215             |
| 1/4"                  | 0.540             | 0.088                    | 0.119   | 0.364             | 0.302             |
| 3/8"                  | 0.675             | 0.091                    | 0.126   | 0.584             | 0.423             |
| 1/2"                  | 0.840             | 0.109                    | 0.147   | 0.622             | 0.546             |
| 3/4"                  | 1.050             | 0.113                    | 0.154   | 0.824             | 0.742             |
| 1"                    | 1.315             | 0.133                    | 0.179   | 1.049             | 0.957             |
| 1-1/4"                | 1.660             | 0.140                    | 0.191   | 1.380             | 1.278             |
| 1-1/2"                | 1.900             | 0.145                    | 0.200   | 1.610             | 1.500             |
| 2"                    | 2.375             | 0.154                    | 0.218   | 2.067             | 1.939             |
| 2-1/2"                | 2.875             | 0.203                    | 0.276   | 2.469             | 2.323             |
| 3"                    | 3.500             | 0.216                    | 0.300   | 3.068             | 2.900             |
| 3-1/2"                | 4.000             | 0.226                    | 0.318   | 3.548             | 3.364             |
| 4"                    | 4.500             | 0.237                    | 0.337   | 4.026             | 3.826             |
| 5"                    | 5.563             | 0.258                    | 0.375   | 5.047             | 4.813             |
| 6"                    | 6.625             | 0.280                    | 0.432   | 6.065             | 5.761             |
| 8"                    | 8.625             | 0.322                    | 0.500   | 7.981             | 7.625             |
| 10"                   | 10.750            | 0.365                    | 0.593   | 10.020            | 9.564             |
| 12"                   | 12.750            | 0.406                    | 0.687   | 12.00             | 11.376            |

Continuous Butt Weld – Meets ASTM A53 type F. Available in Schedule 40 and Schedule 80 black or galvanized and includes sizes 4" and smaller. Commonly used for water, steam, gas and air lines. No minimum mechanical properties specified.

Electric Resistance Welded (ERW) – Meets ASTM A53 grade B. Includes our 5 and 6 Schedule 40 sizes.



# Pipe

## ASTM A-53



### SCH 40 BLK P.E. (Plain End)

| Size                | Length | WT / FT | WT / Length |
|---------------------|--------|---------|-------------|
| 1/8" blk. 40 p.e.   | 21'    | 0.240   | 5.04        |
| 1/4" blk. 40 p.e.   | 21'    | 0.420   | 8.82        |
| 3/8" blk. 40 p.e.   | 21'    | 0.568   | 11.93       |
| 1/2" blk. 40 p.e.   | 21'    | 0.850   | 17.85       |
| 3/4" blk. 40 p.e.   | 21'    | 1.130   | 23.73       |
| 1" blk. 40 p.e.     | 21'    | 1.680   | 35.28       |
| 1-1/4" blk. 40 p.e. | 21'    | 2.270   | 47.67       |
| 1-1/2" blk. 40 p.e. | 21'    | 2.720   | 57.12       |
| 2" blk. 40 p.e.     | 21'    | 3.650   | 76.65       |
| 2-1/2" blk. 40 p.e. | 21'    | 5.790   | 121.59      |
| 3" blk. 40 p.e.     | 21'    | 7.580   | 159.18      |
| 3-1/2" blk. 40 p.e. | 21'    | 9.110   | 191.31      |
| 4" blk. 40 p.e.     | 21'    | 10.790  | 226.59      |
| 5" blk. 40 p.e.     | 21'    | 14.620  | 307.02      |
| 6" blk. 40 p.e.     | 21'    | 18.970  | 398.37      |
| 8" blk. 40 p.e.     | 21'    | 28.550  | 599.55      |



### SCH 80 BLK P.E. (Plain End)

| Size                | Length | WT / FT | WT / Length |
|---------------------|--------|---------|-------------|
| 1/4" blk. 80 p.e.   | 21'    | 0.540   | 11.34       |
| 3/8" blk. 80 p.e.   | 21'    | 0.739   | 15.52       |
| 1/2" blk. 80 p.e.   | 21'    | 1.090   | 22.89       |
| 3/4" blk. 80 p.e.   | 21'    | 1.470   | 30.87       |
| 1" blk. 80 p.e.     | 21'    | 2.170   | 45.57       |
| 1-1/4" blk. 80 p.e. | 21'    | 3.000   | 63.00       |
| 1-1/2" blk. 80 p.e. | 21'    | 3.630   | 76.23       |
| 2" blk. 80 p.e.     | 21'    | 5.020   | 105.42      |
| 2-1/2" blk. 80 p.e. | 21'    | 7.660   | 160.86      |
| 3" blk. 80 p.e.     | 21'    | 10.250  | 215.25      |
| 3-1/2" blk. 80 p.e. | 21'    | 12.510  | 262.71      |
| 4" blk. 80 p.e.     | 21'    | 14.980  | 314.58      |



### SCH 40 BLK T&C (Threaded & Coupled)

| Size               | Length | WT / FT | WT / Length |
|--------------------|--------|---------|-------------|
| 1/2" blk. 40 T&C   | 21'    | 0.850   | 17.85       |
| 3/4" blk. 40 T&C   | 21'    | 1.130   | 23.73       |
| 1" blk. 40 T&C     | 21'    | 1.680   | 35.28       |
| 1-1/4" blk. 40 T&C | 21'    | 2.270   | 47.67       |
| 1-1/2" blk. 40 T&C | 21'    | 2.720   | 57.12       |
| 2" blk. 40 T&C     | 21'    | 3.650   | 76.65       |
| 2-1/2" blk. 40 T&C | 21'    | 5.790   | 121.59      |
| 3" blk. 40 T&C     | 21'    | 7.580   | 159.18      |



### SCH 40 GALV T&C (Threaded & Coupled)

| Size                | Length | WT / FT | WT / Length |
|---------------------|--------|---------|-------------|
| 1/4" galv. 40 T&C   | 21'    | 0.420   | 8.82        |
| 3/8" galv. 40 T&C   | 21'    | 0.568   | 11.93       |
| 1/2" galv. 40 T&C   | 21'    | 0.850   | 17.85       |
| 3/4" galv. 40 T&C   | 21'    | 1.130   | 23.73       |
| 1" galv. 40 T&C     | 21'    | 1.680   | 35.28       |
| 1-1/4" galv. 40 T&C | 21'    | 2.270   | 47.67       |
| 1-1/2" galv. 40 T&C | 21'    | 2.720   | 57.12       |
| 2" galv. 40 T&C     | 21'    | 3.650   | 76.65       |
| 3" galv. 40 T&C     | 21'    | 7.580   | 159.18      |



### SCH 40 GALV. P.E. (Plain End)

| Size                 | Length | WT / FT | WT / Length |
|----------------------|--------|---------|-------------|
| 1/2" galv. 40 p.e.   | 21'    | 0.850   | 17.85       |
| 1-1/4" galv. 40 p.e. | 21'    | 2.270   | 47.67       |
| 4" galv. 40 p.e.     | 21'    | 10.890  | 228.69      |



# Square Tubing

Mechanical ASTM A513 / Structural ASTM A500 Grade B

| Size                   | Length | WT / FT | WT / Length |
|------------------------|--------|---------|-------------|
| 1/2 x 1/2 x .035       | 20'    | 0.221   | 4.42        |
| 1/2 x 1/2 x 16 ga.     | 20'    | 0.385   | 7.70        |
| 1/2 x 1/2 x 16 ga.     | 24'    | 0.385   | 9.24        |
| 5/8 x 5/8 x 16 ga.     | 20'    | 0.495   | 9.90        |
| 3/4 x 3/4 x 16 ga.     | 20'    | 0.606   | 12.12       |
| 3/4 x 3/4 x 16 ga.     | 24'    | 0.606   | 14.54       |
| 3/4 x 3/4 x 14 ga.     | 24'    | 0.753   | 18.07       |
| 3/4 x 3/4 x 11 ga.     | 24'    | 1.028   | 24.67       |
| 1 x 1 x 16 ga.         | 20'    | 0.827   | 16.54       |
| 1 x 1 x 16 ga.         | 24'    | 0.827   | 19.85       |
| 1 x 1 x 15 ga.         | 20'    | 0.909   | 18.18       |
| 1 x 1 x 15 ga.         | 24'    | 0.909   | 21.82       |
| 1 x 1 x 14 ga.         | 20'    | 1.035   | 20.70       |
| 1 x 1 x 14 ga.         | 24'    | 1.035   | 24.84       |
| 1 x 1 x 13 ga.         | 20'    | 1.169   | 23.38       |
| 1 x 1 x 12 ga.         | 24'    | 1.321   | 31.70       |
| 1 x 1 x 11 ga.         | 20'    | 1.436   | 28.72       |
| 1 x 1 x 11 ga.         | 24'    | 1.436   | 34.46       |
| 1-1/4 x 1-1/4 x 16 ga. | 24'    | 1.048   | 25.15       |
| 1-1/4 x 1-1/4 x 14 ga. | 20'    | 1.317   | 26.34       |
| 1-1/4 x 1-1/4 x 14 ga. | 24'    | 1.317   | 31.61       |
| 1-1/4 x 1-1/4 x 12 ga. | 24'    | 1.691   | 40.58       |
| 1-1/4 x 1-1/4 x 11 ga. | 24'    | 1.844   | 44.26       |
| 1-1/4 x 1-1/4 x 3/16   | 20'    | 2.400   | 48.00       |
| 1-1/2 x 1-1/2 x 18 ga. | 20'    | 0.967   | 19.34       |
| 1-1/2 x 1-1/2 x 16 ga. | 24'    | 1.269   | 30.46       |
| 1-1/2 x 1-1/2 x 14 ga. | 20'    | 1.600   | 32.00       |
| 1-1/2 x 1-1/2 x 14 ga. | 24'    | 1.600   | 38.40       |
| 1-1/2 x 1-1/2 x 13 ga. | 20'    | 1.815   | 36.30       |
| 1-1/2 x 1-1/2 x 13 ga. | 24'    | 1.815   | 43.56       |
| 1-1/2 x 1-1/2 x 12 ga. | 24'    | 2.062   | 49.49       |
| 1-1/2 x 1-1/2 x 11 ga. | 20'    | 2.252   | 45.04       |
| 1-1/2 x 1-1/2 x 11 ga. | 24'    | 2.252   | 54.05       |
| 1-1/2 x 1-1/2 x 3/16   | 20'    | 3.040   | 60.80       |
| 1-1/2 x 1-1/2 x 3/16   | 24'    | 3.040   | 72.96       |
| 1-1/2 x 1-1/2 x 1/4    | 20'    | 4.067   | 81.34       |
| 1-1/2 x 1-1/2 x 1/4    | 24'    | 4.067   | 97.61       |

| Size                   | Length | WT / FT | WT / Length |
|------------------------|--------|---------|-------------|
| 1-3/4 x 1-3/4 x 14 ga. | 24'    | 1.882   | 45.17       |
| 1-3/4 x 1-3/4 x 11 ga. | 24'    | 2.660   | 63.84       |
| 2 x 2 x 14 ga.         | 20'    | 2.164   | 43.28       |
| 2 x 2 x 14 ga.         | 24'    | 2.164   | 51.94       |
| 2 x 2 x 12 ga.         | 24'    | 2.800   | 67.20       |
| 2 x 2 x 11 ga.         | 20'    | 3.050   | 61.00       |
| 2 x 2 x 11 ga.         | 24'    | 3.050   | 73.20       |
| 2 x 2 x 3/16           | 24'    | 4.320   | 103.68      |
| 2 x 2 x 1/4            | 24'    | 5.410   | 129.84      |
| 2-1/2 x 2-1/2 x 11 ga. | 24'    | 3.900   | 93.60       |
| 2-1/2 x 2-1/2 x 3/16   | 24'    | 5.590   | 134.16      |
| 2-1/2 x 2-1/2 x 1/4    | 24'    | 7.110   | 170.64      |
| 3 x 3 x 14 ga.         | 24'    | 3.240   | 77.76       |
| 3 x 3 x 11 ga.         | 20'    | 4.750   | 95.00       |
| 3 x 3 x 11 ga.         | 24'    | 4.750   | 114.00      |
| 3 x 3 x 11 ga.         | 40'    | 4.750   | 190.00      |
| 3 x 3 x 3/16           | 20'    | 6.870   | 137.40      |
| 3 x 3 x 3/16           | 24'    | 6.870   | 164.88      |
| 3 x 3 x 3/16           | 40'    | 6.870   | 274.80      |
| 3 x 3 x 1/4            | 20'    | 8.810   | 176.20      |
| 3 x 3 x 1/4            | 24'    | 8.810   | 211.44      |
| 3 x 3 x 1/4            | 40'    | 8.810   | 352.40      |
| 3-1/2 x 3-1/2 x 3/16   | 20'    | 8.150   | 163.00      |
| 3-1/2 x 3-1/2 x 3/16   | 24'    | 8.150   | 195.60      |
| 3-1/2 x 3-1/2 x 1/4    | 24'    | 10.510  | 252.24      |
| 4 x 4 x 11 ga.         | 20'    | 6.460   | 129.20      |
| 4 x 4 x 11 ga.         | 24'    | 6.460   | 155.04      |
| 4 x 4 x 11 ga.         | 36'4"  | 6.460   | 234.71      |
| 4 x 4 x 11 ga.         | 40'    | 6.460   | 258.40      |
| 4 x 4 x 3/16           | 20'    | 9.420   | 188.40      |
| 4 x 4 x 3/16           | 30'    | 9.420   | 282.60      |
| 4 x 4 x 3/16           | 40'    | 9.420   | 376.80      |

# Square & Rectangle Tube

Mechanical ASTM A513 / Structural ASTM A500 Grade B



## Square Tube

| Size         | Length | WT / FT | WT / Length |
|--------------|--------|---------|-------------|
| 4 x 4 x 1/4  | 24'    | 12.210  | 293.04      |
| 4 x 4 x 3/8  | 20'    | 17.270  | 345.40      |
| 4 x 4 x 3/8  | 24'    | 17.270  | 414.48      |
| 4 x 4 x 3/8  | 40'    | 17.270  | 690.80      |
| 4 x 4 x 1/2  | 24'    | 21.630  | 519.12      |
|              |        |         |             |
| 5 x 5 X 3/16 | 20'    | 11.970  | 239.40      |
| 5 x 5 X 3/16 | 24'    | 11.970  | 287.28      |
| 5 x 5 X 3/16 | 40'    | 11.970  | 478.80      |
| 5 x 5 x 1/4  | 20'    | 15.620  | 312.40      |
| 5 x 5 x 1/4  | 24'    | 15.620  | 374.88      |
| 5 x 5 x 1/4  | 40'    | 15.620  | 624.80      |
| 5 x 5 x 3/8  | 20'    | 22.370  | 447.40      |
| 5 x 5 x 3/8  | 40'    | 22.370  | 894.80      |
|              |        |         |             |
| 6 x 6 x 1/4  | 20'    | 19.020  | 380.40      |
| 6 x 6 x 1/4  | 24'    | 19.020  | 456.48      |
| 6 x 6 x 1/4  | 40'    | 19.020  | 760.80      |
| 6 x 6 x 3/8  | 20'    | 27.480  | 549.60      |
| 6 x 6 x 3/8  | 24'    | 27.480  | 659.52      |
| 6 x 6 x 3/8  | 40'    | 27.480  | 1099.20     |
| 6 x 6 x 1/2  | 20'    | 35.240  | 704.80      |
| 6 x 6 x 1/2  | 40'    | 35.240  | 1409.60     |
|              |        |         |             |
| 7 x 7 x 1/4  | 20'    | 22.420  | 448.40      |
| 7 x 7 x 1/4  | 24'    | 22.420  | 538.08      |
| 7 x 7 x 1/4  | 40'    | 22.420  | 896.80      |
| 7 x 7 x 3/8  | 20'    | 32.580  | 651.60      |
| 7 x 7 x 3/8  | 24'    | 32.580  | 781.92      |
| 7 x 7 x 3/8  | 40'    | 32.580  | 1303.20     |
|              |        |         |             |
| 8 x 8 x 3/16 | 20'    | 19.630  | 392.60      |
| 8 x 8 x 3/16 | 40'    | 19.630  | 785.20      |
| 8 x 8 x 1/4  | 40'    | 25.820  | 1032.80     |
| 8 x 8 x 3/8  | 40'    | 37.690  | 1507.60     |



## Rectangle Tube

| Size                   | Length | WT / FT | WT / Length |
|------------------------|--------|---------|-------------|
| 3/4 x 1-1/2 x 14 ga.   | 20'    | 1.176   | 23.52       |
|                        |        |         |             |
| 1 x 1-1/2 x 14 ga.     | 24'    | 1.317   | 31.61       |
| 1 x 1-1/2 x 11 ga.     | 24'    | 1.844   | 44.26       |
|                        |        |         |             |
| 1 x 2 x 14 ga.         | 24'    | 1.600   | 38.40       |
| 1 x 2 x 11 ga.         | 20'    | 2.252   | 45.04       |
| 1 x 2 x 11 ga.         | 24'    | 2.252   | 54.05       |
|                        |        |         |             |
| 1 x 3 x 14 ga.         | 24'    | 2.164   | 51.94       |
| 1 x 3 x 11 ga.         | 24'    | 3.050   | 73.20       |
|                        |        |         |             |
| 1-1/4 x 1-3/4 x 11 ga. | 20'    | 2.252   | 45.04       |
| 1-1/4 x 1-3/4 x 11 ga. | 24'    | 2.252   | 54.05       |
| 1-1/4 x 2 x 14 ga.     | 24'    | 1.741   | 41.78       |
|                        |        |         |             |
| 1-1/2 x 2 x 14 ga.     | 24'    | 1.882   | 45.17       |
| 1-1/2 x 2 x 11 ga.     | 20'    | 2.660   | 53.20       |
| 1-1/2 x 2 x 11 ga.     | 24'    | 2.660   | 63.84       |
|                        |        |         |             |
| 1-1/2 x 2-1/2 x 14 ga. | 24'    | 2.164   | 51.94       |
| 1-1/2 x 2-1/2 x 14 ga. | 40'    | 2.164   | 86.56       |
| 1-1/2 x 2-1/2 x 11 ga. | 20'    | 3.050   | 61.00       |
| 1-1/2 x 2-1/2 x 11 ga. | 24'    | 3.050   | 73.20       |
| 1-1/2 x 2-1/2 x 3/16   | 24'    | 4.320   | 103.68      |
| 1-1/2 x 2-1/2 x 1/4    | 20'    | 5.410   | 108.20      |
|                        |        |         |             |
| 1-1/2 x 3 x 14 ga.     | 24'    | 2.446   | 58.70       |
| 1-1/2 x 3 x 11 ga.     | 24'    | 3.480   | 83.52       |
| 1-1/2 x 3 x 3/16       | 20'    | 4.960   | 99.20       |
| 1-1/2 x 3 x 3/16       | 24'    | 4.960   | 119.04      |
|                        |        |         |             |
| 2 x 3 x 14 ga.         | 24'    | 2.670   | 64.08       |
| 2 x 3 x 11 ga.         | 20'    | 3.900   | 78.00       |
| 2 x 3 x 11 ga.         | 24'    | 3.900   | 93.60       |
|                        |        |         |             |
| 2 x 3 x 3/16           | 24'    | 5.590   | 134.16      |
| 2 x 3 x 1/4            | 24'    | 7.110   | 170.64      |

Square and Rectangle Tubing ASTM A500 - Grade B –  
Cold formed, electric resistance weld, flash in. Easily  
welded, formed, drilled, punched, and cut. Estimated  
Minimum Mechanical Properties (EMMP) –  
Yield – 46,000 psi. Tensile – 58,000 psi.



# Rectangle Tube

Structural ASTM A500 Grade B

| Size                 | Length | WT / FT | WT / Length |
|----------------------|--------|---------|-------------|
| 2 x 4 x 14 ga.       | 24'    | 3.263   | 65.26       |
| 2 x 4 x 11 ga.       | 20'    | 4.750   | 95.00       |
| 2 x 4 x 11 ga.       | 24'    | 4.750   | 114.00      |
| 2 x 4 x 11 ga.       | 40'    | 4.750   | 190.00      |
| 2 x 4 x 3/16         | 20'    | 6.870   | 137.40      |
| 2 x 4 x 3/16         | 24'    | 6.870   | 164.88      |
| 2 x 4 x 1/4          | 24'    | 8.810   | 211.44      |
|                      |        |         |             |
| 2 x 5 x 11 ga.       | 24'    | 5.610   | 134.64      |
| 2 x 5 x 3/16         | 24'    | 8.150   | 195.60      |
| 2 x 5 x 3/16         | 40'    | 8.150   | 326.00      |
| 2 x 5 x 1/4          | 20'    | 10.510  | 210.20      |
| 2 x 5 x 1/4          | 24'    | 10.510  | 252.24      |
| 2 x 5 x 1/4          | 40'    | 10.510  | 420.40      |
|                      |        |         |             |
| 2 x 6 x 11 ga.       | 20'    | 6.460   | 129.20      |
| 2 x 6 x 11 ga.       | 24'    | 6.460   | 155.04      |
| 2 x 6 x 3/16         | 20'    | 9.420   | 188.40      |
| 2 x 6 x 3/16         | 24'    | 9.420   | 226.08      |
| 2 x 6 x 3/16         | 40'    | 9.420   | 376.80      |
| 2 x 6 x 1/4          | 24'    | 12.210  | 293.04      |
| 2 x 6 x 1/4          | 40'    | 12.210  | 488.40      |
|                      |        |         |             |
| 2 x 8 x 3/16         | 24'    | 11.970  | 287.28      |
| 2 x 8 x 1/4          | 40'    | 15.620  | 624.80      |
| 2 x 10 x 1/4         | 40'    | 19.020  | 760.80      |
|                      |        |         |             |
| 2-1/2 x 3-1/2 x 3/16 | 20'    | 6.870   | 137.40      |
| 2-1/2 x 3-1/2 x 3/16 | 24'    | 6.870   | 164.88      |
| 2-1/2 x 3-1/2 x 3/16 | 40'    | 6.870   | 274.80      |
|                      |        |         |             |
| 3 x 4 x 11 ga.       | 24'    | 5.610   | 134.64      |
| 3 x 4 x 11 ga.       | 40'    | 5.610   | 224.40      |
| 3 x 4 x 3/16         | 24'    | 8.150   | 195.60      |
| 3 x 4 x 1/4          | 20'    | 10.510  | 210.20      |
| 3 x 4 x 1/4          | 24'    | 10.510  | 252.24      |
| 3 x 4 x 1/4          | 40'    | 10.510  | 420.40      |
|                      |        |         |             |
| 3 x 5 x 11 ga.       | 24'    | 6.460   | 155.04      |
| 3 x 5 x 3/16         | 20'    | 9.420   | 188.40      |
| 3 x 5 x 3/16         | 24'    | 9.420   | 226.08      |
| 3 x 5 x 3/16         | 40'    | 9.420   | 376.80      |

| Size           | Length | WT / FT | WT / Length |
|----------------|--------|---------|-------------|
| 3 x 5 x 1/4    | 20'    | 12.210  | 244.20      |
| 3 x 5 x 1/4    | 24'    | 12.210  | 293.04      |
| 3 x 5 x 1/4    | 40'    | 12.210  | 488.40      |
| 3 x 5 x 3/8    | 24'    | 17.270  | 414.48      |
|                |        |         |             |
| 3 x 6 x 11 ga. | 20'    | 7.200   | 144.00      |
| 3 x 6 x 11 ga. | 24'    | 7.200   | 172.80      |
| 3 x 6 x 3/16   | 24'    | 10.700  | 256.80      |
| 3 x 6 x 1/4    | 20'    | 13.910  | 278.20      |
| 3 x 6 x 1/4    | 24'    | 13.910  | 333.84      |
| 3 x 6 x 1/4    | 40'    | 13.910  | 556.40      |
| 3 x 7 x 1/4    | 40'    | 15.620  | 624.80      |
| 3 x 8 x 3/16   | 40'    | 13.250  | 530.00      |
| 3 x 8 x 1/4    | 24'    | 17.320  | 415.68      |
|                |        |         |             |
| 4 x 6 x 3/16   | 20'    | 11.970  | 239.40      |
| 4 x 6 x 3/16   | 24'    | 11.970  | 287.28      |
| 4 x 6 x 3/16   | 40'    | 11.970  | 478.80      |
| 4 x 6 x 1/4    | 20'    | 15.620  | 312.40      |
| 4 x 6 x 1/4    | 24'    | 15.620  | 374.88      |
| 4 x 6 x 1/4    | 40'    | 15.620  | 624.80      |
| 4 x 6 x 3/8    | 20'    | 22.370  | 447.40      |
| 4 x 6 x 3/8    | 40'    | 22.370  | 894.80      |
|                |        |         |             |
| 4 x 8 x 1/4    | 20'    | 19.020  | 380.40      |
| 4 x 8 x 1/4    | 24'    | 19.020  | 456.48      |
| 4 x 8 x 1/4    | 40'    | 19.020  | 760.80      |
| 4 x 8 x 3/8    | 24'    | 27.480  | 659.52      |
| 4 x 8 x 3/8    | 40'    | 27.480  | 1099.20     |
| 4 x 10 x 3/16  | 20'    | 17.080  | 341.60      |
| 4 x 10 x 3/16  | 40'    | 17.080  | 683.20      |
|                |        |         |             |
| 5 x 7 x 1/4    | 20'    | 19.020  | 380.40      |
| 5 x 7 x 1/4    | 24'    | 19.020  | 456.48      |
| 5 x 7 x 1/4    | 40'    | 19.020  | 760.80      |
| 5 x 7 x 3/8    | 20'    | 27.480  | 549.60      |
| 5 x 7 x 3/8    | 40'    | 27.480  | 1099.20     |
|                |        |         |             |
| 6 x 8 x 3/16   | 40'    | 17.080  | 683.20      |
| 6 x 10 x 1/4   | 40'    | 25.820  | 1032.80     |

## Pipe Size Tube



### Pipe Size Tube

Electric Resistant Weld

| Size   | O.D.   | Gauge   | Length | WT / FT | WT / Bar |
|--------|--------|---------|--------|---------|----------|
| 1/2"   | 0.840  | 14 ga.  | 21'    | 0.671   | 14.09    |
| 1/2"   | 0.840  | 12 ga.  | 21'    | 0.851   | 17.87    |
| 3/4"   | 1.050  | 14 ga.  | 21'    | 0.857   | 18.00    |
| 3/4"   | 1.050  | 12 ga.  | 21'    | 1.096   | 23.02    |
| 1"     | 1.315  | 14 ga.  | 21'    | 1.092   | 22.93    |
| 1"     | 1.315  | 12 ga.  | 21'    | 1.404   | 29.48    |
| 1"     | 1.315  | Sch. 40 | 21'    | 1.680   | 35.28    |
| 1-1/4" | 1.660  | 14 ga.  | 21'    | 1.398   | 29.36    |
| 1-1/4" | 1.660  | 12 ga.  | 21'    | 1.806   | 37.93    |
| 1-1/4" | 1.660  | Sch. 40 | 21'    | 2.270   | 47.67    |
| 1-1/2" | 1.900  | 14 ga.  | 21'    | 1.611   | 33.83    |
| 1-1/2" | 1.900  | 12 ga.  | 21'    | 2.085   | 43.78    |
| 1-1/2" | 1.900  | 11 ga.  | 21'    | 2.281   | 47.90    |
| 1-1/2" | 1.900  | Sch. 40 | 21'    | 2.720   | 57.12    |
| 2"     | 2.375  | 14 ga.  | 21'    | 2.032   | 42.67    |
| 2"     | 2.375  | 12 ga.  | 21'    | 2.638   | 55.40    |
| 2"     | 2.375  | 11 ga.  | 21'    | 2.890   | 60.69    |
| 2"     | 2.375  | Sch. 40 | 21'    | 3.650   | 76.65    |
| 2-1/2" | 2.875  | Sch. 40 | 21'    | 5.790   | 121.59   |
| 3"     | 3.500  | Sch. 40 | 21'    | 7.580   | 159.18   |
| 3-1/2" | 4.000  | Sch. 40 | 21'    | 9.110   | 191.31   |
| 4"     | 4.500  | Sch. 40 | 21'    | 10.790  | 226.59   |
| 5"     | 5.563  | Sch. 40 | 21'    | 14.620  | 307.02   |
| 6"     | 6.625  | Sch. 40 | 21'    | 18.970  | 398.37   |
| 8"     | 8.625  | Sch. 40 | 21'    | 28.550  | 599.55   |
| 10"    | 10.750 | Sch. 40 | 21'    | 40.480  | 850.08   |
| 12"    | 12.750 | Sch. 40 | 21'    | 49.560  | 1040.76  |



### Pipe Size Tube

Electric Resistant Weld SCH. 80

| Size | O.D.  | Gauge   | Length | WT / FT | WT / Bar |
|------|-------|---------|--------|---------|----------|
| 6"   | 6.625 | Sch. 80 | 21"    | 28.580  | 600.18   |



### Round Mechanical Tube

Hot Rolled – Electric Welded – ASTM A513

| Size/O.D. | Gauge  | Length | WT / FT | WT / Bar |
|-----------|--------|--------|---------|----------|
| 3/8"      | 0.035  | 20'    | 0.127   | 2.54     |
| 5/8"      | 16 ga. | 20'2"  | 0.389   | 7.84     |
| 3/4"      | 16 ga. | 20'    | 0.476   | 9.52     |
| 3/4"      | 14 ga. | 20'    | 0.591   | 11.82    |
| 3/4"      | 11 ga. | 20'    | 0.807   | 16.14    |
| 7/8"      | 14 ga. | 20'    | 0.702   | 14.04    |
| 1"        | 16 ga. | 20'    | 0.649   | 12.98    |
| 1"        | 14 ga. | 20'    | 0.813   | 16.26    |
| 1"        | 11 ga. | 20'    | 1.128   | 22.56    |
| 1"        | 5/8 ID | 20'    | 1.630   | 32.60    |
| 1-1/8"    | 16 ga. | 20'2"  | 0.736   | 14.84    |
| 1-1/4"    | 14 ga. | 20'    | 1.035   | 20.70    |
| 1-1/4"    | 11 ga. | 20'    | 1.448   | 28.96    |
| 1-1/2"    | 16 ga. | 20'    | 0.996   | 19.92    |
| 1-1/2"    | 14 ga. | 20'    | 1.257   | 25.14    |
| 1-1/2"    | 12 ga. | 20'    | 1.619   | 32.38    |
| 1-5/8"    | 11 ga. | 20'    | 1.929   | 38.58    |
| 2"        | 11 ga. | 20'    | 2.410   | 48.20    |

Electric Resistance Welded – Is produced from low carbon steel and is the lowest cost mechanical tubing. Includes square, rectangular, and round shapes.

Possesses a good surface finish and has good cold working characteristics. Produced to meet ASTM A513. A flash in product.

# Round Tube



## Round Tube

Hot Rolled – ASTM A513 – Flash in

| Size   | Gauge  | Length | WT / FT | WT / Length |
|--------|--------|--------|---------|-------------|
| 4"     | 16 ga. | 20'    | 2.732   | 54.64       |
| 4"     | 14 ga. | 20'    | 3.472   | 69.44       |
| 4"     | 12 ga. | 20'    | 4.530   | 90.60       |
| 5"     | 14 ga. | 20'    | 4.359   | 87.18       |
| 5"     | 12 ga. | 20'    | 5.694   | 113.88      |
| 5"     | 7 ga.  | 20'    | 9.266   | 185.32      |
| 6"     | 16 ga. | 20'    | 4.120   | 82.40       |
| 6"     | 14 ga. | 20'    | 5.245   | 104.90      |
| 6"     | 12 ga. | 20'    | 6.858   | 137.16      |
| 6"     | 10 ga. | 20'    | 8.395   | 167.90      |
| 6-5/8" | 10 ga. | 20'    | 9.289   | 185.78      |
| 6-5/8" | 7 ga.  | 20'    | 12.390  | 247.80      |
| 7"     | 14 ga. | 20'    | 5.547   | 110.94      |
| 7"     | 12 ga. | 20'    | 8.022   | 160.44      |
| 8"     | 14 ga. | 20'    | 7.018   | 140.36      |
| 8"     | 12 ga. | 20'    | 9.186   | 183.72      |
| 8"     | 10 ga. | 20'    | 11.257  | 225.14      |
| 10"    | 14 ga. | 20'    | 7.950   | 159.00      |
| 10"    | 12 ga. | 20'    | 11.514  | 230.28      |
| 10"    | 10 ga. | 20'    | 14.119  | 282.38      |
| 12"    | 12 ga. | 20'    | 13.843  | 276.86      |
| 12"    | 10 ga. | 20'    | 16.982  | 339.64      |
| 14"    | 10 ga. | 20'    | 19.844  | 396.88      |

## Round Mechanical Tube

| O.D.  | G.A. | Wall Dec. | I.D.  | WT / FT | O.D.   | G.A. | Wall Dec. | I.D.  | WT / FT |
|-------|------|-----------|-------|---------|--------|------|-----------|-------|---------|
| 1/8"  | 24   | 0.022     | 0.081 | 0.0242  | 5/16"  | 24   | 0.022     | 0.268 | 0.0684  |
| 1/8"  | 22   | 0.028     | 0.069 | 0.0290  | 5/16"  | 23   | 0.025     | 0.263 | 0.0769  |
| 1/8"  | 20   | 0.035     | 0.055 | 0.0336  | 5/16"  | 22   | 0.028     | 0.256 | 0.0852  |
| 1/8"  | 18   | 0.049     | 0.027 | 0.0398  | 5/16"  | 21   | 0.032     | 0.249 | 0.0960  |
|       |      |           |       |         | 5/16"  | 20   | 0.035     | 0.242 | 0.1039  |
| 5/32" | 22   | 0.028     | 0.100 | 0.0384  | 5/16"  | 19   | 0.042     | 0.228 | 0.1216  |
| 5/32" | 21   | 0.032     | 0.092 | 0.0425  | 5/16"  | 18   | 0.049     | 0.214 | 0.1382  |
|       |      |           |       |         | 5/16"  | 17   | 0.058     | 0.196 | 0.1580  |
| 3/16" | 26   | 0.018     | 0.152 | 0.0327  | 5/16"  | 16   | 0.065     | 0.182 | 0.1722  |
| 3/16" | 24   | 0.022     | 0.143 | 0.0390  | 5/16"  | 14   | 0.083     | 0.146 | 0.2039  |
| 3/16" | 22   | 0.028     | 0.131 | 0.0478  | 5/16"  | 13   | 0.095     | 0.122 | 0.2212  |
| 3/16" | 21   | 0.032     | 0.123 | 0.0533  | 5/16"  | 12   | 0.109     | 0.094 | 0.2375  |
| 3/16" | 20   | 0.035     | 0.117 | 0.0572  | 5/16"  | 11   | 0.120     | 0.072 | 0.2473  |
| 3/16" | 19   | 0.042     | 0.103 | 0.0655  |        |      |           |       |         |
| 3/16" | 18   | 0.049     | 0.089 | 0.0727  | 11/32" | 21   | 0.032     | 0.280 | 0.1066  |
| 3/16" | 17   | 0.058     | 0.072 | 0.0805  |        |      |           |       |         |
| 3/16" | 16   | 0.065     | 0.057 | 0.0854  | 3/8"   | 24   | 0.022     | 0.331 | 0.0829  |
|       |      |           |       |         | 3/8"   | 23   | 0.025     | 0.325 | 0.0935  |
| 7/32" | 24   | 0.022     | 0.175 | 0.0463  | 3/8"   | 22   | 0.028     | 0.319 | 0.1038  |
| 7/32" | 22   | 0.028     | 0.166 | 0.0571  | 3/8"   | 21   | 0.032     | 0.311 | 0.1172  |
| 7/32" | 20   | 0.035     | 0.148 | 0.0687  | 3/8"   | 20   | 0.035     | 0.305 | 0.1271  |
| 7/32" | 18   | 0.049     | 0.120 | 0.0888  | 3/8"   | 19   | 0.042     | 0.291 | 0.1494  |
| 7/32" | 16   | 0.065     | 0.088 | 0.1069  | 3/8"   | 18   | 0.049     | 0.277 | 0.1706  |
|       |      |           |       |         | 3/8"   | 17   | 0.058     | 0.259 | 0.1964  |
| 1/4"  | 24   | 0.022     | 0.206 | 0.0536  | 3/8"   | 16   | 0.065     | 0.245 | 0.2152  |
| 1/4"  | 23   | 0.025     | 0.200 | 0.0601  | 3/8"   | 15   | 0.072     | 0.231 | 0.2330  |
| 1/4"  | 22   | 0.028     | 0.194 | 0.0664  | 3/8"   | 14   | 0.083     | 0.209 | 0.2588  |
| 1/4"  | 21   | 0.032     | 0.187 | 0.0745  | 3/8"   | 13   | 0.095     | 0.185 | 0.2841  |
| 1/4"  | 20   | 0.035     | 0.180 | 0.0804  | 3/8"   | 12   | 0.109     | 0.157 | 0.3097  |
| 1/4"  | 19   | 0.042     | 0.166 | 0.0933  | 3/8"   | 1/8  | 0.125     | 0.125 | 0.3338  |
| 1/4"  | 18   | 0.049     | 0.152 | 0.1052  | 3/8"   | 10   | 0.134     | 0.107 | 0.3449  |
| 1/4"  | 17   | 0.058     | 0.134 | 0.1189  |        |      |           |       |         |
| 1/4"  | 16   | 0.065     | 0.120 | 0.1284  | 13/32" | 16   | 0.065     | 0.276 | 0.2367  |
| 1/4"  | 14   | 0.083     | 0.084 | 0.1480  | 13/32" | 14   | 0.083     | 0.240 | 0.2863  |
| 1/4"  | 13   | 0.095     | 0.060 | 0.1573  | 13/32" | 13   | 0.095     | 0.216 | 0.3155  |
|       |      |           |       |         |        |      |           |       |         |
| 9/32" | 18   | 0.049     | 0.183 | 0.1217  |        |      |           |       |         |

Cold Drawn Seamless – Is normally produced to O.D. and I.D. dimensions. Typical applications include rollers, shafts, hydraulic cylinders. Produced to ASTM A519.

Drawn Over Mandrel – An electric welded tube carefully tested for weld soundness and redrawn over mandrel. All welding flash is removed. This tube is superior in finish and wall uniformity to seamless tube. Especially suitable for hydraulic cylinders, where superior finish and accuracy are desirable. Less costly than cold drawn seamless tubing. Normally drawn to O.D. and I.D. dimensions. Produced to ASTM – A513 Type 5.

## Round Mechanical Tube

| O.D.  | G.A. | Wall Dec. | I.D.  | WT / FT |
|-------|------|-----------|-------|---------|
| 7/16" | 24   | 0.022     | 0.393 | 0.0977  |
| 7/16" | 23   | 0.025     | 0.388 | 0.1103  |
| 7/16" | 22   | 0.028     | 0.381 | 0.1226  |
| 7/16" | 21   | 0.032     | 0.373 | 0.1388  |
| 7/16" | 20   | 0.035     | 0.367 | 0.1506  |
| 7/16" | 18   | 0.049     | 0.339 | 0.2036  |
| 7/16" | 17   | 0.058     | 0.321 | 0.2354  |
| 7/16" | 16   | 0.065     | 0.307 | 0.2589  |
| 7/16" | 14   | 0.083     | 0.271 | 0.3147  |
| 7/16" | 13   | 0.095     | 0.247 | 0.3480  |
| 7/16" | 12   | 0.109     | 0.219 | 0.3830  |
| 7/16" | 1/8  | 0.125     | 0.188 | 0.4179  |
| 7/16" | 10   | 0.134     | 0.169 | 0.4351  |
|       |      |           |       |         |
| 1/2"  | 24   | 0.022     | 0.456 | 0.1123  |
| 1/2"  | 22   | 0.028     | 0.444 | 0.1411  |
| 1/2"  | 21   | 0.032     | 0.436 | 0.1599  |
| 1/2"  | 20   | 0.035     | 0.430 | 0.1738  |
| 1/2"  | 19   | 0.042     | 0.416 | 0.2054  |
| 1/2"  | 18   | 0.049     | 0.402 | 0.2360  |
| 1/2"  | 17   | 0.058     | 0.384 | 0.2738  |
| 1/2"  | 16   | 0.065     | 0.370 | 0.3020  |
| 1/2"  | 15   | 0.072     | 0.356 | 0.3291  |
| 1/2"  | 14   | 0.083     | 0.334 | 0.3696  |
| 1/2"  | 13   | 0.095     | 0.310 | 0.4109  |
| 1/2"  | 12   | 0.109     | 0.282 | 0.4552  |
| 1/2"  | 11   | 0.120     | 0.260 | 0.4870  |
| 1/2"  | 1/8  | 0.125     | 0.250 | 0.5006  |
| 1/2"  | 10   | 0.134     | 0.232 | 0.5238  |
| 1/2"  | 5/32 | 0.156     | 0.187 | 0.5731  |
| 1/2"  | 3/16 | 0.187     | 0.125 | 0.6264  |

| O.D.   | G.A. | Wall Dec. | I.D.  | WT / FT |
|--------|------|-----------|-------|---------|
| 17/32" | 16   | 0.065     | 0.401 | 0.3237  |
| 17/32" | 14   | 0.083     | 0.365 | 0.3971  |
| 17/32" | 11   | 0.120     | 0.291 | 0.5267  |
|        |      |           |       |         |
| 9/16"  | 24   | 0.022     | 0.518 | 0.1271  |
| 9/16"  | 23   | 0.025     | 0.513 | 0.1436  |
| 9/16"  | 22   | 0.028     | 0.506 | 0.1600  |
| 9/16"  | 21   | 0.032     | 0.499 | 0.1815  |
| 9/16"  | 20   | 0.035     | 0.492 | 0.1974  |
| 9/16"  | 18   | 0.049     | 0.464 | 0.2690  |
| 9/16"  | 16   | 0.065     | 0.432 | 0.3457  |
| 9/16"  | 14   | 0.083     | 0.396 | 0.4255  |
| 9/16"  | 13   | 0.095     | 0.372 | 0.4748  |
| 9/16"  | 12   | 0.109     | 0.344 | 0.5285  |
| 9/16"  | 11   | 0.120     | 0.322 | 0.5677  |
| 9/16"  | 1/8  | 0.125     | 0.313 | 0.5847  |
| 9/16"  | 10   | 0.134     | 0.294 | 0.6140  |
| 9/16"  | 5/32 | 0.156     | 0.250 | 0.6781  |
| 9/16"  | 3/16 | 0.187     | 0.187 | 0.7529  |
|        |      |           |       |         |
| 5/8"   | 24   | 0.022     | 0.581 | 0.1417  |
| 5/8"   | 23   | 0.025     | 0.575 | 0.1602  |
| 5/8"   | 22   | 0.028     | 0.569 | 0.1785  |
| 5/8"   | 21   | 0.032     | 0.561 | 0.2027  |
| 5/8"   | 20   | 0.035     | 0.555 | 0.2205  |
| 5/8"   | 18   | 0.049     | 0.527 | 0.3014  |
| 5/8"   | 17   | 0.058     | 0.509 | 0.3512  |
| 5/8"   | 16   | 0.065     | 0.495 | 0.3888  |
| 5/8"   | 15   | 0.072     | 0.481 | 0.4252  |
| 5/8"   | 14   | 0.083     | 0.459 | 0.4805  |
| 5/8"   | 13   | 0.095     | 0.435 | 0.5377  |
| 5/8"   | 12   | 0.109     | 0.407 | 0.6007  |
| 5/8"   | 11   | 0.120     | 0.385 | 0.6472  |
| 5/8"   | 1/8  | 0.125     | 0.375 | 0.6675  |
| 5/8"   | 10   | 0.134     | 0.357 | 0.7027  |
| 5/8"   | 5/32 | 0.156     | 0.312 | 0.7814  |
| 5/8"   | 3/16 | 0.187     | 0.250 | 0.8774  |
| 5/8"   | 7/32 | 0.219     | 0.187 | 0.9496  |
| 5/8"   | 1/4  | 0.250     | 0.125 | 1.0010  |

**Cold Drawn Butt Welded** – A low cost steel tube which may be redrawn from continuous welded steel pipe. Drawn to commercial tolerances and satisfactory for many applications where strength is not critical. Not intended for pressure applications. Produced to ASTM A512.



## Round Mechanical Tube

| O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT | O.D.   | G.A. | Wall Dec. | I.D.  | WT / FT |
|--------|-------|-----------|-------|---------|--------|------|-----------|-------|---------|
| 21/32" | 13    | 0.095     | 0.466 | 0.5692  | 13/16" | 22   | 0.028     | 0.756 | 0.2347  |
|        |       |           |       |         | 13/16" | 20   | 0.035     | 0.742 | 0.2908  |
| 11/16" | 23    | 0.025     | 0.638 | 0.1770  | 13/16" | 18   | 0.049     | 0.714 | 0.3998  |
| 11/16" | 22    | 0.028     | 0.631 | 0.1974  | 13/16" | 17   | 0.058     | 0.697 | 0.4677  |
| 11/16" | 21    | 0.032     | 0.624 | 0.2242  | 13/16" | 16   | 0.065     | 0.682 | 0.5193  |
| 11/16" | 18    | 0.049     | 0.589 | 0.3344  | 13/16" | 14   | 0.083     | 0.646 | 0.6471  |
| 11/16" | 17    | 0.058     | 0.571 | 0.3902  | 13/16" | 13   | 0.095     | 0.622 | 0.7285  |
| 11/16" | 16    | 0.065     | 0.557 | 0.4325  | 13/16" | 12   | 0.109     | 0.594 | 0.8195  |
| 11/16" | 14    | 0.083     | 0.521 | 0.5363  | 13/16" | 11   | 0.120     | 0.572 | 0.8881  |
| 11/16" | 13    | 0.095     | 0.497 | 0.6017  | 13/16" | 1/8  | 0.125     | 0.563 | 0.9185  |
| 11/16" | 12    | 0.109     | 0.467 | 0.6740  | 13/16" | 10   | 0.134     | 0.544 | 0.9717  |
| 11/16" | 11    | 0.120     | 0.447 | 0.7279  | 13/16" | 5/32 | 0.156     | 0.500 | 1.0950  |
| 11/16" | 1/8   | 0.125     | 0.438 | 0.7516  | 13/16" | 3/16 | 0.187     | 0.437 | 1.2550  |
| 11/16" | 10    | 0.134     | 0.419 | 0.7928  | 13/16" | 7/32 | 0.219     | 0.375 | 1.3890  |
| 11/16" | 5/32  | 0.156     | 0.375 | 0.8864  | 13/16" | 1/4  | 0.250     | 0.312 | 1.5030  |
| 11/16" | 3/16  | 0.187     | 0.312 | 1.0040  | 27/32" | 12   | 0.109     | 0.625 | 0.8554  |
| 11/16" | 7/32  | 0.219     | 0.250 | 1.0970  | 27/32" | 5/32 | 0.156     | 0.531 | 1.1460  |
| 3/4"   | 24    | 0.022     | 0.706 | 0.1711  | 7/8"   | 24   | 0.022     | 0.831 | 0.2004  |
| 3/4"   | 22    | 0.028     | 0.694 | 0.2159  | 7/8"   | 22   | 0.028     | 0.819 | 0.2533  |
| 3/4"   | 20    | 0.035     | 0.680 | 0.2673  | 7/8"   | 21   | 0.032     | 0.811 | 0.2881  |
| 3/4"   | 18    | 0.049     | 0.652 | 0.3668  | 7/8"   | 20   | 0.035     | 0.805 | 0.3140  |
| 3/4"   | 17    | 0.058     | 0.634 | 0.4287  | 7/8"   | 18   | 0.049     | 0.777 | 0.4323  |
| 3/4"   | 16    | 0.065     | 0.620 | 0.4755  | 7/8"   | 17   | 0.058     | 0.759 | 0.5061  |
| 3/4"   | 15    | 0.072     | 0.606 | 0.5214  | 7/8"   | 16   | 0.065     | 0.745 | 0.5623  |
| 3/4"   | 14    | 0.083     | 0.584 | 0.5913  | 7/8"   | 15   | 0.072     | 0.731 | 0.6175  |
| 3/4"   | 13    | 0.095     | 0.560 | 0.6646  | 7/8"   | 14   | 0.083     | 0.709 | 0.7021  |
| 3/4"   | 12    | 0.109     | 0.532 | 0.7462  | 7/8"   | 13   | 0.095     | 0.685 | 0.7914  |
| 3/4"   | 11    | 0.120     | 0.510 | 0.8074  | 7/8"   | 12   | 0.109     | 0.657 | 0.8917  |
| 3/4"   | 1/8   | 0.125     | 0.500 | 0.8344  | 7/8"   | 11   | 0.120     | 0.635 | 0.9676  |
| 3/4"   | 10    | 0.134     | 0.482 | 0.8816  | 7/8"   | 1/8  | 0.125     | 0.625 | 1.0010  |
| 3/4"   | 5/32  | 0.156     | 0.437 | 0.9897  | 7/8"   | 10   | 0.134     | 0.607 | 1.0600  |
| 3/4"   | 11/64 | 0.172     | 0.406 | 1.0620  | 7/8"   | 5/32 | 0.156     | 0.562 | 1.1980  |
| 3/4"   | 3/16  | 0.187     | 0.375 | 1.1280  | 7/8"   | 3/16 | 0.187     | 0.500 | 1.3790  |
| 3/4"   | 7/32  | 0.219     | 0.312 | 1.2420  | 7/8"   | 7/32 | 0.219     | 0.437 | 1.5340  |
| 3/4"   | 1/4   | 0.250     | 0.250 | 1.3350  | 7/8"   | 1/4  | 0.250     | 0.375 | 1.6690  |
|        |       |           |       |         | 7/8"   | 9/32 | 0.281     | 0.313 | 1.7830  |
|        |       |           |       |         | 7/8"   | 5/16 | 0.313     | 0.250 | 1.8790  |

## Round Mechanical Tube

| O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT | O.D.    | G.A.  | Wall Dec. | I.D.  | WT / FT |
|--------|-------|-----------|-------|---------|---------|-------|-----------|-------|---------|
| 15/16" | 20    | 0.035     | 0.867 | 0.3375  | 1-1/16" | 22    | 0.028     | 1.006 | 0.3095  |
| 15/16" | 18    | 0.049     | 0.839 | 0.4652  | 1-1/16" | 20    | 0.035     | 0.992 | 0.3843  |
| 15/16" | 16    | 0.065     | 0.807 | 0.6060  | 1-1/16" | 18    | 0.049     | 0.964 | 0.5306  |
| 15/16" | 14    | 0.083     | 0.771 | 0.7579  | 1-1/16" | 16    | 0.065     | 0.932 | 0.6928  |
| 15/16" | 13    | 0.095     | 0.747 | 0.8553  | 1-1/16" | 14    | 0.083     | 0.896 | 0.8687  |
| 15/16" | 12    | 0.109     | 0.719 | 0.9651  | 1-1/16" | 13    | 0.095     | 0.872 | 0.9821  |
| 15/16" | 11    | 0.120     | 0.697 | 1.0480  | 1-1/16" | 12    | 0.109     | 0.844 | 1.1110  |
| 15/16" | 1/8   | 0.125     | 0.688 | 1.0850  | 1-1/16" | 11    | 0.120     | 0.822 | 1.2090  |
| 15/16" | 10    | 0.134     | 0.669 | 1.1510  | 1-1/16" | 1/8   | 0.125     | 0.813 | 1.2520  |
| 15/16" | 5/32  | 0.156     | 0.625 | 1.3030  | 1-1/16" | 10    | 0.134     | 0.795 | 1.3300  |
| 15/16" | 3/16  | 0.187     | 0.562 | 1.5060  | 1-1/16" | 5/32  | 0.156     | 0.750 | 1.5110  |
| 15/16" | 7/32  | 0.219     | 0.500 | 1.6820  | 1-1/16" | 3/16  | 0.187     | 0.687 | 1.7570  |
| 15/16" | 1/4   | 0.250     | 0.437 | 1.8370  | 1-1/16" | 8/32  | 0.219     | 0.625 | 1.9740  |
|        |       |           |       |         | 1-1/16" | 1/4   | 0.250     | 0.562 | 2.1710  |
| 1"     | 22    | 0.028     | 0.944 | 0.2907  | 1-1/16" | 9/32  | 0.281     | 0.500 | 2.3470  |
| 1"     | 21    | 0.032     | 0.936 | 0.3308  | 1-1/16" | 5/16  | 0.313     | 0.437 | 2.5070  |
| 1"     | 20    | 0.035     | 0.930 | 0.3607  | 1-1/16" | 3/8   | 0.375     | 0.313 | 2.7550  |
| 1"     | 18    | 0.049     | 0.902 | 0.4977  |         |       |           |       |         |
| 1"     | 17    | 0.058     | 0.884 | 0.5835  | 1-1/8"  | 24    | 0.022     | 1.081 | 0.2592  |
| 1"     | 16    | 0.065     | 0.870 | 0.6491  | 1-1/8"  | 22    | 0.028     | 1.069 | 0.3280  |
| 1"     | 15    | 0.072     | 0.856 | 0.7136  | 1-1/8"  | 20    | 0.035     | 1.055 | 0.4074  |
| 1"     | 14    | 0.083     | 0.834 | 0.8129  | 1-1/8"  | 18    | 0.049     | 1.027 | 0.5631  |
| 1"     | 13    | 0.095     | 0.810 | 0.9182  | 1-1/8"  | 17    | 0.058     | 1.009 | 0.6609  |
| 1"     | 12    | 0.109     | 0.782 | 1.0370  | 1-1/8"  | 16    | 0.065     | 0.995 | 0.7359  |
| 1"     | 11    | 0.120     | 0.760 | 1.1280  | 1-1/8"  | 14    | 0.083     | 0.959 | 0.9237  |
| 1"     | 1/8   | 0.125     | 0.750 | 1.1680  | 1-1/8"  | 13    | 0.095     | 0.935 | 1.0450  |
| 1"     | 10    | 0.134     | 0.732 | 1.2390  | 1-1/8"  | 12    | 0.109     | 0.907 | 1.1830  |
| 1"     | 5/32  | 0.156     | 0.687 | 1.4060  | 1-1/8"  | 11    | 0.120     | 0.885 | 1.2880  |
| 1"     | 11/64 | 0.172     | 0.656 | 1.5210  | 1-1/8"  | 1/8   | 0.125     | 0.875 | 1.3350  |
| 1"     | 7     | 0.180     | 0.640 | 1.5760  | 1-1/8"  | 10    | 0.134     | 0.857 | 1.4180  |
| 1"     | 3/16  | 0.187     | 0.625 | 1.6300  | 1-1/8"  | 5/32  | 0.156     | 0.812 | 1.6140  |
| 1"     | 7/32  | 0.219     | 0.562 | 1.8270  | 1-1/8"  | 11/64 | 0.172     | 0.781 | 1.7510  |
| 1"     | 1/4   | 0.250     | 0.500 | 2.0030  | 1-1/8"  | 3/16  | 0.187     | 0.750 | 1.8810  |
| 1"     | 9/32  | 0.281     | 0.437 | 2.1580  | 1-1/8"  | 7/32  | 0.219     | 0.687 | 2.1190  |
| 1"     | 5/16  | 0.313     | 0.375 | 2.2970  | 1-1/8"  | 1/4   | 0.250     | 0.625 | 2.3360  |
| 1"     | 11/32 | 0.344     | 0.312 | 2.4100  | 1-1/8"  | 9/32  | 0.281     | 0.563 | 2.5330  |
| 1"     | 3/8   | 0.375     | 0.250 | 2.5030  | 1-1/8"  | 5/16  | 0.313     | 0.500 | 2.7140  |
|        |       |           |       |         | 1-1/8"  | 3/8   | 0.375     | 0.375 | 3.0040  |

## Round Mechanical Tube

| O.D.    | G.A.  | Wall Dec. | I.D.  | WT / FT | O.D.    | G.A.  | Wall Dec. | I.D.  | WT / FT |
|---------|-------|-----------|-------|---------|---------|-------|-----------|-------|---------|
| 1-3/16" | 22    | 0.028     | 1.131 | 0.3469  | 1-5/16" | 20    | 0.035     | 1.242 | 0.4777  |
| 1-3/16" | 21    | 0.032     | 1.124 | 0.3951  | 1-5/16" | 17    | 0.058     | 1.197 | 0.7774  |
| 1-3/16" | 20    | 0.035     | 1.117 | 0.4310  | 1-5/16" | 16    | 0.065     | 1.182 | 0.8664  |
| 1-3/16" | 18    | 0.049     | 1.089 | 0.5961  | 1-5/16" | 14    | 0.083     | 1.146 | 1.0900  |
| 1-3/16" | 16    | 0.065     | 1.057 | 0.7796  | 1-5/16" | 13    | 0.095     | 1.122 | 1.2360  |
| 1-3/16" | 14    | 0.083     | 1.021 | 0.9795  | 1-5/16" | 12    | 0.109     | 1.094 | 1.4020  |
| 1-3/16" | 13    | 0.095     | 0.997 | 1.1090  | 1-5/16" | 11    | 0.120     | 1.072 | 1.5290  |
| 1-3/16" | 11    | 0.120     | 0.947 | 1.3690  | 1-5/16" | 1/8   | 0.125     | 1.063 | 1.5860  |
| 1-3/16" | 1/8   | 0.125     | 0.938 | 1.4190  | 1-5/16" | 10    | 0.134     | 1.044 | 1.6870  |
| 1-3/16" | 5/32  | 0.156     | 0.875 | 1.7190  | 1-5/16" | 9     | 0.148     | 1.017 | 1.8410  |
| 1-3/16" | 3/16  | 0.187     | 0.812 | 2.0080  | 1-5/16" | 5/32  | 0.156     | 1.000 | 1.9280  |
| 1-3/16" | 7/32  | 0.219     | 0.750 | 2.2660  | 1-5/16" | 3/16  | 0.187     | 0.937 | 2.2590  |
| 1-3/16" | 1/4   | 0.250     | 0.687 | 2.5040  | 1-5/16" | 7/32  | 0.219     | 0.875 | 2.5590  |
| 1-3/16" | 5/16  | 0.313     | 0.562 | 2.9250  | 1-5/16" | 1/4   | 0.250     | 0.812 | 2.8380  |
|         |       |           |       |         | 1-5/16" | 9/32  | 0.281     | 0.750 | 3.0970  |
| 1-1/4"  | 22    | 0.028     | 1.194 | 0.3654  | 1-5/16" | 5/16  | 0.313     | 0.687 | 3.3430  |
| 1-1/4"  | 20    | 0.035     | 1.180 | 0.4542  | 1-5/16" | 3/8   | 0.375     | 0.562 | 3.7570  |
| 1-1/4"  | 18    | 0.049     | 1.152 | 0.6285  |         |       |           |       |         |
| 1-1/4"  | 17    | 0.058     | 1.134 | 0.7384  | 1-3/8"  | 22    | 0.028     | 1.319 | 0.4028  |
| 1-1/4"  | 16    | 0.065     | 1.120 | 0.8226  | 1-3/8"  | 20    | 0.035     | 1.305 | 0.5009  |
| 1-1/4"  | 14    | 0.083     | 1.084 | 1.0340  | 1-3/8"  | 18    | 0.049     | 1.277 | 0.6939  |
| 1-1/4"  | 13    | 0.095     | 1.060 | 1.1720  | 1-3/8"  | 17    | 0.058     | 1.259 | 0.8158  |
| 1-1/4"  | 12    | 0.109     | 1.032 | 1.3280  | 1-3/8"  | 16    | 0.065     | 1.245 | 0.9094  |
| 1-1/4"  | 11    | 0.120     | 1.010 | 1.4480  | 1-3/8"  | 14    | 0.083     | 1.209 | 1.1450  |
| 1-1/4"  | 1/8   | 0.125     | 1.000 | 1.5020  | 1-3/8"  | 13    | 0.095     | 1.185 | 1.2990  |
| 1-1/4"  | 10    | 0.134     | 0.982 | 1.5970  | 1-3/8"  | 12    | 0.109     | 1.157 | 1.4740  |
| 1-1/4"  | 5/32  | 0.156     | 0.937 | 1.8230  | 1-3/8"  | 11    | 0.120     | 1.135 | 1.6080  |
| 1-1/4"  | 3/16  | 0.187     | 0.875 | 2.1320  | 1-3/8"  | 1/8   | 0.125     | 1.125 | 1.6690  |
| 1-1/4"  | 7/32  | 0.219     | 0.812 | 2.4110  | 1-3/8"  | 10    | 0.134     | 1.107 | 1.7760  |
| 1-1/4"  | 1/4   | 0.250     | 0.750 | 2.6700  | 1-3/8"  | 5/32  | 0.156     | 1.062 | 2.0310  |
| 1-1/4"  | 9/32  | 0.281     | 0.687 | 2.9080  | 1-3/8"  | 11/64 | 0.1720    | 1.031 | 2.2100  |
| 1-1/4"  | 5/16  | 0.313     | 0.625 | 3.1320  | 1-3/8"  | 3/16  | 0.187     | 1.000 | 2.3830  |
| 1-1/4"  | 11/32 | 0.344     | 0.562 | 3.3290  | 1-3/8"  | 7/32  | 0.219     | 0.937 | 2.7040  |
| 1-1/4"  | 3/8   | 0.375     | 0.500 | 3.5040  | 1-3/8"  | 1/4   | 0.250     | 0.875 | 3.0040  |
| 1-1/4"  | 7/16  | 0.437     | 0.375 | 3.7980  | 1-3/8"  | 9/32  | 0.281     | 0.813 | 3.2830  |
|         |       |           |       |         | 1-3/8"  | 5/16  | 0.313     | 0.750 | 3.5500  |
|         |       |           |       |         | 1-3/8"  | 3/8   | 0.375     | 0.625 | 4.0050  |
|         |       |           |       |         | 1-3/8"  | 1/2   | 0.500     | 0.375 | 4.6730  |

## Round Mechanical Tube

| O.D.    | G.A.  | Wall Dec. | I.D.  | WT / FT |
|---------|-------|-----------|-------|---------|
| 1-7/16" | 20    | 0.035     | 1.367 | 0.5244  |
| 1-7/16" | 16    | 0.065     | 1.307 | 0.9531  |
| 1-7/16" | 14    | 0.083     | 1.271 | 1.2010  |
| 1-7/16" | 13    | 0.095     | 1.247 | 1.3630  |
| 1-7/16" | 11    | 0.120     | 1.197 | 1.6890  |
| 1-7/16" | 10    | 0.134     | 1.170 | 1.8660  |
| 1-7/16" | 5/32  | 0.156     | 1.125 | 2.1360  |
| 1-7/16" | 3/16  | 0.187     | 1.062 | 2.5100  |
| 1-7/16" | 7/32  | 0.219     | 1.000 | 2.8510  |
| 1-7/16" | 1/4   | 0.250     | 0.937 | 3.1720  |
|         |       |           |       |         |
| 1-1/2"  | 22    | 0.028     | 1.444 | 0.4402  |
| 1-1/2"  | 20    | 0.035     | 1.430 | 0.5476  |
| 1-1/2"  | 18    | 0.049     | 1.402 | 0.7593  |
| 1-1/2"  | 17    | 0.058     | 1.384 | 0.8932  |
| 1-1/2"  | 16    | 0.065     | 1.370 | 0.9962  |
| 1-1/2"  | 14    | 0.083     | 1.334 | 1.2560  |
| 1-1/2"  | 13    | 0.095     | 1.310 | 1.4260  |
| 1-1/2"  | 12    | 0.109     | 1.282 | 1.6190  |
| 1-1/2"  | 11    | 0.120     | 1.260 | 1.7690  |
| 1-1/2"  | 1/8   | 0.125     | 1.250 | 1.8360  |
| 1-1/2"  | 10    | 0.134     | 1.232 | 1.9550  |
| 1-1/2"  | 5/32  | 0.156     | 1.187 | 2.2390  |
| 1-1/2"  | 3/16  | 0.187     | 1.125 | 2.6340  |
| 1-1/2"  | 7/32  | 0.219     | 1.062 | 2.9960  |
| 1-1/2"  | 1/4   | 0.250     | 1.000 | 3.3380  |
| 1-1/2"  | 9/32  | 0.281     | 0.938 | 3.6580  |
| 1-1/2"  | 5/16  | 0.313     | 0.875 | 3.9680  |
| 1-1/2"  | 11/32 | 0.344     | 0.812 | 4.2470  |
| 1-1/2"  | 3/8   | 0.375     | 0.750 | 4.5060  |
| 1-1/2"  | 7/16  | 0.438     | 0.625 | 4.9680  |
| 1-1/2"  | 1/2   | 0.500     | 0.500 | 5.3400  |

| O.D.    | G.A.  | Wall Dec. | I.D.  | WT / FT |
|---------|-------|-----------|-------|---------|
| 1-9/16" | 20    | 0.035     | 1.493 | 0.5712  |
| 1-9/16" | 16    | 0.065     | 1.432 | 1.0400  |
| 1-9/16" | 13    | 0.095     | 1.372 | 1.4890  |
| 1-9/16" | 12    | 0.109     | 1.345 | 1.6930  |
| 1-9/16" | 11    | 0.120     | 1.322 | 1.8490  |
| 1-9/16" | 1/8   | 0.125     | 1.313 | 1.9200  |
| 1-9/16" | 10    | 0.134     | 1.295 | 2.0450  |
| 1-9/16" | 5/32  | 0.156     | 1.250 | 2.3440  |
| 1-9/16" | 3/16  | 0.187     | 1.187 | 2.7610  |
| 1-9/16" | 1/4   | 0.250     | 1.062 | 3.5060  |
| 1-9/16" | 5/16  | 0.313     | 0.937 | 4.1790  |
| 1-9/16" | 3/8   | 0.375     | 0.812 | 4.7580  |
|         |       |           |       |         |
| 1-5/8"  | 20    | 0.035     | 1.555 | 0.5943  |
| 1-5/8"  | 18    | 0.049     | 1.527 | 0.8248  |
| 1-5/8"  | 17    | 0.058     | 1.509 | 0.9707  |
| 1-5/8"  | 16    | 0.065     | 1.495 | 1.0830  |
| 1-5/8"  | 14    | 0.083     | 1.459 | 1.3670  |
| 1-5/8"  | 13    | 0.095     | 1.435 | 1.5520  |
| 1-5/8"  | 12    | 0.109     | 1.407 | 1.7650  |
| 1-5/8"  | 11    | 0.120     | 1.385 | 1.9290  |
| 1-5/8"  | 1/8   | 0.125     | 1.375 | 2.0030  |
| 1-5/8"  | 10    | 0.134     | 1.357 | 2.1340  |
| 1-5/8"  | 5/32  | 0.156     | 1.312 | 2.4470  |
| 1-5/8"  | 11/64 | 0.172     | 1.281 | 2.6690  |
| 1-5/8"  | 3/16  | 0.187     | 1.250 | 2.8850  |
| 1-5/8"  | 7/32  | 0.219     | 1.187 | 3.2890  |
| 1-5/8"  | 1/4   | 0.250     | 1.125 | 3.6710  |
| 1-5/8"  | 9/32  | 0.281     | 1.063 | 4.0330  |
| 1-5/8"  | 5/16  | 0.313     | 1.000 | 4.3860  |
| 1-5/8"  | 3/8   | 0.375     | 0.875 | 5.0060  |
| 1-5/8"  | 7/16  | 0.438     | 0.749 | 5.5530  |
| 1-5/8"  | 1/2   | 0.500     | 0.625 | 6.0080  |

## Round Mechanical Tube

| O.D.     | G.A. | Wall Dec. | I.D.  | WT / FT | O.D.     | G.A. | Wall Dec. | I.D.  | WT / FT |
|----------|------|-----------|-------|---------|----------|------|-----------|-------|---------|
| 1-11/16" | 16   | 0.065     | 1.558 | 1.1270  | 1-7/8"   | 20   | 0.035     | 1.805 | 0.6878  |
| 1-11/16" | 11   | 0.120     | 1.447 | 2.0100  | 1-7/8"   | 18   | 0.049     | 1.777 | 0.9556  |
| 1-11/16" | 1/8  | 0.125     | 1.438 | 2.0860  | 1-7/8"   | 16   | 0.065     | 1.745 | 1.2570  |
| 1-11/16" | 5/32 | 0.156     | 1.376 | 2.5520  | 1-7/8"   | 14   | 0.083     | 1.709 | 1.5890  |
| 1-11/16" | 3/16 | 0.187     | 1.312 | 3.0120  | 1-7/8"   | 13   | 0.095     | 1.685 | 1.8060  |
| 1-11/16" | 7/32 | 0.219     | 1.250 | 3.4360  | 1-7/8"   | 12   | 0.109     | 1.657 | 2.0560  |
| 1-11/16" | 1/4  | 0.250     | 1.188 | 3.8390  | 1-7/8"   | 11   | 0.120     | 1.635 | 2.2490  |
|          |      |           |       |         | 1-7/8"   | 1/8  | 0.125     | 1.625 | 2.3360  |
| 1-3/4"   | 20   | 0.035     | 1.680 | 0.6411  | 1-7/8"   | 10   | 0.134     | 1.607 | 2.4920  |
| 1-3/4"   | 19   | 0.42      | 1.666 | 0.7661  | 1-7/8"   | 5/32 | 0.156     | 1.562 | 2.8640  |
| 1-3/4"   | 18   | 0.049     | 1.652 | 0.8902  | 1-7/8"   | 3/16 | 0.187     | 1.500 | 3.3870  |
| 1-3/4"   | 16   | 0.065     | 1.620 | 1.1700  | 1-7/8"   | 7/32 | 0.219     | 1.437 | 3.8730  |
| 1-3/4"   | 14   | 0.083     | 1.584 | 1.4780  | 1-7/8"   | 1/4  | 0.250     | 1.375 | 4.3390  |
| 1-3/4"   | 13   | 0.095     | 1.560 | 1.6790  | 1-7/8"   | 9/32 | 0.281     | 1.313 | 4.7840  |
| 1-3/4"   | 12   | 0.109     | 1.532 | 1.9100  | 1-7/8"   | 5/16 | 0.313     | 1.250 | 5.2220  |
| 1-3/4"   | 11   | 0.120     | 1.510 | 2.0890  | 1-7/8"   | 3/8  | 0.375     | 1.125 | 6.0080  |
| 1-3/4"   | 1/8  | 0.125     | 1.500 | 2.1690  | 1-7/8"   | 7/16 | 0.438     | 1.000 | 6.7220  |
| 1-3/4"   | 10   | 0.134     | 1.482 | 2.3130  | 1-7/8"   | 1/2  | 0.500     | 0.875 | 7.3430  |
| 1-3/4"   | 5/32 | 0.156     | 1.437 | 2.6560  | 1-7/8"   | 9/16 | 0.563     | 0.750 | 7.8890  |
| 1-3/4"   | 3/16 | 0.187     | 1.375 | 3.1360  |          |      |           |       |         |
| 1-3/4"   | 7/32 | 0.219     | 1.312 | 3.5810  | 1-15/16" | 1/8  | 0.125     | 1.688 | 2.4200  |
| 1-3/4"   | 1/4  | 0.250     | 1.250 | 4.0050  | 1-15/16" | 5/32 | 0.156     | 1.626 | 2.9690  |
| 1-3/4"   | 9/32 | 0.281     | 1.188 | 4.4090  | 1-15/16" | 7/32 | 0.219     | 1.499 | 4.0210  |
| 1-3/4"   | 5/16 | 0.313     | 1.125 | 4.8040  | 1-15/16" | 1/4  | 0.250     | 1.437 | 4.5070  |
| 1-3/4"   | 3/8  | 0.375     | 1.000 | 5.5070  | 1-15/16" | 3/8  | 0.375     | 1.188 | 6.2600  |
| 1-3/4"   | 7/16 | 0.438     | 0.875 | 6.1370  |          |      |           |       |         |
| 1-3/4"   | 1/2  | 0.500     | 0.750 | 6.6750  | 2"       | 20   | 0.035     | 1.930 | 0.7345  |
| 1-3/4"   | 9/16 | 0.563     | 0.624 | 7.1370  | 2"       | 18   | 0.049     | 1.902 | 1.0210  |
| 1-3/4"   | 5/8  | 0.625     | 0.500 | 7.5090  | 2"       | 16   | 0.065     | 1.870 | 1.3430  |
|          |      |           |       |         | 2"       | 14   | 0.083     | 1.834 | 1.6990  |
| 1-13/16" | 11   | 0.120     | 1.572 | 2.1700  | 2"       | 13   | 0.095     | 1.810 | 1.9330  |
| 1-13/16" | 5/32 | 0.156     | 1.501 | 2.7610  | 2"       | 12   | 0.109     | 1.782 | 2.2010  |
| 1-13/16" | 3/16 | 0.187     | 1.439 | 3.2630  | 2"       | 11   | 0.120     | 1.760 | 2.4090  |
| 1-13/16" | 1/4  | 0.250     | 1.313 | 4.1730  | 2"       | 1/8  | 0.125     | 1.751 | 2.5030  |
|          |      |           |       |         | 2"       | 10   | 0.134     | 1.732 | 2.6700  |
|          |      |           |       |         | 2"       | 5/32 | 0.156     | 1.687 | 3.0720  |
|          |      |           |       |         | 2"       | 7    | 0.180     | 1.640 | 3.4990  |
|          |      |           |       |         | 2"       | 3/16 | 0.187     | 1.625 | 3.6380  |
|          |      |           |       |         | 2"       | 7/32 | 0.219     | 1.562 | 4.1660  |
|          |      |           |       |         | 2"       | 1/4  | 0.250     | 1.500 | 4.6730  |

## Round Mechanical Tube

| O.D.    | G.A.  | Wall Dec. | I.D.  | WT / FT | O.D.    | G.A.  | Wall Dec. | I.D.  | WT / FT |
|---------|-------|-----------|-------|---------|---------|-------|-----------|-------|---------|
| 2"      | 9/32  | 0.281     | 1.438 | 5.1590  | 2-1/4"  | 20    | 0.035     | 2.180 | 0.8280  |
| 2"      | 5/16  | 0.313     | 1.375 | 5.6390  | 2-1/4"  | 18    | 0.049     | 2.152 | 1.1520  |
| 2"      | 11/32 | 0.344     | 1.312 | 6.0840  | 2-1/4"  | 16    | 0.065     | 2.120 | 1.5170  |
| 2"      | 3/8   | 0.375     | 1.250 | 6.5080  | 2-1/4"  | 14    | 0.083     | 2.084 | 1.9210  |
| 2"      | 7/16  | 0.438     | 1.125 | 7.3070  | 2-1/4"  | 13    | 0.095     | 2.060 | 2.1860  |
| 2"      | 1/2   | 0.500     | 1.000 | 8.0100  | 2-1/4"  | 12    | 0.109     | 2.032 | 2.4920  |
| 2"      | 9/16  | 0.563     | 0.876 | 8.6400  | 2-1/4"  | 11    | 0.120     | 2.010 | 2.7300  |
| 2"      | 5/8   | 0.625     | 0.750 | 9.1780  | 2-1/4"  | 1/8   | 0.125     | 2.000 | 2.8370  |
| 2"      | 3/4   | 0.750     | 0.500 | 10.0100 | 2-1/4"  | 10    | 0.134     | 1.982 | 3.0280  |
|         |       |           |       |         | 2-1/4"  | 5/32  | 0.156     | 1.937 | 3.4890  |
| 2-1/16" | 5/32  | 0.156     | 1.750 | 3.1770  | 2-1/4"  | 3/16  | 0.187     | 1.875 | 4.1400  |
| 2-1/16" | 3/16  | 0.187     | 1.689 | 3.7650  | 2-1/4"  | 7/32  | 0.219     | 1.812 | 4.7500  |
| 2-1/16" | 1/4   | 0.250     | 1.562 | 4.8410  | 2-1/4"  | 1/4   | 0.250     | 1.750 | 5.3400  |
| 2-1/16" | 5/16  | 0.313     | 1.437 | 5.8500  | 2-1/4"  | 9/32  | 0.281     | 1.688 | 5.9090  |
|         |       |           |       |         | 2-1/4"  | 5/16  | 0.313     | 1.625 | 6.4750  |
| 2-1/8"  | 20    | 0.035     | 2.055 | 0.7813  | 2-1/4"  | 11/32 | 0.344     | 1.562 | 7.0020  |
| 2-1/8"  | 18    | 0.049     | 2.027 | 1.0860  | 2-1/4"  | 3/8   | 0.375     | 1.500 | 7.5090  |
| 2-1/8"  | 16    | 0.065     | 1.995 | 1.4300  | 2-1/4"  | 13/32 | 0.406     | 1.438 | 7.9960  |
| 2-1/8"  | 14    | 0.083     | 1.959 | 1.8100  | 2-1/4"  | 7/16  | 0.438     | 1.375 | 8.4760  |
| 2-1/8"  | 13    | 0.095     | 1.935 | 2.0600  | 2-1/4"  | 1/2   | 0.500     | 1.250 | 9.3450  |
| 2-1/8"  | 11    | 0.120     | 1.885 | 2.5700  | 2-1/4"  | 9/16  | 0.563     | 1.124 | 10.1400 |
| 2-1/8"  | 1/8   | 0.125     | 1.875 | 2.6700  | 2-1/4"  | 5/8   | 0.625     | 1.000 | 10.8500 |
| 2-1/8"  | 5/32  | 0.156     | 1.812 | 3.2810  | 2-1/4"  | 3/4   | 0.750     | 0.750 | 12.0200 |
| 2-1/8"  | 3/16  | 0.187     | 1.750 | 3.8890  |         |       |           |       |         |
| 2-1/8"  | 7/32  | 0.219     | 1.687 | 4.4580  | 2-5/16" | 3/16  | 0.187     | 1.939 | 4.2670  |
| 2-1/8"  | 1/4   | 0.250     | 1.625 | 5.0060  | 2-5/16" | 1/4   | 0.250     | 1.813 | 5.5080  |
| 2-1/8"  | 9/32  | 0.281     | 1.563 | 5.5340  |         |       |           |       |         |
| 2-1/8"  | 5/16  | 0.313     | 1.500 | 6.0570  | 2-3/8"  | 18    | 0.049     | 2.277 | 1.2170  |
| 2-1/8"  | 3/8   | 0.375     | 1.375 | 7.0090  | 2-3/8"  | 16    | 0.065     | 2.245 | 1.6040  |
| 2-1/8"  | 7/16  | 0.438     | 1.250 | 7.8920  | 2-3/8"  | 14    | 0.083     | 2.209 | 2.0320  |
| 2-1/8"  | 1/2   | 0.500     | 1.125 | 8.6780  | 2-3/8"  | 13    | 0.095     | 2.185 | 2.3130  |
| 2-1/8"  | 9/16  | 0.563     | 1.000 | 9.3920  | 2-3/8"  | 11    | 0.120     | 2.135 | 2.8900  |
| 2-1/8"  | 5/8   | 0.625     | 0.875 | 10.0100 | 2-3/8"  | 1/8   | 0.125     | 2.125 | 3.0040  |
|         |       |           |       |         | 2-3/8"  | 5/32  | 0.156     | 2.062 | 3.6970  |
| 2-3/16" | 1/8   | 0.125     | 1.938 | 2.7540  | 2-3/8"  | 3/16  | 0.187     | 2.000 | 4.3910  |
| 2-3/16" | 1/4   | 0.250     | 1.688 | 5.1740  | 2-3/8"  | 7/32  | 0.219     | 1.937 | 5.0430  |
|         |       |           |       |         | 2-3/8"  | 1/4   | 0.250     | 1.875 | 5.6740  |
|         |       |           |       |         | 2-3/8"  | 9/32  | 0.281     | 1.813 | 6.2840  |
|         |       |           |       |         | 2-3/8"  | 5/16  | 0.313     | 1.750 | 6.8930  |
|         |       |           |       |         | 2-3/8"  | 11/32 | 0.344     | 1.687 | 7.4620  |

## Round Mechanical Tube

| O.D.    | G.A.  | Wall Dec. | I.D.  | WT / FT | O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT |
|---------|-------|-----------|-------|---------|--------|-------|-----------|-------|---------|
| 2-3/8"  | 3/8   | 0.375     | 1.625 | 8.0100  | 2-5/8" | 18    | 0.049     | 2.528 | 1.3480  |
| 2-3/8"  | 7/16  | 0.438     | 1.500 | 9.0610  | 2-5/8" | 16    | 0.065     | 2.495 | 1.7770  |
| 2-3/8"  | 1/2   | 0.500     | 1.375 | 10.0100 | 2-5/8" | 14    | 0.083     | 2.459 | 2.2530  |
| 2-3/8"  | 9/16  | 0.563     | 1.249 | 10.9000 | 2-5/8" | 13    | 0.095     | 2.435 | 2.5670  |
| 2-3/8"  | 5/8   | 0.625     | 1.125 | 11.6800 | 2-5/8" | 12    | 0.109     | 2.407 | 2.9290  |
| 2-3/8"  | 3/4   | 0.750     | 0.875 | 13.0200 | 2-5/8" | 11    | 0.120     | 2.385 | 3.2100  |
|         |       |           |       |         | 2-5/8" | 1/8   | 0.125     | 2.375 | 3.3380  |
| 2-7/16" | 1/4   | 0.250     | 1.937 | 5.8420  | 2-5/8" | 5/32  | 0.156     | 2.312 | 4.1140  |
|         |       |           |       |         | 2-5/8" | 7     | 0.180     | 2.265 | 4.7000  |
| 2-1/2"  | 18    | 0.049     | 2.402 | 1.2830  | 2-5/8" | 3/16  | 0.187     | 2.250 | 4.8930  |
| 2-1/2"  | 16    | 0.065     | 2.370 | 1.6900  | 2-5/8" | 7/32  | 0.219     | 2.187 | 5.6270  |
| 2-1/2"  | 14    | 0.083     | 2.334 | 2.1430  | 2-5/8" | 1/4   | 0.250     | 2.125 | 6.3410  |
| 2-1/2"  | 13    | 0.095     | 2.310 | 2.4400  | 2-5/8" | 9/32  | 0.281     | 2.063 | 7.0350  |
| 2-1/2"  | 12    | 0.109     | 2.282 | 2.7830  | 2-5/8" | 5/16  | 0.313     | 2.000 | 7.7290  |
| 2-1/2"  | 11    | 0.120     | 2.260 | 3.0500  | 2-5/8" | 3/8   | 0.375     | 1.875 | 9.0110  |
| 2-1/2"  | 1/8   | 0.125     | 2.250 | 3.1710  | 2-5/8" | 7/16  | 0.483     | 1.751 | 10.2300 |
| 2-1/2"  | 10    | 0.134     | 2.232 | 3.3860  | 2-5/8" | 1/2   | 0.500     | 1.625 | 11.3500 |
| 2-1/2"  | 5/32  | 0.156     | 2.187 | 3.9050  | 2-5/8" | 9/16  | 0.563     | 1.501 | 12.4000 |
| 2-1/2"  | 7     | 0.180     | 2.140 | 4.4600  | 2-5/8" | 5/8   | 0.625     | 1.375 | 13.3500 |
| 2-1/2"  | 3/16  | 0.187     | 2.125 | 4.6420  |        |       |           |       |         |
| 2-1/2"  | 7/32  | 0.219     | 2.062 | 5.3350  | 2-3/4" | 18    | 0.049     | 2.652 | 1.4130  |
| 2-1/2"  | 1/4   | 0.250     | 2.000 | 6.0080  | 2-3/4" | 16    | 0.065     | 2.620 | 1.8640  |
| 2-1/2"  | 9/32  | 0.281     | 1.937 | 6.6590  | 2-3/4" | 14    | 0.083     | 2.584 | 2.3640  |
| 2-1/2"  | 5/16  | 0.313     | 1.875 | 7.3110  | 2-3/4" | 13    | 0.095     | 2.560 | 2.6940  |
| 2-1/2"  | 11/32 | 0.344     | 1.812 | 7.9210  | 2-3/4" | 11    | 0.120     | 2.510 | 3.3710  |
| 2-1/2"  | 3/8   | 0.375     | 1.750 | 8.5110  | 2-3/4" | 1/8   | 0.125     | 2.500 | 3.5040  |
| 2-1/2"  | 7/16  | 0.438     | 1.625 | 9.6460  | 2-3/4" | 10    | 0.134     | 2.482 | 3.7440  |
| 2-1/2"  | 1/2   | 0.500     | 1.500 | 10.6800 | 2-3/4" | 5/32  | 0.156     | 2.437 | 4.3220  |
| 2-1/2"  | 9/16  | 0.563     | 1.375 | 11.6500 | 2-3/4" | 3/16  | 0.187     | 2.375 | 5.1440  |
| 2-1/2"  | 5/8   | 0.625     | 1.250 | 12.5200 | 2-3/4" | 7/32  | 0.219     | 2.312 | 5.9200  |
| 2-1/2"  | 3/4   | 0.750     | 1.000 | 14.0200 | 2-3/4" | 1/4   | 0.250     | 2.250 | 6.6750  |
|         |       |           |       |         | 2-3/4" | 9/32  | 0.281     | 2.188 | 7.4100  |
| 2-9/16" | 1/4   | 0.250     | 2.062 | 6.1760  | 2-3/4" | 5/16  | 0.313     | 2.125 | 8.1470  |
|         |       |           |       |         | 2-3/4" | 11/32 | 0.344     | 2.062 | 8.8390  |
|         |       |           |       |         | 2-3/4" | 3/8   | 0.375     | 2.000 | 9.5120  |
|         |       |           |       |         | 2-3/4" | 7/16  | 0.437     | 1.875 | 10.8200 |

## Round Mechanical Tube

| O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT | O.D.    | G.A.  | Wall Dec. | I.D.  | WT / FT |
|--------|-------|-----------|-------|---------|---------|-------|-----------|-------|---------|
| 2-3/4" | 1/2   | 0.500     | 1.750 | 12.0200 | 3"      | 1/4   | 0.250     | 2.500 | 7.3430  |
| 2-3/4" | 9/16  | 0.563     | 1.625 | 13.1500 | 3"      | 9/32  | 0.281     | 2.437 | 8.1600  |
| 2-3/4" | 5/8   | 0.625     | 1.500 | 14.1800 | 3"      | 5/16  | 0.313     | 2.375 | 8.9820  |
| 2-3/4" | 11/16 | 0.688     | 1.374 | 15.1500 | 3"      | 11/32 | 0.344     | 2.312 | 9.7580  |
| 2-3/4" | 3/4   | 0.750     | 1.250 | 16.0200 | 3"      | 3/8   | 0.375     | 2.250 | 10.5100 |
| 2-3/4" | 7/8   | 0.875     | 1.000 | 17.5200 | 3"      | 7/16  | 0.438     | 2.125 | 11.9800 |
| 2-3/4" | 1     | 1.000     | 0.750 | 18.6900 | 3"      | 1/2   | 0.500     | 2.000 | 13.3500 |
|        |       |           |       |         | 3"      | 9/16  | 0.563     | 1.875 | 14.6500 |
| 2-7/8" | 16    | 0.065     | 2.745 | 1.9510  | 3"      | 5/8   | 0.625     | 1.750 | 15.8500 |
| 2-7/8" | 14    | 0.083     | 2.709 | 2.4750  | 3"      | 11/16 | 0.688     | 1.625 | 16.9900 |
| 2-7/8" | 13    | 0.095     | 2.685 | 2.8210  | 3"      | 3/4   | 0.750     | 1.500 | 18.0200 |
| 2-7/8" | 11    | 0.120     | 2.635 | 3.5310  | 3"      | 7/8   | 0.875     | 1.250 | 19.8600 |
| 2-7/8" | 1/8   | 0.125     | 2.625 | 3.6710  | 3"      | 1     | 1.000     | 1.000 | 21.3600 |
| 2-7/8" | 5/32  | 0.156     | 2.563 | 4.5300  |         |       |           |       |         |
| 2-7/8" | 7     | 0.180     | 2.515 | 5.1810  | 3-1/16" | 1/4   | 0.250     | 2.562 | 7.5110  |
| 2-7/8" | 3/16  | 0.187     | 2.500 | 5.3950  | 3-1/16" | 5/16  | 0.313     | 2.437 | 9.1930  |
| 2-7/8" | 7/32  | 0.219     | 2.437 | 6.2120  | 3-1/16" | 3/8   | 0.375     | 2.313 | 10.7700 |
| 2-7/8" | 1/4   | 0.250     | 2.375 | 7.0090  |         |       |           |       |         |
| 2-7/8" | 9/32  | 0.281     | 2.313 | 7.7850  | 3-1/8"  | 16    | 0.065     | 2.995 | 2.1240  |
| 2-7/8" | 5/16  | 0.313     | 2.250 | 8.5640  | 3-1/8"  | 13    | 0.095     | 2.935 | 3.0740  |
| 2-7/8" | 3/8   | 0.375     | 2.125 | 10.0100 | 3-1/8"  | 11    | 0.120     | 2.885 | 3.8510  |
| 2-7/8" | 7/16  | 0.438     | 2.001 | 11.4000 | 3-1/8"  | 1/8   | 0.125     | 2.875 | 4.0050  |
| 2-7/8" | 1/2   | 0.500     | 1.875 | 12.6800 | 3-1/8"  | 3/16  | 0.187     | 2.750 | 5.8970  |
| 2-7/8" | 9/16  | 0.563     | 1.751 | 13.9000 | 3-1/8"  | 7/32  | 0.219     | 2.687 | 6.7970  |
| 2-7/8" | 5/8   | 0.625     | 1.625 | 15.0200 | 3-1/8"  | 1/4   | 0.250     | 2.625 | 7.6760  |
| 2-7/8" | 3/4   | 0.750     | 1.375 | 17.0200 | 3-1/8"  | 5/16  | 0.313     | 2.500 | 9.4000  |
|        |       |           |       |         | 3-1/8"  | 3/8   | 0.375     | 2.375 | 11.0100 |
| 3"     | 18    | 0.049     | 2.902 | 1.5440  | 3-1/8"  | 7/16  | 0.438     | 2.250 | 12.5700 |
| 3"     | 16    | 0.065     | 2.870 | 2.0370  | 3-1/8"  | 1/2   | 0.500     | 2.125 | 14.0200 |
| 3"     | 14    | 0.083     | 2.834 | 2.5860  | 3-1/8"  | 9/16  | 0.563     | 2.000 | 15.4000 |
| 3"     | 13    | 0.095     | 2.810 | 2.9470  | 3-1/8"  | 5/8   | 0.625     | 1.875 | 16.6900 |
| 3"     | 12    | 0.109     | 2.782 | 3.3650  | 3-1/8"  | 3/4   | 0.750     | 1.625 | 19.0200 |
| 3"     | 11    | 0.120     | 2.760 | 3.6910  | 3-1/8"  | 7/8   | 0.875     | 1.375 | 21.0300 |
| 3"     | 1/8   | 0.125     | 2.750 | 3.8380  |         |       |           |       |         |
| 3"     | 10    | 0.134     | 2.732 | 4.1020  |         |       |           |       |         |
| 3"     | 5/32  | 0.156     | 2.687 | 4.7380  |         |       |           |       |         |
| 3"     | 7     | 0.180     | 2.640 | 5.4210  |         |       |           |       |         |
| 3"     | 3/16  | 0.187     | 2.625 | 5.6460  |         |       |           |       |         |
| 3"     | 7/32  | 0.219     | 2.562 | 6.5050  |         |       |           |       |         |



## Round Mechanical Tube

| O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT | O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT |
|--------|-------|-----------|-------|---------|--------|-------|-----------|-------|---------|
| 3-1/4" | 16    | 0.065     | 3.120 | 2.2110  | 3-1/2" | 18    | 0.049     | 3.402 | 1.8060  |
| 3-1/4" | 14    | 0.083     | 3.084 | 2.8070  | 3-1/2" | 16    | 0.065     | 3.370 | 2.3850  |
| 3-1/4" | 13    | 0.095     | 3.060 | 3.2010  | 3-1/2" | 14    | 0.083     | 3.334 | 3.0290  |
| 3-1/4" | 11    | 0.120     | 3.010 | 4.0110  | 3-1/2" | 13    | 0.095     | 3.310 | 3.4550  |
| 3-1/4" | 1/8   | 0.125     | 3.000 | 4.1720  | 3-1/2" | 11    | 0.120     | 3.260 | 4.3320  |
| 3-1/4" | 10    | 0.134     | 2.982 | 4.4590  | 3-1/2" | 1/8   | 0.125     | 3.250 | 4.5060  |
| 3-1/4" | 5/32  | 0.156     | 2.937 | 5.1550  | 3-1/2" | 10    | 0.134     | 3.232 | 4.8170  |
| 3-1/4" | 3/16  | 0.187     | 2.875 | 6.1480  | 3-1/2" | 5/32  | 0.156     | 3.188 | 5.5710  |
| 3-1/4" | 7/32  | 0.219     | 2.812 | 7.0890  | 3-1/2" | 7     | 0.180     | 3.140 | 6.3820  |
| 3-1/4" | 1/4   | 0.250     | 2.750 | 8.0100  | 3-1/2" | 3/16  | 0.187     | 3.125 | 6.6500  |
| 3-1/4" | 9/32  | 0.281     | 2.688 | 8.9100  | 3-1/2" | 7/32  | 0.219     | 3.062 | 7.6740  |
| 3-1/4" | 5/16  | 0.313     | 2.625 | 9.8180  | 3-1/2" | 1/4   | 0.250     | 3.000 | 8.6780  |
| 3-1/4" | 11/32 | 0.344     | 2.562 | 10.6800 | 3-1/2" | 9/32  | 0.281     | 2.938 | 9.6600  |
| 3-1/4" | 3/8   | 0.375     | 2.500 | 11.5100 | 3-1/2" | 5/16  | 0.313     | 2.875 | 10.6500 |
| 3-1/4" | 13/32 | 0.406     | 2.438 | 12.3300 | 3-1/2" | 11/32 | 0.344     | 2.812 | 11.5900 |
| 3-1/4" | 7/16  | 0.438     | 2.376 | 13.1500 | 3-1/2" | 3/8   | 0.375     | 2.750 | 12.5200 |
| 3-1/4" | 1/2   | 0.500     | 2.250 | 14.6900 | 3-1/2" | 7/16  | 0.438     | 2.626 | 14.3200 |
| 3-1/4" | 9/16  | 0.563     | 2.126 | 16.1600 | 3-1/2" | 1/2   | 0.500     | 2.500 | 16.0200 |
| 3-1/4" | 5/8   | 0.625     | 2.000 | 17.5200 | 3-1/2" | 9/16  | 0.563     | 2.374 | 17.6600 |
| 3-1/4" | 3/4   | 0.750     | 1.750 | 20.0300 | 3-1/2" | 5/8   | 0.625     | 2.250 | 19.1900 |
| 3-1/4" | 7/8   | 0.875     | 1.500 | 22.1900 | 3-1/2" | 3/4   | 0.750     | 2.000 | 22.0300 |
| 3-1/4" | 1     | 1.000     | 1.250 | 24.0300 | 3-1/2" | 7/8   | 0.875     | 1.750 | 24.5300 |
|        |       |           |       |         | 3-1/2" | 1     | 1.000     | 1.500 | 26.7000 |
| 3-3/8" | 11    | 0.120     | 3.135 | 4.1720  |        |       |           |       |         |
| 3-3/8" | 1/8   | 0.125     | 3.125 | 4.3390  | 3-5/8" | 16    | 0.065     | 3.495 | 2.4710  |
| 3-3/8" | 3/16  | 0.187     | 3.000 | 6.3990  | 3-5/8" | 11    | 0.120     | 3.385 | 4.4920  |
| 3-3/8" | 1/4   | 0.250     | 2.875 | 8.3440  | 3-5/8" | 3/16  | 0.187     | 3.250 | 6.9010  |
| 3-3/8" | 5/16  | 0.313     | 2.750 | 10.2400 | 3-5/8" | 1/4   | 0.250     | 3.125 | 9.0110  |
| 3-3/8" | 3/8   | 0.375     | 2.625 | 12.0200 | 3-5/8" | 9/32  | 0.281     | 3.063 | 10.0400 |
| 3-3/8" | 7/16  | 0.438     | 2.501 | 13.7400 | 3-5/8" | 5/16  | 0.313     | 3.000 | 11.0700 |
| 3-3/8" | 1/2   | 0.500     | 2.375 | 15.3500 | 3-5/8" | 3/8   | 0.375     | 2.875 | 13.0200 |
| 3-3/8" | 9/16  | 0.563     | 2.249 | 16.9100 | 3-5/8" | 7/16  | 0.438     | 2.750 | 14.9100 |
| 3-3/8" | 5/8   | 0.625     | 2.125 | 18.3600 | 3-5/8" | 1/2   | 0.500     | 2.625 | 16.6900 |
| 3-3/8" | 3/4   | 0.750     | 1.875 | 21.0300 | 3-5/8" | 9/16  | 0.563     | 2.499 | 18.4100 |
|        |       |           |       |         | 3-5/8" | 5/8   | 0.625     | 2.375 | 20.0300 |
|        |       |           |       |         | 3-5/8" | 3/4   | 0.750     | 2.125 | 23.0300 |

## Round Mechanical Tube

| O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT | O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT |
|--------|-------|-----------|-------|---------|--------|-------|-----------|-------|---------|
| 3-3/4" | 16    | 0.065     | 3.620 | 2.5580  | 4"     | 18    | 0.049     | 3.902 | 2.0680  |
| 3-3/4" | 13    | 0.095     | 3.560 | 3.7080  | 4"     | 16    | 0.065     | 3.870 | 2.7320  |
| 3-3/4" | 11    | 0.120     | 3.510 | 4.6520  | 4"     | 14    | 0.083     | 3.834 | 3.4750  |
| 3-3/4" | 1/8   | 0.125     | 3.500 | 4.8390  | 4"     | 13    | 0.095     | 3.810 | 3.9620  |
| 3-3/4" | 10    | 0.134     | 3.482 | 5.1750  | 4"     | 12    | 0.109     | 3.782 | 4.5300  |
| 3-3/4" | 5/32  | 0.156     | 3.437 | 5.9880  | 4"     | 11    | 0.120     | 3.760 | 3.9730  |
| 3-3/4" | 7     | 0.180     | 3.390 | 6.8630  | 4"     | 1/8   | 0.125     | 3.750 | 5.1730  |
| 3-3/4" | 3/16  | 0.187     | 3.375 | 7.1520  | 4"     | 10    | 0.134     | 3.732 | 5.5330  |
| 3-3/4" | 7/32  | 0.219     | 3.312 | 8.2590  | 4"     | 5/32  | 0.156     | 3.687 | 6.4040  |
| 3-3/4" | 1/4   | 0.250     | 3.250 | 9.3450  | 4"     | 7     | 0.180     | 3.640 | 7.3440  |
| 3-3/4" | 9/32  | 0.281     | 3.188 | 10.4100 | 4"     | 3/16  | 0.187     | 3.625 | 7.6540  |
| 3-3/4" | 5/16  | 0.313     | 3.125 | 11.4900 | 4"     | 7/32  | 0.219     | 3.562 | 8.8430  |
| 3-3/4" | 11/32 | 0.344     | 3.062 | 12.5100 | 4"     | 1/4   | 0.250     | 3.500 | 10.0100 |
| 3-3/4" | 3/8   | 0.375     | 3.000 | 13.5200 | 4"     | 9/32  | 0.281     | 3.438 | 11.1600 |
| 3-3/4" | 7/16  | 0.438     | 2.875 | 15.4900 | 4"     | 5/16  | 0.313     | 3.375 | 12.3300 |
| 3-3/4" | 1/2   | 0.500     | 2.750 | 17.3600 | 4"     | 3/8   | 0.375     | 3.250 | 14.5200 |
| 3-3/4" | 9/16  | 0.563     | 2.624 | 19.1600 | 4"     | 7/16  | 0.438     | 3.126 | 16.6600 |
| 3-3/4" | 5/8   | 0.625     | 2.500 | 20.8600 | 4"     | 1/2   | 0.500     | 3.000 | 18.6900 |
| 3-3/4" | 11/16 | 0.688     | 2.374 | 22.5000 | 4"     | 9/16  | 0.563     | 2.875 | 20.6700 |
| 3-3/4" | 3/4   | 0.750     | 2.250 | 24.0300 | 4"     | 5/8   | 0.625     | 2.750 | 22.5300 |
| 3-3/4" | 7/8   | 0.875     | 2.000 | 26.8700 | 4"     | 11/16 | 0.688     | 2.624 | 24.3400 |
| 3-3/4" | 1     | 1.000     | 1.750 | 29.3700 | 4"     | 3/4   | 0.750     | 2.500 | 26.0300 |
|        |       |           |       |         | 4"     | 7/8   | 0.875     | 2.250 | 29.2000 |
| 3-7/8" | 1/8   | 0.125     | 3.625 | 5.0060  | 4"     | 1     | 1.000     | 2.000 | 32.0400 |
| 3-7/8" | 3/16  | 0.187     | 3.500 | 7.4030  | 4"     | 1-1/8 | 1.125     | 1.750 | 34.5400 |
| 3-7/8" | 1/4   | 0.250     | 3.375 | 9.6790  | 4"     | 1-1/4 | 1.250     | 1.500 | 36.7100 |
| 3-7/8" | 5/16  | 0.313     | 3.249 | 11.9100 | 4-1/8" | 3/16  | 0.187     | 3.751 | 7.9050  |
| 3-7/8" | 3/8   | 0.375     | 3.125 | 14.0200 | 4-1/8" | 1/4   | 0.250     | 3.625 | 10.3500 |
| 3-7/8" | 7/16  | 0.438     | 3.000 | 16.0800 | 4-1/8" | 5/16  | 0.313     | 3.500 | 12.7400 |
| 3-7/8" | 1/2   | 0.500     | 2.875 | 18.0200 | 4-1/8" | 3/8   | 0.375     | 3.375 | 15.0200 |
| 3-7/8" | 9/16  | 0.563     | 2.750 | 19.9100 | 4-1/8" | 7/16  | 0.438     | 3.249 | 17.2500 |
| 3-7/8" | 5/8   | 0.625     | 2.625 | 21.6900 | 4-1/8" | 1/2   | 0.500     | 3.125 | 19.3600 |
| 3-7/8" | 3/4   | 0.750     | 2.375 | 25.0300 | 4-1/8" | 9/16  | 0.563     | 2.999 | 21.4200 |
|        |       |           |       |         | 4-1/8" | 5/8   | 0.625     | 2.875 | 23.3600 |

## Round Mechanical Tube

| O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT | O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT |
|--------|-------|-----------|-------|---------|--------|-------|-----------|-------|---------|
| 4-1/4" | 16    | 0.065     | 4.120 | 2.9050  | 4-1/2" | 3/16  | 0.187     | 4.125 | 8.6580  |
| 4-1/4" | 13    | 0.095     | 4.060 | 4.2160  | 4-1/2" | 7/32  | 0.219     | 4.062 | 10.0100 |
| 4-1/4" | 11    | 0.120     | 4.010 | 5.2930  | 4-1/2" | 1/4   | 0.250     | 4.000 | 11.3500 |
| 4-1/4" | 1/8   | 0.125     | 4.000 | 5.5070  | 4-1/2" | 9/32  | 0.281     | 3.938 | 12.6600 |
| 4-1/4" | 10    | 0.134     | 3.982 | 5.8900  | 4-1/2" | 5/16  | 0.313     | 3.875 | 14.000  |
| 4-1/4" | 5/32  | 0.156     | 3.937 | 6.8210  | 4-1/2" | 3/8   | 0.375     | 3.750 | 16.5200 |
| 4-1/4" | 3/16  | 0.187     | 3.875 | 8.1560  | 4-1/2" | 7/16  | 0.438     | 3.624 | 19.0000 |
| 4-1/4" | 1/4   | 0.250     | 3.750 | 10.6800 | 4-1/2" | 1/2   | 0.500     | 3.500 | 21.3600 |
| 4-1/4" | 5/16  | 0.313     | 3.625 | 13.1600 | 4-1/2" | 9/16  | 0.563     | 3.375 | 23.6700 |
| 4-1/4" | 11/32 | 0.344     | 3.562 | 14.3500 | 4-1/2" | 5/8   | 0.625     | 3.250 | 25.8700 |
| 4-1/4" | 3/8   | 0.375     | 3.500 | 15.5200 | 4-1/2" | 11/16 | 0.688     | 3.125 | 28.0100 |
| 4-1/4" | 7/16  | 0.438     | 3.375 | 17.8300 | 4-1/2" | 3/4   | 0.750     | 3.000 | 30.0400 |
| 4-1/4" | 1/2   | 0.500     | 3.250 | 20.0300 | 4-1/2" | 7/8   | 0.875     | 2.750 | 33.8800 |
| 4-1/4" | 9/16  | 0.563     | 3.125 | 22.1700 | 4-1/2" | 1     | 1.000     | 2.500 | 37.3800 |
| 4-1/4" | 5/8   | 0.625     | 3.000 | 24.2000 | 4-1/2" | 1-1/8 | 1.125     | 2.250 | 40.5500 |
| 4-1/4" | 11/16 | 0.688     | 2.874 | 26.1700 | 4-1/2" | 1-1/4 | 1.250     | 2.000 | 43.3900 |
| 4-1/4" | 3/4   | 0.750     | 2.750 | 28.0400 | 4-1/2" | 1-1/2 | 1.500     | 1.500 | 48.0600 |
| 4-1/4" | 7/8   | 0.875     | 2.500 | 31.5400 |        |       |           |       |         |
| 4-1/4" | 1     | 1.000     | 2.250 | 34.7100 | 4-5/8" | 3/16  | 0.187     | 4.251 | 8.9090  |
| 4-1/4" | 1-1/8 | 1.125     | 2.000 | 37.5500 | 4-5/8" | 1/4   | 0.250     | 4.125 | 11.6800 |
| 4-1/4" | 1-1/4 | 1.250     | 1.750 | 40.0500 | 4-5/8" | 5/16  | 0.313     | 3.999 | 14.4100 |
|        |       |           |       |         | 4-5/8" | 3/8   | 0.375     | 3.875 | 17.0200 |
| 4-3/8" | 3/16  | 0.187     | 4.001 | 8.4070  | 4-5/8" | 7/16  | 0.438     | 3.749 | 19.5900 |
| 4-3/8" | 1/4   | 0.250     | 3.875 | 11.0100 | 4-5/8" | 1/2   | 0.500     | 3.625 | 22.0300 |
| 4-3/8" | 5/16  | 0.313     | 3.749 | 13.5800 | 4-5/8" | 5/8   | 0.625     | 3.375 | 26.7000 |
| 4-3/8" | 3/8   | 0.375     | 3.625 | 16.0200 | 4-5/8" | 3/4   | 0.750     | 3.125 | 31.0400 |
| 4-3/8" | 7/16  | 0.438     | 3.500 | 18.4200 |        |       |           |       |         |
| 4-3/8" | 1/2   | 0.500     | 3.375 | 20.6900 | 4-3/4" | 16    | 0.065     | 4.620 | 3.2520  |
| 4-3/8" | 5/8   | 0.625     | 3.125 | 25.0300 | 4-3/4" | 11    | 0.120     | 4.510 | 5.9340  |
| 4-3/8" | 3/4   | 0.750     | 2.875 | 29.0400 | 4-3/4" | 1/8   | 0.125     | 4.500 | 6.1740  |
|        |       |           |       |         | 4-3/4" | 3/16  | 0.187     | 4.376 | 9.1600  |
| 4-1/2" | 16    | 0.065     | 4.370 | 3.0790  | 4-3/4" | 1/4   | 0.250     | 4.250 | 12.0200 |
| 4-1/2" | 14    | 0.083     | 4.334 | 3.9150  | 4-3/4" | 5/16  | 0.313     | 4.125 | 14.8300 |
| 4-1/2" | 13    | 0.095     | 4.310 | 4.4690  | 4-3/4" | 3/8   | 0.375     | 4.000 | 17.5200 |
| 4-1/2" | 11    | 0.120     | 4.260 | 5.6130  | 4-3/4" | 0.385 | 0.385     | 3.980 | 17.9500 |
| 4-1/2" | 1/8   | 0.125     | 4.250 | 5.8410  | 4-3/4" | 7/16  | 0.438     | 3.874 | 20.1700 |
| 4-1/2" | 10    | 0.134     | 4.232 | 6.2480  |        |       |           |       |         |
| 4-1/2" | 5/32  | 0.156     | 4.188 | 7.2370  |        |       |           |       |         |
| 4-1/2" | 7     | 0.180     | 4.140 | 8.3050  |        |       |           |       |         |

## Round Mechanical Tube

| O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT | O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT |
|--------|-------|-----------|-------|---------|--------|-------|-----------|-------|---------|
| 4-3/4" | 1/2   | 0.500     | 3.750 | 22.7000 | 5-1/4" | 11    | 0.120     | 5.010 | 6.5750  |
| 4-3/4" | 9/16  | 0.563     | 3.625 | 25.1800 | 5-1/4" | 1/8   | 0.125     | 5.000 | 6.8420  |
| 4-3/4" | 5/8   | 0.625     | 3.500 | 27.5300 | 5-1/4" | 3/16  | 0.187     | 4.875 | 10.1600 |
| 4-3/4" | 3/4   | 0.750     | 3.250 | 32.0400 | 5-1/4" | 1/4   | 0.250     | 4.750 | 13.3500 |
| 4-3/4" | 7/8   | 0.875     | 3.000 | 36.2100 | 5-1/4" | 5/16  | 0.313     | 4.625 | 16.5000 |
| 4-3/4" | 1     | 1.000     | 2.750 | 40.0500 | 5-1/4" | 3/8   | 0.375     | 4.500 | 19.5200 |
| 4-3/4" | 1-1/4 | 1.250     | 2.250 | 46.7300 | 5-1/4" | 1/2   | 0.500     | 4.250 | 25.3700 |
|        |       |           |       |         | 5-1/4" | 5/8   | 0.625     | 4.000 | 30.8700 |
| 4-7/8" | 3/16  | 0.188     | 4.499 | 9.4110  | 5-1/4" | 3/4   | 0.750     | 3.750 | 36.0500 |
| 4-7/8" | 1/4   | 0.250     | 4.375 | 12.3500 | 5-1/4" | 7/8   | 0.875     | 3.500 | 40.8800 |
| 4-7/8" | 3/8   | 0.375     | 4.125 | 18.0200 | 5-1/4" | 1     | 1.000     | 3.250 | 45.3900 |
| 4-7/8" | 7/16  | 0.438     | 3.999 | 20.7600 | 5-1/4" | 1-1/8 | 1.125     | 3.000 | 49.5600 |
| 4-7/8" | 1/2   | 0.500     | 3.875 | 23.3600 | 5-1/4" | 1-1/4 | 1.250     | 2.750 | 53.4000 |
| 4-7/8" | 3/4   | 0.750     | 3.375 | 33.0400 |        |       |           |       |         |
|        |       |           |       |         | 5-3/8" | 3/16  | 0.188     | 5.000 | 10.4100 |
| 5"     | 16    | 0.065     | 4.870 | 3.4260  | 5-3/8" | 1/4   | 0.250     | 4.875 | 13.6800 |
| 5"     | 14    | 0.083     | 4.834 | 4.3590  |        |       |           |       |         |
| 5"     | 11    | 0.120     | 4.760 | 6.2540  | 5-1/2" | 16    | 0.065     | 5.370 | 3.7730  |
| 5"     | 1/8   | 0.125     | 4.750 | 6.5080  | 5-1/2" | 11    | 0.120     | 5.260 | 6.8950  |
| 5"     | 5/32  | 0.156     | 4.687 | 8.0700  | 5-1/2" | 1/8   | 0.125     | 5.250 | 7.1760  |
| 5"     | 7     | 0.180     | 4.640 | 9.2660  | 5-1/2" | 3/16  | 0.187     | 5.125 | 10.6700 |
| 5"     | 3/16  | 0.187     | 4.625 | 9.6620  | 5-1/2" | 1/4   | 0.250     | 5.000 | 14.0200 |
| 5"     | 1/4   | 0.250     | 4.500 | 12.6800 | 5-1/2" | 5/16  | 0.313     | 4.875 | 17.3400 |
| 5"     | 5/16  | 0.313     | 4.375 | 15.6700 | 5-1/2" | 3/8   | 0.375     | 4.750 | 20.5300 |
| 5"     | 3/8   | 0.375     | 4.250 | 18.5200 | 5-1/2" | 7/16  | 0.438     | 4.624 | 23.6800 |
| 5"     | 7/16  | 0.438     | 4.125 | 21.3400 | 5-1/2" | 1/2   | 0.500     | 4.500 | 26.7000 |
| 5"     | 1/2   | 0.500     | 4.000 | 24.0300 | 5-1/2" | 5/8   | 0.625     | 4.250 | 32.5400 |
| 5"     | 9/16  | 0.563     | 3.876 | 26.6800 | 5-1/2" | 3/4   | 0.750     | 4.000 | 38.0500 |
| 5"     | 5/8   | 0.625     | 3.750 | 29.2000 | 5-1/2" | 7/8   | 0.875     | 3.750 | 43.2200 |
| 5"     | 3/4   | 0.750     | 3.500 | 34.0400 | 5-1/2" | 1     | 1.000     | 3.500 | 48.0600 |
| 5"     | 7/8   | 0.875     | 3.250 | 38.5500 | 5-1/2" | 1-1/4 | 1.250     | 3.000 | 56.7400 |
| 5"     | 1     | 1.000     | 3.000 | 42.7200 | 5-1/2" | 1-1/2 | 1.500     | 2.500 | 64.0800 |
| 5"     | 1-1/8 | 1.125     | 2.750 | 46.5600 |        |       |           |       |         |
| 5"     | 1-1/4 | 1.250     | 2.500 | 50.0600 | 5-5/8" | 5/16  | 0.313     | 5.001 | 17.7600 |
| 5"     | 1-1/2 | 1.500     | 2.000 | 56.0700 | 5-5/8" | 3/8   | 0.375     | 4.875 | 21.0300 |
|        |       |           |       |         | 5-5/8" | 1/2   | 0.500     | 4.623 | 27.3700 |
| 5-1/8" | 5/16  | 0.313     | 4.500 | 16.0900 | 5-5/8" | 5/8   | 0.625     | 4.375 | 33.3800 |
| 5-1/8" | 3/8   | 0.375     | 4.375 | 19.0200 |        |       |           |       |         |
| 5-1/8" | 1/2   | 0.500     | 4.125 | 24.7000 |        |       |           |       |         |
| 5-1/8" | 5/8   | 0.625     | 3.875 | 30.0400 |        |       |           |       |         |
| 5-1/8" | 1     | 1.000     | 3.125 | 44.0600 |        |       |           |       |         |

## Round Mechanical Tube

| O.D.   | G.A.  | Wall Dec. | I.D.  | WT / FT |
|--------|-------|-----------|-------|---------|
| 5-3/4" | 1/8   | 0.125     | 5.500 | 7.5100  |
| 5-3/4" | 3/16  | 0.187     | 5.375 | 11.1700 |
| 5-3/4" | 1/4   | 0.250     | 5.250 | 14.6900 |
| 5-3/4" | 5/16  | 0.313     | 5.125 | 18.1800 |
| 5-3/4" | 3/8   | 0.375     | 5.000 | 21.5300 |
| 5-3/4" | 1/2   | 0.500     | 4.750 | 28.0400 |
| 5-3/4" | 5/8   | 0.625     | 4.500 | 34.2100 |
| 5-3/4" | 3/4   | 0.750     | 4.250 | 40.0500 |
| 5-3/4" | 7/8   | 0.875     | 4.000 | 45.5600 |
| 5-3/4" | 1     | 1.000     | 3.750 | 50.7300 |
| 6"     | 16    | 0.065     | 5.870 | 4.1200  |
| 6"     | 14    | 0.083     | 5.834 | 5.2450  |
| 6"     | 11    | 0.120     | 5.760 | 7.5360  |
| 6"     | 1/8   | 0.125     | 5.750 | 7.8430  |
| 6"     | 10    | 0.134     | 5.732 | 8.3950  |
| 6"     | 7     | 0.180     | 5.640 | 11.1900 |
| 6"     | 3/16  | 0.187     | 5.625 | 11.6700 |
| 6"     | 1/4   | 0.250     | 5.500 | 15.3500 |
| 6"     | 5/16  | 0.313     | 5.374 | 19.0100 |
| 6"     | 3/8   | 0.375     | 5.250 | 22.5300 |
| 6"     | 7/16  | 0.438     | 5.125 | 26.0200 |
| 6"     | 1/2   | 0.500     | 5.000 | 29.3700 |
| 6"     | 9/16  | 0.562     | 4.876 | 32.6900 |
| 6"     | 5/8   | 0.625     | 4.750 | 35.8800 |
| 6"     | 3/4   | 0.750     | 4.500 | 42.0500 |
| 6"     | 7/8   | 0.875     | 4.250 | 47.8900 |
| 6"     | 1     | 1.000     | 4.000 | 53.4000 |
| 6"     | 1-1/4 | 1.250     | 3.500 | 63.4100 |
| 6"     | 1-1/2 | 1.500     | 3.000 | 72.0900 |

**Expanded Metal Flattened****ASTM 569 / 569 M Carbon Steel****Flattened**

| Style      | Size     | WT / SQ FT | WT / EA | Size of Openings<br>In Inches |       | Overall<br>Thickness<br>In Inches | Approx.<br>Open Area<br>(%) |
|------------|----------|------------|---------|-------------------------------|-------|-----------------------------------|-----------------------------|
|            |          |            |         | SWO                           | LWO   |                                   |                             |
| 1/4" #20   | 48 x 96  | 0.830      | 26.56   | 0.084                         | 0.715 | 0.030                             | 47                          |
| 1/2" #13   | 48 x 96  | 1.400      | 44.80   | 0.265                         | 1.00  | 0.070                             | 57                          |
| 1/2" #13   | 48 x 120 | 1.400      | 56.00   | 0.265                         | 1.00  | 0.070                             | 57                          |
| 1/2" #16   | 48 x 96  | 0.820      | 26.24   | 0.312                         | 1.00  | 0.050                             | 60                          |
| 1/2" #16   | 60 x 120 | 0.820      | 41.00   | 0.312                         | 1.00  | 0.050                             | 60                          |
| 1/2" #18   | 48 x 96  | 0.660      | 21.12   | 0.312                         | 1.00  | 0.039                             | 69                          |
| 1/2" #18   | 48 X 120 | 0.660      | 26.40   | 0.312                         | 1.00  | 0.039                             | 69                          |
| 3/4" #9    | 48 x 96  | 1.710      | 54.72   | 0.563                         | 1.688 | 0.120                             | 63                          |
| 3/4" #9    | 48 x 120 | 1.710      | 68.40   | 0.563                         | 1.688 | 0.120                             | 63                          |
| 3/4" #9    | 72 x 96  | 1.710      | 82.08   | 0.563                         | 1.688 | 0.120                             | 63                          |
| 3/4" #9    | 72 x 120 | 1.710      | 102.60  | 0.563                         | 1.688 | 0.120                             | 63                          |
| 3/4" #13   | 48 x 96  | 0.750      | 24.00   | 0.688                         | 1.781 | 0.070                             | 73                          |
| 3/4" #13   | 48 x 120 | 0.750      | 30.00   | 0.688                         | 1.781 | 0.070                             | 73                          |
| 3/4" #13   | 60 X 120 | 0.750      | 37.50   | 0.688                         | 1.781 | 0.070                             | 73                          |
| 3/4" #16   | 48 X 96  | 0.510      | 16.32   | 0.750                         | 1.750 | 0.048                             | 75                          |
| 3/4" #16   | 48 X 120 | 0.510      | 20.40   | 0.750                         | 1.750 | 0.048                             | 75                          |
| 1-1/2" #9  | 48 x 96  | 1.140      | 36.48   | 1.000                         | 2.563 | 0.110                             | 77                          |
| 1-1/2" #9  | 48 X 120 | 1.140      | 45.60   | 1.000                         | 2.563 | 0.110                             | 77                          |
| 1-1/2" #13 | 48 X 96  | 0.570      | 18.24   | 1.063                         | 2.750 | 0.070                             | 80                          |

**Flattened Expanded Metal**

First number – nominal width of diamond

Second number – Approximate gauge of sheet before flattening. Materials will measure slightly less than gauge designation due to this fact.

Width – The width of the sheet is measured parallel to the short way of the diamond (SWD).


Length – The length of the sheet is measured parallel to the long way of the diamond (LWD).

SWD = Short Way of Diamond

LWD = Long Way of Diamond

SWO = Short Way of Opening

LWO = Long Way of Opening



# Expanded Metal Standard

## ASTM 569 / 569 M Carbon Steel



### Standard

| Style      | Size     | WT / SQ FT | WT / EA | Size of Openings<br>In Inches |       | Overall<br>Thickness<br>In Inches | Approx.<br>Open Area<br>(%) |
|------------|----------|------------|---------|-------------------------------|-------|-----------------------------------|-----------------------------|
|            |          |            |         | SWO                           | LWO   |                                   |                             |
| 1/4" #20   | 48 x 96  | 0.860      | 27.52   | 0.125                         | 0.718 | 0.135                             | 45                          |
| 1/2" #13   | 48 x 96  | 1.470      | 47.04   | 0.312                         | 0.938 | 0.204                             | 58                          |
| 1/2" #13   | 48 x 120 | 1.470      | 58.80   | 0.312                         | 0.938 | 0.204                             | 58                          |
| 1/2" #16   | 48 x 96  | 0.860      | 27.52   | 0.375                         | 0.938 | 0.175                             | 71                          |
| 3/4" #9    | 48 x 96  | 1.800      | 57.60   | 0.688                         | 1.562 | 0.312                             | 66                          |
| 3/4" #9    | 48 x 120 | 1.800      | 72.00   | 0.688                         | 1.562 | 0.312                             | 66                          |
| 3/4" #9    | 60 x 120 | 1.800      | 90.00   | 0.688                         | 1.562 | 0.312                             | 66                          |
| 3/4" #9    | 72 x 120 | 1.800      | 108.00  | 0.688                         | 1.562 | 0.312                             | 66                          |
| 3/4" #13   | 48 x 96  | 0.800      | 25.60   | 0.750                         | 1.688 | 0.205                             | 78                          |
| 3/4" #13   | 48 x 120 | 0.800      | 32.00   | 0.750                         | 1.688 | 0.205                             | 78                          |
| 1-1/2" #6  | 48 x 96  | 2.500      | 80.00   | 1.110                         | 2.313 | 0.433                             | 63                          |
| 1-1/2" #9  | 48 x 96  | 1.200      | 38.40   | 1.125                         | 2.375 | 0.312                             | 75                          |
| 1-1/2" #9  | 48 x 120 | 1.200      | 48.00   | 1.125                         | 2.375 | 0.312                             | 75                          |
| 1-1/2" #13 | 72 x 120 | 0.600      | 36.00   | 1.188                         | 2.500 | 0.242                             | 86                          |
| 1-1/2" #16 | 48 x 96  | 0.400      | 12.80   | 1.250                         | 2.625 | 0.230                             | 89                          |

**Expanded Metal** – Expanded metal is available in two types – Standard (rough or raised surface) and Flattened (flat surface). Aside from its light weight, expanded metal has other advantages such as being open to let heat, air, and liquids through, as well as allowing visibility. Even though expanded metal is most commonly produced from carbon steel it is also available in aluminum, stainless, and hot dipped galvanized.

### Standard Expanded Metal


First Number = Nominal width of diamond in inches.

Second Number = Approximate gauge of sheet.


### When Ordering Expanded Metal Please Specify:

- (1) Number of sheets required
- (2) Nominal width of diamond (SWD)
- (3) Thickness or gauge of material
- (4) Standard or Flattened
- (5) Type of Metal: Carbon steel, stainless steel, galvanized, or aluminum
- (6) Size of sheet required, listing SWD first and then LWD. EXAMPLE: 4' SWD x 8' LWD

## Full Scale Drawings




1/2" #18 Flat




3/4" #16 Flat




1-1/2" #9 Flat




3/4" #13 Flat




1/2" #13 Std



3/4" #9 Std



1-1/2" #9 Std



1-1/2" #6 Std



## Grating



### Bar Grating

Non Serrated – Unpainted

| Style        | Size     | WT / SQ FT | WT / EA |
|--------------|----------|------------|---------|
| 3/16 x 1     | 24 x 240 | 7.100      | 284.00  |
| 3/16 x 1     | 36 x 240 | 7.100      | 426.00  |
| 3/16 x 1-1/2 | 24 x 240 | 10.300     | 412.00  |
| 3/16 x 1-1/2 | 36 x 240 | 10.300     | 618.00  |



### Bar Grating

Serrated – Unpainted

| Style        | Size     | WT / SQ FT | WT / EA |
|--------------|----------|------------|---------|
| 3/16 x 1-1/4 | 36 x 240 | 8.700      | 522.00  |



### Catwalk Grating


| Style | Size     | WT / SQ FT | WT / EA | Size of Openings<br>In Inches |       | Overall<br>Thickness<br>In Inches | Approx.<br>Open Area<br>(%) |
|-------|----------|------------|---------|-------------------------------|-------|-----------------------------------|-----------------------------|
|       |          |            |         | SWO                           | LWO   |                                   |                             |
| 3#    | 48 x 96  | 3.000      | 96.00   | 0.940                         | 3.440 | 0.540                             | 73                          |
| 3#    | 48 x 120 | 3.000      | 120.00  | 0.940                         | 3.440 | 0.540                             | 73                          |
| 3#    | 60 x 120 | 3.000      | 150.00  | 0.940                         | 3.440 | 0.540                             | 73                          |
| 3#    | 72 x 120 | 3.000      | 180.00  | 0.940                         | 3.440 | 0.540                             | 73                          |
| 4#    | 48 x 96  | 4.000      | 128.00  | 0.940                         | 3.440 | 0.618                             | 65                          |
| 4#    | 48 x 120 | 4.000      | 160.00  | 0.940                         | 3.440 | 0.618                             | 65                          |
| 4#    | 60 x 120 | 4.000      | 200.00  | 0.940                         | 3.440 | 0.618                             | 65                          |
| 6-1/4 | 48 x 96  | 6.250      | 200.00  | 0.813                         | 3.380 | 0.715                             | 55                          |
| 6-1/4 | 72 x 96  | 6.250      | 300.00  | 0.813                         | 3.380 | 0.715                             | 55                          |

SWD = Short Way of Diamond

LWD = Long Way of Diamond

SWO = Short Way of Opening

LWO = Long Way of Opening



## Galvanized Grip Strut — Plank (Legs go in)

| Catalog Number | Width In Inches | Channel Depth In Inches | Material Gauge | WT. LB. per Lin. Ft. | Length In Feet |
|----------------|-----------------|-------------------------|----------------|----------------------|----------------|
| 21512          | 4-3/4           | 1-1/2                   | 12 ga.         | 3.13                 | 12             |
| 22012          | 4-3/4           | 2                       | 12 ga.         | 3.49                 | 12             |
| 31514          | 7               | 1-1/2                   | 14 ga.         | 2.84                 | 12             |
| 32012          | 7               | 2                       | 12 ga.         | 4.61                 | 12             |
| 41514          | 9-1/2           | 1-1/2                   | 14 ga.         | 3.47                 | 12             |
| 41512          | 9-1/2           | 1-1/2                   | 12 ga.         | 4.88                 | 12             |
| 42014          | 9-1/2           | 2                       | 14 ga.         | 3.72                 | 12             |
| 42012          | 9-1/2           | 2                       | 12 ga.         | 5.24                 | 12             |
| 51514          | 11-3/4          | 1-1/2                   | 14 ga.         | 4.03                 | 12             |
| 51512          | 11-3/4          | 1-1/2                   | 12 ga.         | 5.72                 | 10             |
| 51512          | 11-3/4          | 1-1/2                   | 12 ga.         | 5.72                 | 12             |
| 52014          | 11-3/4          | 2                       | 14 ga.         | 4.30                 | 12             |
| 52012          | 11-3/4          | 2                       | 12 ga.         | 6.20                 | 10             |
| 52012          | 11-3/4          | 2                       | 12 ga.         | 6.20                 | 12             |
| 81514          | 18-3/4          | 1-1/2                   | 14 ga.         | 5.84                 | 10             |
| 82014          | 18-3/4          | 2                       | 14 ga.         | 6.10                 | 12             |
| 82012          | 18-3/4          | 2                       | 12 ga.         | 8.60                 | 12             |
| 102014         | 24              | 2                       | 14 ga.         | 7.40                 | 10             |
| 102012         | 24              | 2                       | 12 ga.         | 10.42                | 12             |
| 82010          | 36              | 2                       | 10 ga.         | 20.23                | 10             |


## H.R. P&O Grip Strut — Plank (Legs go down and in)

| Catalog Number | Width In Inches | Channel Depth In Inches | Material Gauge | WT. LB. per Lin. Ft. | Length In Feet |
|----------------|-----------------|-------------------------|----------------|----------------------|----------------|
| 41514-B        | 9-1/2           | 1-1/2                   | 14 ga.         | 3.58                 | 12             |
| 51512-B        | 11-3/4          | 1-1/2                   | 12 ga.         | 5.60                 | 12             |


## Galvanized Grip Strut — Walkway (Legs go up and out)

| Catalog Number | Width In Inches | Channel Depth In Inches | Material Gauge | WT. LB. per Lin. Ft. | Length In Feet |
|----------------|-----------------|-------------------------|----------------|----------------------|----------------|
| 104514-U       | 24              | 4-1/2                   | 14 ga.         | 8.80                 | 10             |
| 104512-U       | 24              | 4-1/2                   | 12 ga.         | 12.41                | 12             |

**Grip Strut Plank  
End View**



**Grip Strut Plank  
Top View**



## Stainless



### Stainless Channel

Type 304 Annealed and Pickled

| Size            | Length | WT / FT | WT / Bar |
|-----------------|--------|---------|----------|
| 3 x 1-1/2 x 1/4 | 20' rl | 4.750   | 95.00    |
| 4 x 1-3/4 x 1/4 | 20' rl | 6.690   | 133.80   |



### Stainless Squares

Type 304 Annealed Cold Drawn

| Size   | Length | WT / FT | WT / Bar |
|--------|--------|---------|----------|
| 1/4"   | 12' rl | 0.213   | 2.56     |
| 5/16"  | 12' rl | 0.332   | 3.98     |
| 3/8"   | 12' rl | 0.478   | 5.74     |
| 7/16"  | 12' rl | 0.651   | 7.81     |
| 1/2"   | 12' rl | 0.850   | 10.20    |
| 3/4"   | 12' rl | 1.913   | 22.96    |
| 1"     | 12' rl | 3.400   | 40.80    |
| 1-1/4" | 12' rl | 5.313   | 63.76    |
| 1-1/2" | 12' rl | 7.650   | 91.80    |



### Stainless Angles

Type 304 Hot Rolled / Annealed and Pickled

| Size                 | Length | WT / FT | WT / Bar |
|----------------------|--------|---------|----------|
| 3/4 x 3/4 x 1/8      | 20' rl | 0.590   | 11.80    |
| 1 x 1 x 1/8          | 20' rl | 0.800   | 16.00    |
| 1 x 1 x 3/16         | 20' rl | 1.160   | 23.20    |
| 1 x 1 x 1/4          | 20' rl | 1.490   | 29.80    |
| 1-1/4 x 1-1/4 x 1/8  | 20' rl | 1.010   | 20.20    |
| 1-1/4 x 1-1/4 x 3/16 | 20' rl | 1.480   | 29.60    |
| 1-1/4 x 1-1/4 x 1/4  | 20' rl | 1.920   | 38.40    |
| 1-1/2 x 1-1/2 x 1/8  | 20' rl | 1.230   | 24.60    |
| 1-1/2 x 1-1/2 x 3/16 | 20' rl | 1.800   | 36.00    |
| 1-1/2 x 1-1/2 x 1/4  | 20' rl | 2.340   | 46.80    |
| 2 x 2 x 1/8          | 20' rl | 1.650   | 33.00    |
| 2 x 2 x 3/16         | 20' rl | 2.440   | 48.80    |
| 2 x 2 x 1/4          | 20' rl | 3.190   | 63.80    |
| 2 x 2 x 3/8          | 20' rl | 4.700   | 94.00    |
| 2-1/2 x 2-1/2 x 3/16 | 20' rl | 3.070   | 61.40    |
| 2-1/2 x 2-1/2 x 1/4  | 20' rl | 4.100   | 82.00    |



### Stainless Angles

Type 304 Hot Rolled / Annealed and Pickled

| Size        | Length | WT / FT | WT / Bar |
|-------------|--------|---------|----------|
| 3 x 3 x 1/4 | 20' rl | 4.900   | 98.00    |
| 3 x 3 x 3/8 | 20' rl | 7.200   | 144.00   |
| 4 x 4 x 1/4 | 20' rl | 6.600   | 132.00   |



### Stainless Round

Type 304 Annealed

| Size     | Length | WT / FT | WT / Bar |
|----------|--------|---------|----------|
| 1/8"     | 12' rl | 0.042   | 0.50     |
| 3/16"    | 12' rl | 0.094   | 1.13     |
| 1/4"     | 12' rl | 0.167   | 2.00     |
| 5/16"    | 12' rl | 0.261   | 3.13     |
| 3/8"     | 12' rl | 0.376   | 4.51     |
| 7/16"    | 12' rl | 0.511   | 6.13     |
| 1/2"     | 12' rl | 0.668   | 8.02     |
| 5/8"     | 12' rl | 1.043   | 12.52    |
| 3/4"     | 12' rl | 1.502   | 18.02    |
| 7/8"     | 12' rl | 2.045   | 24.54    |
| 1"       | 12' rl | 2.670   | 32.04    |
| 1-1/8"   | 12' rl | 3.380   | 40.56    |
| 1-3/16"  | 12' rl | 3.766   | 45.19    |
| 1-1/4"   | 12' rl | 4.172   | 50.06    |
| 1-3/8"   | 12' rl | 5.050   | 60.60    |
| 1-7/16"  | 12' rl | 5.518   | 66.22    |
| 1-1/2"   | 12' rl | 6.008   | 72.10    |
| 1-5/8"   | 12' rl | 7.052   | 84.62    |
| 1-3/4"   | 12' rl | 8.178   | 98.14    |
| 1-15/16" | 12' rl | 10.020  | 120.24   |
| 2"       | 12' rl | 10.680  | 128.16   |
| 2-3/16"  | 12' rl | 12.780  | 153.36   |
| 2-1/4"   | 12' rl | 13.520  | 162.24   |
| 2-7/16"  | 12' rl | 15.870  | 190.44   |
| 2-1/2"   | 12' rl | 16.690  | 200.28   |
| 3"       | 12' rl | 24.030  | 288.36   |

# Stainless



## Stainless Strips

Type 304 Hot Rolled / Annealed and Pickled

| Size         | Length | WT / FT | WT / Bar |
|--------------|--------|---------|----------|
| 1/8 x 1/2    | 12'    | 0.213   | 2.56     |
| 1/8 x 3/4    | 12'    | 0.319   | 3.83     |
| 1/8 x 1      | 10'    | 0.425   | 4.25     |
| 1/8 x 1-1/4  | 10'    | 0.531   | 5.31     |
| 1/8 x 1-1/2  | 10'    | 0.638   | 6.38     |
| 1/8 x 2      | 10'    | 0.850   | 8.50     |
| 1/8 x 2-1/2  | 10'    | 1.063   | 10.63    |
| 1/8 x 3      | 10'    | 1.275   | 12.75    |
| 1/8 x 4      | 10'    | 1.700   | 17.00    |
| 1/8 x 5      | 10'    | 2.125   | 21.25    |
| 1/8 x 6      | 10'    | 2.550   | 25.50    |
|              |        |         |          |
| 3/16 x 1/2   | 12'    | 0.319   | 3.83     |
| 3/16 x 3/4   | 12'    | 0.536   | 6.43     |
| 3/16 x 1     | 10'    | 0.715   | 7.15     |
| 3/16 x 1-1/4 | 10'    | 0.893   | 8.93     |
| 3/16 x 1-1/2 | 10'    | 1.072   | 10.72    |
| 3/16 x 1-3/4 | 10'    | 1.251   | 12.51    |
| 3/16 x 2     | 10'    | 1.430   | 14.30    |
| 3/16 x 3     | 10'    | 2.140   | 21.40    |
| 3/16 x 3-1/2 | 10'    | 2.502   | 25.02    |
| 3/16 x 4     | 10'    | 2.860   | 28.60    |
| 3/16 x 6     | 10'    | 4.290   | 42.90    |



## Stainless Flats

Type 304 Hot Rolled / Annealed and Pickled

| Size        | Length | WT / FT | WT / Bar |
|-------------|--------|---------|----------|
| 3/8 x 3/4   | 12'    | 0.956   | 11.47    |
| 3/8 x 1     | 12'    | 1.380   | 16.56    |
| 3/8 x 1-1/4 | 12'    | 1.594   | 19.13    |
| 3/8 x 1-1/2 | 12'    | 2.060   | 24.72    |
| 3/8 x 2     | 12'    | 2.750   | 33.00    |
| 3/8 x 2-1/2 | 12'    | 3.438   | 41.26    |
| 3/8 x 3     | 12'    | 4.125   | 49.50    |
| 3/8 x 4     | 12'    | 5.500   | 66.00    |
| 3/8 x 5     | 12'    | 6.875   | 82.50    |
| 3/8 x 6     | 12'    | 8.250   | 99.00    |
|             |        |         |          |
| 1/2 x 3/4   | 12'    | 1.275   | 15.30    |
| 1/2 x 1     | 12'    | 1.800   | 21.60    |
| 1/2 x 1-1/2 | 12'    | 2.708   | 32.50    |
| 1/2 x 2     | 12'    | 3.610   | 43.32    |
| 1/2 x 2-1/2 | 12'    | 4.512   | 54.14    |
| 1/2 x 3     | 12'    | 5.420   | 65.04    |
| 1/2 x 4     | 12'    | 7.225   | 86.70    |
| 1/2 x 6     | 12'    | 10.830  | 129.96   |
|             |        |         |          |
| 3/4 x 2     | 12'    | 5.100   | 61.20    |
|             |        |         |          |
| 1-1/4 x 3   | 12'    | 12.760  | 153.12   |



## Stainless Flats

Type 304 Hot Rolled / Annealed and Pickled

| Size        | Length | WT / FT | WT / Bar |
|-------------|--------|---------|----------|
| 1/4 x 3/4   | 12'    | 0.638   | 7.66     |
| 1/4 x 1     | 10'    | 0.930   | 9.30     |
| 1/4 x 1-1/4 | 10'    | 1.163   | 11.63    |
| 1/4 x 1-1/2 | 10'    | 1.395   | 13.95    |
| 1/4 x 2     | 10'    | 1.860   | 18.60    |
| 1/4 x 2-1/2 | 10'    | 2.325   | 23.25    |
| 1/4 x 3     | 10'    | 2.791   | 27.91    |
| 1/4 x 4     | 10'    | 3.721   | 37.21    |
| 1/4 x 5     | 10'    | 4.651   | 46.51    |
| 1/4 x 6     | 10'    | 5.581   | 55.81    |

# Stainless Pipe

Type 304 Cold Finished / Annealed and Pickled



## Sch. 40

| Size   | Length | O.D.      | I.D.      | Wall      | WT / FT | WT / Bar |
|--------|--------|-----------|-----------|-----------|---------|----------|
|        |        | In Inches | In Inches | Thickness |         |          |
| 1/8"   | 20' rl | 0.405     | 0.269     | 0.068     | 0.240   | 4.80     |
| 1/4"   | 20' rl | 0.540     | 0.364     | 0.088     | 0.420   | 8.40     |
| 3/8"   | 20' rl | 0.675     | 0.493     | 0.091     | 0.568   | 11.36    |
| 1/2"   | 20' rl | 0.840     | 0.622     | 0.109     | 0.850   | 17.00    |
| 3/4"   | 20' rl | 1.050     | 0.824     | 0.113     | 1.130   | 22.60    |
| 1"     | 20' rl | 1.315     | 1.049     | 0.133     | 1.680   | 33.60    |
| 1-1/4" | 20' rl | 1.660     | 1.380     | 0.140     | 2.270   | 45.40    |
| 1-1/2" | 20' rl | 1.900     | 1.610     | 0.145     | 2.720   | 54.40    |
| 2"     | 20' rl | 2.375     | 2.067     | 0.154     | 3.650   | 73.00    |
| 2-1/2" | 20' rl | 2.875     | 2.469     | 0.203     | 5.800   | 116.00   |
| 3"     | 20' rl | 3.500     | 3.068     | 0.216     | 7.580   | 151.60   |
| 4"     | 20' rl | 4.500     | 4.026     | 0.237     | 10.790  | 215.80   |

## Stainless



### Stainless Square Tube

Mill Finish

| Size                   | Length | WT / FT | WT / Bar |
|------------------------|--------|---------|----------|
| 3/4 x 3/4 x 16 ga.     | 20' rl | 0.606   | 12.12    |
| 1 x 1 x 16 ga.         | 20' rl | 0.827   | 16.54    |
| 1 x 1 x 14 ga.         | 20' rl | 1.035   | 20.70    |
| 1 x 1 x 11 ga.         | 20' rl | 1.436   | 28.72    |
| 1-1/4 x 1-1/4 x 16 ga. | 20' rl | 1.048   | 20.96    |
| 1-1/4 x 1-1/4 x 14 ga. | 20' rl | 1.317   | 26.34    |
| 1-1/4 x 1-1/4 x 11 ga. | 20' rl | 1.844   | 36.88    |
| 1-1/2 x 1-1/2 x 16 ga. | 20' rl | 1.269   | 25.38    |
| 1-1/2 x 1-1/2 x 14 ga. | 20' rl | 1.600   | 32.00    |
| 1-1/2 x 1-1/2 x 11 ga. | 20' rl | 2.255   | 45.10    |
| 1-1/2 x 1-1/2 x 3/16   | 20' rl | 3.630   | 72.60    |
| 2 x 2 x 16 ga.         | 20' rl | 1.710   | 34.20    |
| 2 x 2 x 11 ga.         | 20' rl | 3.068   | 61.36    |
| 2 x 2 x 3/16           | 20' rl | 4.460   | 89.20    |
| 2 x 2 x 1/4            | 20' rl | 6.010   | 120.20   |
| 3 x 3 x 11 ga.         | 20' rl | 4.700   | 94.00    |
| 3 x 3 x 3/16           | 20' rl | 6.900   | 138.00   |
| 3 x 3 x 1/4            | 20' rl | 10.000  | 200.00   |
| 4 x 4 x 11 ga.         | 20' rl | 6.260   | 125.20   |
| 4 x 4 x 3/16           | 20' rl | 9.270   | 185.40   |
| 4 x 4 x 1/4            | 20' rl | 12.680  | 253.60   |



### Stainless Rectangular Tube

Mill Finish


| Size           | Length | WT / FT | WT / Bar |
|----------------|--------|---------|----------|
| 1 x 2 x 11 ga. | 20' rl | 2.252   | 45.04    |
| 2 x 3 x 11 ga. | 20' rl | 3.884   | 77.68    |
| 2 x 3 x 3/16   | 20' rl | 5.679   | 113.58   |
| 2 x 4 x 11 ga. | 20' rl | 4.700   | 94.00    |
| 2 x 4 x 3/16   | 20' rl | 6.900   | 138.00   |
| 2 x 4 x 1/4    | 20' rl | 10.000  | 200.00   |



### Square Tube

Polished Finish

| Size                   | Length | WT / FT | WT / Bar |
|------------------------|--------|---------|----------|
| 1 x 1 x 11 ga.         | 20' rl | 1.436   | 28.72    |
| 1-1/2 x 1-1/2 x 11 ga. | 20' rl | 2.255   | 45.10    |



### Stainless Expanded Metal

Type 304 – Flattened

| Style           | Size    | WT / FT | WT / Bar |
|-----------------|---------|---------|----------|
| 1/2 #13 FL SS   | 48 x 96 | 1.780   | 56.96    |
| 3/4 #13 FL SS   | 48 x 96 | 0.860   | 27.52    |
| 3/4 #9 FL SS    | 48 x 96 | 1.950   | 62.40    |
| 1-1/2 #13 FL SS | 48 x 96 | 0.650   | 20.80    |
| 1-1/2 #9 FL SS  | 48 x 96 | 1.310   | 41.92    |


## Stainless Sheets Type 304



### Stainless Sheets

No. 2B Finish

| Gauge  | Size     | WT / FT | WT / Sheet |
|--------|----------|---------|------------|
| 26 ga. | 48 x 120 | 0.756   | 30.24      |
| 24 ga. | 36 x 96  | 1.008   | 24.19      |
| 24 ga. | 48 x 96  | 1.008   | 32.26      |
| 24 ga. | 48 x 120 | 1.008   | 40.32      |
| 22 ga. | 36 x 96  | 1.260   | 30.24      |
| 22 ga. | 48 x 96  | 1.260   | 40.32      |
| 22 ga. | 48 x 120 | 1.260   | 50.40      |
| 20 ga. | 48 x 96  | 1.512   | 48.38      |
| 20 ga. | 48 x 120 | 1.512   | 60.48      |
| 18 ga. | 36 x 96  | 2.016   | 48.38      |
| 18 ga. | 48 x 96  | 2.016   | 64.51      |
| 18 ga. | 48 x 120 | 2.016   | 80.64      |
| 18 ga. | 60 x 120 | 2.016   | 100.80     |
| 16 ga. | 48 x 96  | 2.520   | 80.64      |
| 16 ga. | 48 x 120 | 2.520   | 100.80     |
| 16 ga. | 60 x 120 | 2.520   | 126.00     |
| 14 ga. | 36 x 96  | 3.150   | 75.60      |
| 14 ga. | 36 x 120 | 3.150   | 94.50      |
| 14 ga. | 48 x 96  | 3.150   | 100.80     |
| 14 ga. | 48 x 120 | 3.150   | 126.00     |
| 14 ga. | 60 x 96  | 3.150   | 126.00     |
| 14 ga. | 60 x 120 | 3.150   | 157.50     |
| 12 ga. | 36 x 120 | 4.410   | 132.30     |
| 12 ga. | 48 x 96  | 4.410   | 141.12     |
| 12 ga. | 48 x 120 | 4.410   | 176.40     |
| 12 ga. | 60 x 120 | 4.410   | 220.50     |
| 12 ga. | 60 x 144 | 4.410   | 264.60     |
| 11 ga. | 48 x 120 | 5.040   | 201.60     |



### Stainless Sheets

No. 2B Finish

| Gauge  | Size     | WT / FT | WT / Sheet |
|--------|----------|---------|------------|
| 10 ga. | 48 x 96  | 5.670   | 181.44     |
| 10 ga. | 48 x 120 | 5.670   | 226.80     |
| 10 ga. | 48 x 144 | 5.670   | 272.16     |
| 10 ga. | 60 x 96  | 5.670   | 226.80     |
| 10 ga. | 60 x 120 | 5.670   | 283.50     |
| 7 ga.  | 48 x 96  | 7.854   | 251.33     |
| 7 ga.  | 48 x 120 | 7.854   | 314.16     |
| 7 ga.  | 60 x 120 | 7.854   | 392.70     |



### Stainless Sheets

#4 Polish Sheets

| Gauge  | Size     | WT / FT | WT / Sheet |
|--------|----------|---------|------------|
| 24 ga. | 48 x 120 | 1.008   | 40.32      |
| 22 ga. | 48 x 120 | 1.260   | 50.40      |
| 20 ga. | 48 x 120 | 1.512   | 60.48      |
| 18 ga. | 48 x 120 | 2.016   | 80.64      |
| 16 ga. | 48 x 120 | 2.520   | 100.80     |
| 14 ga. | 36 x 120 | 3.150   | 94.50      |
| 14 ga. | 48 x 120 | 3.150   | 126.00     |
| 12 ga. | 48 x 120 | 4.410   | 176.40     |
| 12 ga. | 60 x 120 | 4.410   | 220.50     |



### Stainless Sheets

#1 Mill Finish

| Gauge  | Size     | WT / FT | WT / Sheet |
|--------|----------|---------|------------|
| 11 ga. | 48 x 120 | 5.040   | 201.60     |

#### Standard Stainless Finishes

- #1 – Hot rolled, annealed and pickled
- #2B – Annealed, pickled and bright cold rolled
- #4 – Standard polish – PVC coated

**Type 304** – Good formability, weldability and corrosion resistance. Widely used in food processing as well as in chemical corrosive environments.



## Stainless Plates

Hot Rolled, Annealed & Pickled

Type 304 #1 Mill Finish

| Thickness | Size         | WT / FT | WT / Sheet |
|-----------|--------------|---------|------------|
| 3/16" PL  | 48 x 96      | 8.579   | 274.53     |
| 3/16" PL  | 48 x 120     | 8.579   | 343.16     |
| 3/16" PL  | 48 x 144     | 8.579   | 411.79     |
| 3/16" PL  | 60 x 96      | 8.579   | 343.16     |
| 3/16" PL  | 60 x 120     | 8.579   | 428.95     |
| 3/16" PL  | 60 x 144     | 8.579   | 514.74     |
| 1/4" PL   | 48 x 96      | 11.162  | 357.18     |
| 1/4" PL   | 48 x 120     | 11.162  | 446.48     |
| 1/4" PL   | 48 x 144     | 11.162  | 535.78     |
| 1/4" PL   | 60 x 96      | 11.162  | 446.48     |
| 1/4" PL   | 60 x 120     | 11.162  | 558.10     |
| 1/4" PL   | 60 x 144     | 11.162  | 669.72     |
| 3/8" PL   | 48 x 96      | 16.500  | 528.00     |
| 3/8" PL   | 48 x 120     | 16.500  | 660.00     |
| 3/8" PL   | 48 x 144     | 16.500  | 792.00     |
| 3/8" PL   | 60 x 144     | 16.500  | 990.00     |
| 1/2" PL   | 48 x 120     | 21.660  | 866.40     |
| 1/2" PL   | 60 x 144     | 21.660  | 1299.60    |
| 1/2" PL   | 61-3/4 x 144 | 21.660  | 1337.51    |





## Aluminum

### Aluminum I Beams 6061-T6 AS

| Size            | Length | WT / FT | WT / Length |
|-----------------|--------|---------|-------------|
| 3 x 2.33 x 0.17 | 25'    | 1.963   | 49.08       |
| 4 x 2.66 x 0.19 | 25'    | 2.644   | 66.10       |
| 6 x 3.33 x 0.23 | 25'    | 4.302   | 107.55      |



### Aluminum Channel 6061-T6 AA

| Size              | Length | WT / FT | WT / Length |
|-------------------|--------|---------|-------------|
| 2 x 1 x 0.130     | 25'    | 0.577   | 14.43       |
| 2 x 1-1/4 x 0.170 | 25'    | 1.071   | 26.77       |
| 6 x 2-1/2 x 0.170 | 25'    | 2.834   | 70.85       |
| 10 x 3-1/2 x 0.25 | 25'    | 6.136   | 153.40      |



### Aluminum Channel 6061-T6 AS

| Size              | Length | WT / FT | WT / Length |
|-------------------|--------|---------|-------------|
| 3 x 1.410 x 0.170 | 25'    | 1.417   | 35.42       |
| 4 x 1.580 x 0.180 | 25'    | 1.846   | 46.15       |
| 4 x 1.720 x 0.320 | 25'    | 2.504   | 62.60       |
| 5 x 1.750 x 0.190 | 25'    | 2.316   | 57.90       |
| 5 x 1.885 x 0.325 | 25'    | 3.108   | 77.70       |
| 6 x 1.945 x 0.225 | 25'    | 3.002   | 75.05       |
| 8 x 2.290 x 0.250 | 25'    | 4.252   | 106.30      |



### Aluminum Angle 6061-T6

| Size                 | Length | WT / FT | WT / Length |
|----------------------|--------|---------|-------------|
| 3/4 x 3/4 x 1/8      | 25'    | 0.201   | 5.03        |
| 1 x 1 x 1/8          | 25'    | 0.275   | 6.88        |
| 1 x 1 x 3/16         | 25'    | 0.400   | 10.00       |
| 1 x 1 x 1/4          | 25'    | 0.514   | 12.85       |
| 1-1/4 x 1-1/4 x 1/8  | 25'    | 0.343   | 8.57        |
| 1-1/4 x 1-1/4 x 3/16 | 25'    | 0.510   | 12.75       |
| 1-1/4 x 1-1/4 x 1/4  | 25'    | 0.656   | 16.40       |
| 1-1/2 x 1-1/2 x 1/8  | 25'    | 0.423   | 10.57       |
| 1-1/2 x 1-1/2 x 3/16 | 25'    | 0.619   | 15.47       |
| 1-1/2 x 1-1/2 x 1/4  | 25'    | 0.809   | 20.23       |



### Aluminum Angle 6061-T6

| Size                 | Length | WT / FT | WT / Length |
|----------------------|--------|---------|-------------|
| 1-3/4 x 1-3/4 x 1/8  | 25'    | 0.497   | 12.43       |
| 1-3/4 x 1-3/4 x 3/16 | 25'    | 0.731   | 18.27       |
| 1-3/4 x 1-3/4 x 1/4  | 25'    | 0.956   | 23.90       |
| 2 x 2 x 1/8          | 25'    | 0.577   | 14.43       |
| 2 x 2 x 3/16         | 25'    | 0.850   | 21.25       |
| 2 x 2 x 1/4          | 25'    | 1.110   | 27.75       |
| 2 x 2 x 3/8          | 25'    | 1.606   | 40.15       |
| 2-1/2 x 2-1/2 x 1/4  | 25'    | 1.404   | 35.10       |
| 2-1/2 x 2-1/2 x 3/8  | 25'    | 2.047   | 51.17       |
| 3 x 2 x 3/16         | 25'    | 1.071   | 26.77       |
| 3 x 2 x 1/4          | 25'    | 1.403   | 35.08       |
| 3 x 3 x 1/4          | 25'    | 1.684   | 42.10       |
| 3 x 3 x 3/8          | 25'    | 2.474   | 61.85       |
| 3-1/2 x 3-1/2 x 1/4  | 25'    | 1.989   | 49.73       |
| 3-1/2 x 3-1/2 x 3/8  | 25'    | 2.926   | 73.15       |
| 4 x 4 x 1/4          | 25'    | 2.283   | 57.08       |
| 4 x 4 x 3/8          | 25'    | 3.366   | 84.15       |

**I Beams** – The edges of the flanges of I beams are tapered in for added strength. They generally are not used for structural purposes, but instead are used for hoists and cranes.

**6061** – Very corrosion resistant – strength, formability and machinability are still good.

## Aluminum



### Aluminum Rounds 6061-T6

| Size   | Length | WT / FT | WT / Length |
|--------|--------|---------|-------------|
| 1/8"   | 12'    | 0.014   | 0.17        |
| 1/4"   | 12'    | 0.058   | 0.70        |
| 5/16"  | 12'    | 0.090   | 1.08        |
| 3/8"   | 12'    | 0.130   | 1.56        |
| 1/2"   | 12'    | 0.231   | 2.77        |
| 5/8"   | 12'    | 0.361   | 4.33        |
| 7/8"   | 12'    | 0.707   | 8.48        |
| 3/4"   | 12'    | 0.520   | 6.24        |
| 1"     | 12'    | 0.924   | 11.09       |
| 1-1/4" | 12'    | 1.443   | 17.32       |
| 1-3/8" | 12'    | 1.746   | 20.95       |
| 1-1/2" | 12'    | 2.078   | 24.94       |
| 1-3/4" | 12'    | 2.829   | 33.95       |
| 2"     | 12'    | 3.695   | 44.34       |
| 2-1/2" | 12'    | 5.773   | 69.28       |
| 2-3/4" | 12'    | 6.985   | 83.82       |
| 3"     | 12'    | 8.313   | 99.76       |
| 3-1/2" | 12'    | 11.315  | 135.78      |



### Aluminum Square 6061-T6

| Size   | Length | WT / FT | WT / Length |
|--------|--------|---------|-------------|
| 1/2"   | 12'    | 0.294   | 3.53        |
| 3/4"   | 12'    | 0.662   | 7.94        |
| 1"     | 12'    | 1.176   | 14.11       |
| 1-1/4" | 12'    | 1.838   | 22.06       |
| 1-1/2" | 12'    | 2.646   | 31.75       |
| 2"     | 12'    | 4.704   | 56.45       |



### Aluminum Square Tube 6063-T52

| Size                  | Length | WT / FT | WT / Length |
|-----------------------|--------|---------|-------------|
| 3/4 x 3/4 x 0.062     | 21'1"  | 0.199   | 4.20        |
| 3/4 x 3/4 x 0.125     | 21'1"  | 0.364   | 7.67        |
| 1 x 1 x 0.062         | 21'1"  | 0.271   | 5.71        |
| 1 x 1 x 0.125         | 21'1"  | 0.509   | 10.73       |
| 1-1/4 x 1-1/4 x 0.125 | 21'1"  | 0.655   | 13.81       |
| 1-1/2 x 1-1/2 x 0.125 | 21'1"  | 0.800   | 16.87       |
| 2 x 2 x 0.125         | 21'1"  | 1.091   | 23.00       |
| 3 x 3 x 0.125         | 21'1"  | 1.673   | 35.27       |
| 4 x 4 x 0.125         | 21'1"  | 2.255   | 47.54       |



### Aluminum Rectangle Tube 6063-T52

| Size              | Length | WT / FT | WT / Length |
|-------------------|--------|---------|-------------|
| 1 x 2 x 0.125     | 21'1"  | 0.800   | 16.87       |
| 1-1/2 x 2 x 0.125 | 21'1"  | 0.946   | 19.94       |
| 2 x 3 x 0.125     | 21'1"  | 1.382   | 29.14       |
| 2 x 4 x 0.125     | 21'1"  | 1.673   | 35.27       |



### Aluminum Expanded Metal Flattened

| Style      | Length  | WT / FT | WT / Length |
|------------|---------|---------|-------------|
| 3/4" 0.125 | 48 x 96 | 0.656   | 20.99       |



### Aluminum Expanded Metal Standard

| Style        | Length  | WT / FT | WT / Length |
|--------------|---------|---------|-------------|
| 1-1/2" 0.125 | 48 x 96 | 0.430   | 13.76       |

**6063** – Highly corrosion resistant with good weldability and machinability. Excellent finish and is suitable for anodizing. Commonly used for architectural and ornamental applications. Conforms to ASTM B-211 and QQ-A200/9.

# Aluminum



## Aluminum Flats 6061-T6

| Size         | Length | WT / FT | WT / Length |
|--------------|--------|---------|-------------|
| 1/8 x 3/4    | 12'    | 0.109   | 1.31        |
| 1/8 x 1      | 12'    | 0.146   | 1.75        |
| 1/8 x 1-1/2  | 12'    | 0.221   | 2.65        |
| 1/8 x 2      | 12'    | 0.294   | 3.53        |
| 3/16 x 1     | 12'    | 0.221   | 2.65        |
| 3/16 x 1-1/4 | 12'    | 0.276   | 3.31        |
| 3/16 x 1-1/2 | 12'    | 0.331   | 3.97        |
| 3/16 x 2     | 12'    | 0.441   | 5.29        |
| 3/16 x 3     | 12'    | 0.662   | 7.94        |
| 3/16 x 4     | 12'    | 0.882   | 10.58       |
| 1/4 x 1/2    | 12'    | 0.147   | 1.76        |
| 1/4 x 3/4    | 12'    | 0.221   | 2.65        |
| 1/4 x 1      | 12'    | 0.294   | 3.53        |
| 1/4 x 1-1/4  | 12'    | 0.368   | 4.42        |
| 1/4 x 1-1/2  | 12'    | 0.441   | 5.29        |
| 1-1/4 x 2    | 12'    | 0.588   | 7.06        |
| 1/4 x 2-1/2  | 12'    | 0.735   | 8.82        |
| 1/4 x 3      | 12'    | 0.882   | 10.58       |
| 1/4 x 4      | 12'    | 1.176   | 14.11       |
| 1/4 x 5      | 12'    | 1.470   | 17.64       |
| 1/4 x 6      | 12'    | 1.764   | 21.17       |
| 5/16 x 1-1/2 | 12'    | 0.551   | 6.61        |
| 3/8 x 1      | 12'    | 0.441   | 5.29        |
| 3/8 x 1-1/4  | 12'    | 0.551   | 6.61        |
| 3/8 x 1-1/2  | 12'    | 0.662   | 7.94        |
| 3/8 x 2      | 12'    | 0.882   | 10.58       |
| 3/8 x 2-1/2  | 12'    | 1.103   | 13.24       |
| 3/8 x 3      | 12'    | 1.323   | 15.88       |
| 3/8 x 4      | 12'    | 1.764   | 21.17       |
| 3/8 x 6      | 12'    | 2.646   | 31.75       |



## Aluminum Flats 6061-T6

| Size        | Length | WT / FT | WT / Length |
|-------------|--------|---------|-------------|
| 1/2 x 3/4   | 12'    | 0.441   | 5.29        |
| 1/2 x 1     | 12'    | 0.588   | 7.06        |
| 1/2 x 1-1/2 | 12'    | 0.882   | 10.58       |
| 1/2 x 2     | 12'    | 1.176   | 14.11       |
| 1/2 x 2-1/2 | 12'    | 1.470   | 17.64       |
| 1/2 x 3     | 12'    | 1.764   | 21.17       |
| 1/2 x 3-1/2 | 12'    | 2.056   | 24.67       |
| 1/2 x 4     | 12'    | 2.352   | 28.22       |
| 1/2 x 4-1/2 | 12'    | 2.640   | 31.68       |
| 1/2 x 5     | 12'    | 2.940   | 35.28       |
| 1/2 x 6     | 12'    | 3.528   | 42.34       |
| 5/8 x 1     | 12'    | 0.735   | 8.82        |
| 3/4 x 1     | 12'    | 0.882   | 10.58       |
| 3/4 x 1-1/2 | 12'    | 1.323   | 15.88       |
| 3/4 x 2     | 12'    | 1.764   | 21.17       |
| 3/4 x 2-1/2 | 12'    | 2.205   | 26.46       |
| 3/4 x 3     | 12'    | 2.646   | 31.75       |
| 3/4 x 4     | 12'    | 3.528   | 42.34       |
| 3/4 x 5     | 12'    | 4.406   | 52.87       |
| 1 x 1-1/4   | 12'    | 1.470   | 17.64       |
| 1 x 1-1/2   | 12'    | 1.764   | 21.17       |
| 1 x 2       | 12'    | 2.352   | 28.22       |
| 1 x 3       | 12'    | 3.528   | 42.34       |
| 1 x 4       | 12'    | 4.704   | 56.45       |
| 1 x 6       | 12'    | 7.056   | 84.67       |
| 1-1/2 x 2   | 12'    | 3.528   | 42.34       |

## Aluminum Pipe



**Sch. 40 6061-T6**

| Size   | Length | O.D.      | I.D.      | Wall      | WT / FT | WT / Bar |
|--------|--------|-----------|-----------|-----------|---------|----------|
|        |        | In Inches | In Inches | Thickness |         |          |
| 3/8"   | 12'    | 0.675     | 0.493     | 0.091     | 0.196   | 2.35     |
| 1/2"   | 20'    | 0.840     | 0.622     | 0.109     | 0.294   | 5.88     |
| 3/4"   | 20'    | 1.050     | 0.824     | 0.113     | 0.391   | 7.82     |
| 1"     | 20'    | 1.315     | 1.049     | 0.133     | 0.581   | 11.62    |
| 1-1/4" | 20'    | 1.660     | 1.380     | 0.140     | 0.786   | 15.72    |
| 1-1/2" | 20'    | 1.900     | 1.610     | 0.145     | 0.940   | 18.80    |
| 2"     | 20'    | 2.375     | 2.067     | 0.154     | 1.264   | 25.28    |



**Sch. 10 6063-T6**

| Size | Length | O.D.      | I.D.      | Wall      | WT / FT | WT / Bar |
|------|--------|-----------|-----------|-----------|---------|----------|
|      |        | In Inches | In Inches | Thickness |         |          |
| 3"   | 20'    | 3.500     | 3.260     | 0.120     | 1.483   | 29.66    |
| 4"   | 20'    | 4.500     | 4.260     | 0.120     | 1.922   | 38.44    |

### Aluminum Alloy Descriptions

#### Sheet and Plate Typical Temper Designations

**F = As Fabricated      O = Annealed      H = Strained Hardened**

The letter H is always followed by two digits. The first digit indicates the particular method used to obtain the temper. Examples are as follows:

- H1 = Strained hardened only.
- H2 = Strained hardened, then partially annealed.
- H3 = Strained hardened, then stabilized.

The temper is indicated by the second digit. Examples include:

- H x 2 = 1/4 Hard
- H x 4 = 1/2 Hard
- H x 6 = 3/4 Hard
- H x 8 = Full hard
- H x 9 = Extra Hard

T = Heat treated.

T5 = Artificially aged only.


T6 = Solution heat treated, then artificially aged.

T651 = Solution heat treated, stretcher stress relieved, artificially aged.

#### Aluminum Mechanical Properties

|      |      | <u>Tensile (psi)</u> | <u>Yield (psi)</u> |
|------|------|----------------------|--------------------|
| 3003 |      | 16,000               | 6,000              |
| 3003 | H14  | 22,000               | 21,000             |
| 5052 | H32  | 33,000               | 28,000             |
| 6061 | T6   | 45,000               | 40,000             |
| 6061 | T651 | 45,000               | 40,000             |
| 6063 | T5   | 27,000               | 21,000             |

## Aluminum



### Aluminum Plates 5052-H32

| Decimal | Size     | WT / FT | WT / Sheet |
|---------|----------|---------|------------|
| 0.250   | 48 x 96  | 3.492   | 111.74     |
| 0.250   | 48 x 120 | 3.492   | 139.68     |
| 0.250   | 48 x 144 | 3.492   | 167.62     |
| 0.250   | 60 x 120 | 3.492   | 174.60     |
| 0.250   | 60 x 144 | 3.492   | 209.52     |
| 0.375   | 48 X 144 | 5.238   | 251.42     |



### Aluminum Plates 6061-T651

| Decimal | Size             | WT / FT | WT / Sheet |
|---------|------------------|---------|------------|
| 0.250   | 48-1/2 x 144-1/2 | 3.528   | 171.70     |
| 0.250   | 60 x 144         | 3.528   | 211.68     |
| 0.375   | 48-1/2 x 144-1/2 | 5.292   | 257.55     |
| 0.500   | 48-1/2 x 144-1/2 | 7.056   | 343.40     |



### Aluminum Sheets 5052-H32

| Decimal | Size     | WT / SQ FT | WT / Sheet |
|---------|----------|------------|------------|
| 0.0320  | 48 x 120 | 0.447      | 14.30      |
| 0.0625  | 48 x 96  | 0.880      | 28.16      |
| 0.090   | 48 x 120 | 1.257      | 50.28      |
| 0.100   | 48 x 120 | 1.397      | 55.88      |
| 0.125   | 48 x 96  | 1.746      | 55.87      |
| 0.125   | 48 x 120 | 1.746      | 69.84      |
| 0.125   | 48 x 144 | 1.746      | 83.81      |
| 0.125   | 60 x 120 | 1.746      | 87.30      |
| 0.125   | 60 x 144 | 1.746      | 104.76     |
| 0.190   | 36 x 120 | 2.654      | 79.62      |
| 0.190   | 48 x 120 | 2.654      | 106.16     |
| 0.190   | 60 x 120 | 2.654      | 132.70     |




### Aluminum Sheets 3003-H14

| Decimal | Size     | WT / SQ FT | WT / Sheet |
|---------|----------|------------|------------|
| 0.025   | 48 x 120 | 0.356      | 14.24      |
| 0.032   | 48 x 96  | 0.456      | 14.59      |
| 0.032   | 48 x 120 | 0.456      | 18.24      |
| 0.040   | 48 x 120 | 0.570      | 22.80      |
| 0.050   | 48 x 96  | 0.713      | 22.82      |
| 0.050   | 48 x 120 | 0.713      | 28.52      |
| 0.0625  | 48 x 96  | 0.898      | 28.74      |
| 0.0625  | 48 x 120 | 0.898      | 35.92      |
| 0.0625  | 60 x 96  | 0.898      | 35.92      |
| 0.0625  | 60 x 120 | 0.898      | 44.90      |
| 0.080   | 48 x 96  | 1.141      | 36.51      |
| 0.080   | 48 x 120 | 1.141      | 45.64      |
| 0.080   | 60 x 120 | 1.141      | 57.05      |
| 0.090   | 48 x 96  | 1.283      | 41.06      |
| 0.090   | 48 x 120 | 1.283      | 51.32      |
| 0.100   | 48 x 96  | 1.426      | 45.63      |
| 0.100   | 48 x 120 | 1.426      | 57.04      |
| 0.125   | 48 x 120 | 1.782      | 71.28      |
| 0.125   | 60 x 120 | 1.782      | 89.10      |
| 0.125   | 60 x 144 | 1.782      | 106.92     |
| 0.190   | 48 x 120 | 2.709      | 108.36     |
| 0.190   | 60 x 120 | 2.709      | 135.45     |

**Non-Heat Treatable Alloys – Grade 3003** – This alloy is the most commonly used of all. It is commercially pure aluminum with 1.2% manganese added which provides a tensile strength range of 17,000 psi to 30,000 psi. The workability and corrosion resistance of this non-heat-treatable alloy are excellent. It may be welded, brazed, deep drawn, or spun. Some of its common uses are for kitchen equipment and utensils, siding, awnings, chemical equipment and storage tanks. Conforms to ASTM-B209.

**Grade 5052** – This grade is the highest strength alloy of the more ordinary non-heat-treatable grades. It has a higher fatigue strength than most aluminum alloys. It can withstand marine atmospheres and salt water corrosion especially well. Its workability is excellent and can be drawn or formed into elaborate shapes. Tensile strength range of 31,000 psi to 44,000 psi is higher than grade 3003 and is alloyed with 2.5% magnesium. Some common uses are aircraft modules, home appliances, and high-strength kitchen utensils. Conforms to ASTM-B209.



## Aluminum Plates 3003-H14

| Decimal | Size     | WT / SQ FT | WT / Sheet |
|---------|----------|------------|------------|
| 0.250   | 48 x 96  | 3.564      | 114.05     |
| 0.250   | 48 x 120 | 3.564      | 142.56     |



## Aluminum Sheet Color/Painted

### White on White GPSH14

| Decimal | Size     | WT / SQ FT | WT / Sheet |
|---------|----------|------------|------------|
| 0.040   | 48 x 96  | 0.585      | 18.72      |
| 0.040   | 48 x 120 | 0.585      | 23.40      |
| 0.040   | 49 x 144 | 0.585      | 28.66      |



### White / Black Coat GPSH14BL

| Decimal | Size     | WT / SQ FT | WT / Sheet |
|---------|----------|------------|------------|
| 0.040   | 48 x 96  | 0.585      | 18.72      |
| 0.040   | 48 X 144 | 0.585      | 28.08      |



### Bronze GPSH14B

| Decimal | Size     | WT / SQ FT | WT / Sheet |
|---------|----------|------------|------------|
| 0.040   | 48 X 96  | 0.585      | 18.72      |
| 0.040   | 48 X 120 | 0.585      | 23.40      |

## Aluminum Diamond Tread Plate



### 3003 H22 Bright Finish

| Decimal | Size     | WT / SQ FT | WT / Sheet |
|---------|----------|------------|------------|
| 0.0625  | 48 X 96  | 1.009      | 32.29      |
| 0.1000  | 48 X 192 | 1.570      | 100.48     |
| 0.125   | 48 X 96  | 1.925      | 61.60      |
| 0.125   | 48 X 120 | 1.925      | 77.00      |
| 0.125   | 48 X 192 | 1.925      | 123.20     |
| 0.125   | 60 X 96  | 1.925      | 77.00      |
| 0.125   | 60 X 192 | 1.925      | 154.00     |
| 0.1875  | 48 X 96  | 2.823      | 90.34      |
| 0.1875  | 48 X 120 | 2.823      | 112.92     |
| 0.1875  | 48 X 192 | 2.823      | 180.67     |
| 0.1875  | 60 X 144 | 2.823      | 169.38     |
| 0.1875  | 60 X 192 | 2.823      | 225.84     |



### Aluminum Diamond Tread Plate 6061 T6 Mill Finish

| Decimal | Size     | WT / SQ FT | WT / Sheet |
|---------|----------|------------|------------|
| 0.250   | 48 x 96  | 3.669      | 117.41     |
| 0.250   | 48 x 192 | 3.669      | 234.82     |
| 0.250   | 60 x 96  | 3.669      | 146.76     |
| 0.250   | 60 x 192 | 3.669      | 293.52     |
| 0.375   | 48 x 96  | 5.443      | 174.18     |
| 0.375   | 48 x 192 | 5.443      | 348.35     |

## Heat-Treatable Alloys

Grade 6061 – This is the most adaptable of the heat-treatable aluminum alloys. 6061 is mostly used for structural applications. It has the majority of the good properties of aluminum and it extends a wide span of mechanical characteristics and corrosion resistance. It is weldable by all methods. Some common uses are truck frames, boat trailers and machine parts. Conforms to ASTM-B209.

## Decimal Conversion Table

| Fraction of Inch | Decimal of Inch | Millimeters |
|------------------|-----------------|-------------|
| 1/64             | 0.0156          | 0.397       |
| 1/32             | 0.0313          | 0.794       |
| 3/64             | 0.0469          | 1.191       |
| 1/16             | 0.0625          | 1.588       |
|                  |                 |             |
| 5/64             | 0.0781          | 1.984       |
| 3/32             | 0.0938          | 2.381       |
| 7/64             | 0.1094          | 2.778       |
| 1/8              | 0.1250          | 3.175       |
|                  |                 |             |
| 9/64             | 0.1406          | 3.572       |
| 5/32             | 0.1562          | 3.969       |
| 11/64            | 0.1719          | 4.366       |
| 3/16             | 0.1875          | 4.763       |
|                  |                 |             |
| 13/64            | 0.2031          | 5.159       |
| 7/32             | 0.2188          | 5.556       |
| 15/64            | 0.2344          | 5.953       |
| 1/4              | 0.2500          | 6.350       |
|                  |                 |             |
| 17/64            | 0.2656          | 6.747       |
| 9/32             | 0.2813          | 7.144       |
| 19/64            | 0.2969          | 7.541       |
| 5/16             | 0.3125          | 7.938       |
|                  |                 |             |
| 21/64            | 0.3281          | 8.334       |
| 11/32            | 0.3438          | 8.731       |
| 23/64            | 0.3594          | 9.128       |
| 3/8              | 0.3750          | 9.525       |
|                  |                 |             |
| 25/64            | 0.3906          | 9.922       |
| 13/32            | 0.4063          | 10.319      |
| 27/64            | 0.4219          | 10.716      |
| 7/16             | 0.4375          | 11.113      |
|                  |                 |             |
| 29/64            | 0.4531          | 11.509      |
| 15/32            | 0.4688          | 11.906      |
| 31/64            | 0.4844          | 12.303      |
| 1/2              | 0.5000          | 12.700      |

| Fraction of Inch | Decimal of Inch | Millimeters |
|------------------|-----------------|-------------|
| 33/64            | 0.5156          | 13.097      |
| 17/32            | 0.5313          | 13.494      |
| 35/64            | 0.5469          | 13.891      |
| 9/16             | 0.5625          | 14.288      |
|                  |                 |             |
| 37/64            | 0.5781          | 14.684      |
| 19/32            | 0.5938          | 15.081      |
| 39/64            | 0.6094          | 15.478      |
| 5/8              | 0.6250          | 15.875      |
|                  |                 |             |
| 41/64            | 0.6406          | 16.272      |
| 21/32            | 0.6563          | 16.669      |
| 43/64            | 0.6719          | 17.066      |
| 11/16            | 0.6875          | 17.463      |
|                  |                 |             |
| 45/64            | 0.7031          | 17.859      |
| 23/32            | 0.7188          | 18.256      |
| 47/64            | 0.7344          | 18.653      |
| 3/4              | 0.7500          | 19.050      |
|                  |                 |             |
| 49/64            | 0.7656          | 19.447      |
| 25/32            | 0.7813          | 19.844      |
| 51/64            | 0.7969          | 20.241      |
| 13/16            | 0.8125          | 20.638      |
|                  |                 |             |
| 53/64            | 0.8281          | 21.034      |
| 27/32            | 0.8438          | 21.431      |
| 55/64            | 0.8594          | 21.828      |
| 7/8              | 0.8750          | 22.225      |
|                  |                 |             |
| 57/64            | 0.8906          | 22.622      |
| 29/32            | 0.9063          | 23.019      |
| 59/64            | 0.9219          | 23.416      |
| 15/16            | 0.9375          | 23.813      |
|                  |                 |             |
| 61/64            | 0.9531          | 24.209      |
| 31/32            | 0.9688          | 24.606      |
| 63/64            | 0.9844          | 25.003      |
| 1"               | 1.0000          | 25.400      |

## **Glossary of Terms**

**Annealing** – Heating steel to an increased temperature of 1300-1550F, and then slowly cooling it to approximately 1100F, putting the metal in its softest state, and improving machinability and cold-working properties.

**A.S.T.M.** – Abbreviation for American Society for Testing Material. An organization for issuing standard specifications on materials, including metals and alloys.

**Brinell Hardness** – Steel's resistance to penetration is measured by pressing a 10mm steel ball into the surface of a sample under a load of 3,000kg. By measuring the diameter of the depression and evaluating the ratio of load to spherical area of the depression, the level of resistance can be obtained.

**Critical Temperature** – Temperature at which steel transforms from a solid state into a liquid.

**Ductility** – Property that allows cold metals to be mechanically deformed without breaking.

**Elongation** – An increase in length, usually expressed as a percentage of the original gauge length, which occurs before a metal is exposed to stress and cracked. This measures the ductility of the metal.

**Free Machining** – A type of steel that has been altered to increase machinability.

**Galvanizing** – Hot dipping a sheet of steel into molten zinc for a short time to prevent corrosion

**Hardness** – The level of metal's resistance to penetration.

**Heat** – The amount of steel produced by one melting in a furnace.

**Heat Treatment** – Heating and cooling solid steel to obtain specialized physical properties and increase strength.

**High Strength, Low Alloy Steels** – These steels with strengths greater than that of structural carbon steels do not require a heat treatment.

**Kerf** – The piece of steel cut out and lost through processing. Depending on the kind of material and process used, the amount of product lost will vary.



---

## **Glossary of Terms**

*(continued)*

**Level** – To flatten coiled metal sheet or strip.

**Pickling** – The process of removing iron oxide from steel by bathing it in a time and temperature controlled solution of sulfuric acid. This removal of the iron oxide occurs when a gas formation under the scale causes it to flake off.

**Quenching** – Cooling steel quickly from a high temperature through the actions of liquids, gasses, or solids

**Rockwell Hardness (Test)** – A standard method for measuring the hardness of metals. The hardness is expressed as a number related to the depth of residual penetration of a steel ball or diamond cone (“braille”) after a minor load of 10 kilograms has been applied to hold the penetrator in position. This residual penetration is automatically registered on a dial when the major load is removed from the penetrator. Various dial readings combined with different major loads, give “scales” designated by letters varying from “A” to “H”, the “B” and “C” scales are most commonly used.

**Stress Relieving** – The process of heating steel to a temperature of between 300-1300F, and then cooling by air to reduce stress.

**Tempering** – Heat treatment obtained by reheating solid steel to a temperature beneath that of the critical range in order to gain stress relief and better ductility.

**Tensile Strength (also called ultimate strength)** – Breaking strength of a material when subjected to a tensile (stretching) force. Usually measured by placing a standard test piece in the jaws of a tensile machine, gradually separating the jaws, and measuring the stretching force necessary to break the test piece. Tensile strength is commonly expressed as pounds (or tons) per square inch of original cross section.

**Tolerance** – The upper and lower limits of range of deviation from the desired value that is accepted.

**Yield Strength** – Point at which material will not return to its original length or shape if stress is removed.

## Cutting




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10

# Cutting




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16




Figure 17




Figure 18




Figure 19




Figure 20

# Forming




Figure F-1




Figure F-2




Figure F-3




Figure F-4




Figure F-5

## Forming




Figure F-6




Figure F-7




Figure F-8




Figure F-9




Figure F-10

## Forming




Figure F-11




Figure F-12




Figure F-13




Figure F-14